

[Home](#) > [Products](#) > > [9FG1903-1](#) > [9FG1903AK-1LFT](#)
[Add to myIDT \[?\]](#)

You may also like...

## 9FG1903AK-1LFT

|                      |              |
|----------------------|--------------|
| <b>Category:</b>     |              |
| <b>Generic Part:</b> | 9FG1903-1    |
| <b>Market Group:</b> | PC CLOCK     |
| <b>Description:</b>  | PCIE BUGFFER |



### Parameters

|                                |                   |
|--------------------------------|-------------------|
| <b>Package</b>                 | VFQFPN 72 (NLG72) |
| <b>Speed</b>                   | NA                |
| <b>Temperature</b>             | C                 |
| <b>Voltage</b>                 | 3.3 V             |
| <b>Status</b>                  | Active            |
| <b>Sample</b>                  | No                |
| <b>Minimum Order Quantity</b>  | 2500              |
| <b>Factory Order Increment</b> | 2500              |

### Distributor Inventory

No Pricing information is available from our Distributors at this time.

### Documents

| Type                  | Title  | Size   | Revision Date |
|-----------------------|--|--------|---------------|
| Misc                  | PC Clocks Contact Info   | 61 KB  | 05/29/2007    |
| Product Change Notice | PCN# : A0701-02 Punch Singulation as Alternate Assembly Process for 10mm x 10mm VFQFP-N-72   | 514 KB | 01/30/2007    |
|                       | PCN# : A0701-02R1 Punch Singulation as Alternate Assembly Process for 10mm x 10mm VFQFP-N-72 and transfer Test facility from IDT Singapore to IDT Penang | 453 KB | 04/24/2007    |

### Package

|   |  |
|---|--|
| <b>Description</b>                      | VFQFP-N 10.0 X 10.0 X 0.9 MM - NO LEAD |
| <b>Class</b>                            | PLASTIC                                |
| <b>Moisture Sensitivity Level (MSL)</b> | 3                                      |
| <b>Category</b>                         | Green                                  |
| <b>Moisture Exposure Floor Life</b>     | 168 hrs. @ <30°C/60%RH                 |
| <b>Peak Reflow Temperature</b>          | 260°C                                  |
| <b>Rebake Conditions</b>                | 48 hrs.@125°C                          |
| <b>Length</b>                           | 10.0                                   |
| <b>Mark</b>                             | K                                      |
| <b>Width</b>                            | 10.0                                   |
| <b>Pitch</b>                            | 0.5                                    |
| <b>Thickness</b>                        | 1.0                                    |
| <b>Status</b>                           | Active                                 |