

DS3680 Quad Negative Voltage Relay Driver

General Description

The DS3680 is a quad high voltage negative relay driver designed to operate over wide ranges of supply voltage, common-mode voltage, and ambient temperature, with 50 mA sink capability. These drivers are intended for switching the ground end of loads which are directly connected to the negative supply, such as in telephone relay systems.

Since there may be considerable noise and IR drop between logic ground and negative supply ground in many applications, these drivers are designed to operate with a high common-mode range ($\pm 20V$ referenced to negative supply ground). Each driver has a common-mode range separate from the other drivers in the package, which permits input signals from more than one element of the system.

With low differential input current requirements (typically 100 μ A), these drivers are compatible with TTL, LS and CMOS logic. Differential inputs permit either inverting or non-inverting operation.

The driver outputs incorporate transient suppression clamp networks, which eliminate the need for external networks when used in applications of switching inductive loads. A failsafe feature is incorporated to ensure that, if the + IN input or both inputs are open, the driver will be OFF.

Features

- –10V to –60V operation
- Quad 50 mA sink capability
- TTL/LS/CMOS or voltage comparator input
- High input common-mode voltage range
- Very low input current
- Fail-safe disconnect feature
- Built-in output clamp diode

Connection Diagram



Top View Order Number DS3680M See NS Package Number M14A

Block Diagram



Truth Table

Differential Inputs	Outputs
V _{ID} ≥ 2V	On
$V_{ID} \le 0.8V$	Off
Open	Off

© 2008 National Semiconductor Corporation 5821

Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/ Distributors for availability and specifications.

Supply Voltage (GND to $V_{EE^{-}}$, and Any Pin)	–70V		
Positive Input Voltage (Input to GND)	20V		
Negative Input Voltage (Input to V_{EE})	–5V		
Differential Voltage (+ IN to - IN)	±20V		
Inductive Load	L _L ≤5h		
	I _L ≤50 mA		
Output Current	–100 mA		
Storage Temperature	–65°C to +150°C		
Maximum Power Dissipation (Note 2) at 25°C			

Electrical Characteristics (Notes 3, 4)

SO Package	1002 mW
Lead Temperature (Soldering, 4 seconds)	260°C

Recommended Operating Conditions

	Min	Мах	Unit s
Supply Voltage (GND to V _{EE-})	-10	-60	V
Input Voltage (Input to GND)	-20	20	V
Logic ON Voltage (+IN)			
Referenced to –IN	2	20	V
Logic OFF Voltage (+IN)			
Referenced to –IN	-20	0.8	V
Temperature Range	-25	+85	°C

Symbol	Parameter	Conditions	Min	Тур	Max	Units
V _{IH}	Logic "1" Input Voltage		2.0	1.3		V
V _{IL}	Logic "0" Input Voltage			1.3	0.8	V
I _{INH}	Logic "1" Input Current	$V_{IN} = 2V$		40	100	μΑ
				375	1000	μΑ
I _{INL}		$V_{IN} = 0.4V$ $V_{IN} = -7V$		-0.01 -1	-5 -100	μΑ μΑ
V _{OL}	Output ON Voltage	I _{OL} = 50 mA		-1.6	-2.1	V
I _{OFF}	Output Leakage	V _{OUT} = V _{EE} .		-2	-100	μA
I _{FS}	Fail-Safe Output Leakage	V _{OUT} = V _{EE} - (Inputs Open)		-2	-100	μΑ
I _{LC}	Output Clamp Leakage Current	V _{OUT} = GND		2	100	μA
V _C	Output Clamp Voltage	$I_{CLAMP} = -50 \text{ mA}$ Referenced to V_{EE^-}		-2	-1.2	v
V _P	Positive Output Clamp Voltage	I _{CLAMP} = 50 mA Referenced to GND		0.9	1.2	v
I _{EE(ON)}	ON Supply Current	All Drivers ON		-2	-4.4	mA
I _{EE(OFF)}	OFF Supply Current	All Drivers OFF		-1	-100	μA
t _{PD(ON)}	Propagation Delay to Driver ON	$L = 1h, R_{L} = 1k,$ $V_{IN} = 3V Pulse$		1	10	μs
t _{PD(OFF)}	Propagation Delay to Driver OF	$L = 1h, R_L = 1k,$ $V_{IN} = 3V$ Pulse		1	10	μs

Note 1: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. Except for "Operating Temperature Range", they are not meant to imply that the device should be operated at these limits. The table of "Electrical Characteristics" provides conditions for actual device operation.

Note 2: Derate SO package 8.02 mW/°C above 25°C.

Note 3: Unless otherwise specified, the min/max limits of the table of "Electrical Characteristics" apply within the range of the table of "Operating Conditions". All typical values are given for $V_{EE-} = 52V$, and $T_A = 25^{\circ}C$.

Note 4: All currents into device pins shown as positive, out of the device as negative. All voltages are referenced to ground unless otherwise noted.

www.national.com

Schematic Diagrams







Physical Dimensions inches (millimeters) unless otherwise noted

DS3680



4

www.national.com



Notes

For more National Semiconductor product information and proven design tools, visit the following Web sites at:

Products		Design Support		
Amplifiers	www.national.com/amplifiers	WEBENCH® Tools	www.national.com/webench	
Audio	www.national.com/audio	App Notes	www.national.com/appnotes	
Clock and Timing	www.national.com/timing	Reference Designs	www.national.com/refdesigns	
Data Converters	www.national.com/adc	Samples	www.national.com/samples	
Interface	www.national.com/interface	Eval Boards	www.national.com/evalboards	
LVDS	www.national.com/lvds	Packaging	www.national.com/packaging	
Power Management	www.national.com/power	Green Compliance	www.national.com/quality/green	
Switching Regulators	www.national.com/switchers	Distributors	www.national.com/contacts	
LDOs	www.national.com/ldo	Quality and Reliability	www.national.com/quality	
LED Lighting	www.national.com/led	Feedback/Support	www.national.com/feedback	
Voltage Reference	www.national.com/vref	Design Made Easy	www.national.com/easy	
PowerWise® Solutions	www.national.com/powerwise	Solutions	www.national.com/solutions	
Serial Digital Interface (SDI)	www.national.com/sdi	Mil/Aero	www.national.com/milaero	
Temperature Sensors	www.national.com/tempsensors	Solar Magic®	www.national.com/solarmagic	
Wireless (PLL/VCO)	www.national.com/wireless	Analog University®	www.national.com/AU	

THE CONTENTS OF THIS DOCUMENT ARE PROVIDED IN CONNECTION WITH NATIONAL SEMICONDUCTOR CORPORATION ("NATIONAL") PRODUCTS. NATIONAL MAKES NO REPRESENTATIONS OR WARRANTIES WITH RESPECT TO THE ACCURACY OR COMPLETENESS OF THE CONTENTS OF THIS PUBLICATION AND RESERVES THE RIGHT TO MAKE CHANGES TO SPECIFICATIONS AND PRODUCT DESCRIPTIONS AT ANY TIME WITHOUT NOTICE. NO LICENSE, WHETHER EXPRESS, IMPLIED, ARISING BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT.

TESTING AND OTHER QUALITY CONTROLS ARE USED TO THE EXTENT NATIONAL DEEMS NECESSARY TO SUPPORT NATIONAL'S PRODUCT WARRANTY. EXCEPT WHERE MANDATED BY GOVERNMENT REQUIREMENTS, TESTING OF ALL PARAMETERS OF EACH PRODUCT IS NOT NECESSARILY PERFORMED. NATIONAL ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR BUYER PRODUCT DESIGN. BUYERS ARE RESPONSIBLE FOR THEIR PRODUCTS AND APPLICATIONS USING NATIONAL COMPONENTS. PRIOR TO USING OR DISTRIBUTING ANY PRODUCTS THAT INCLUDE NATIONAL COMPONENTS, BUYERS SHOULD PROVIDE ADEQUATE DESIGN, TESTING AND OPERATING SAFEGUARDS.

EXCEPT AS PROVIDED IN NATIONAL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, NATIONAL ASSUMES NO LIABILITY WHATSOEVER, AND NATIONAL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY RELATING TO THE SALE AND/OR USE OF NATIONAL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS PRIOR WRITTEN APPROVAL OF THE CHIEF EXECUTIVE OFFICER AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

Life support devices or systems are devices which (a) are intended for surgical implant into the body, or (b) support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in a significant injury to the user. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system or to affect its safety or effectiveness.

National Semiconductor and the National Semiconductor logo are registered trademarks of National Semiconductor Corporation. All other brand or product names may be trademarks or registered trademarks of their respective holders.

Copyright© 2008 National Semiconductor Corporation

For the most current product information visit us at www.national.com

R

National Semiconductor Americas Technical Support Center Email: support@nsc.com Tel: 1-800-272-9959 National Semiconductor Europe Technical Support Center Email: europe.support@nsc.com German Tel: +49 (0) 180 5010 771 English Tel: +44 (0) 870 850 4288 National Semiconductor Asia Pacific Technical Support Center Email: ap.support@nsc.com National Semiconductor Japan Technical Support Center Email: jpn.feedback@nsc.com

www.national.com