



CLARE

TS120L Multifunction Telecom Switches



	TS120L	Units
Load Voltage	350	V
Load Current	120	mA
Max R _{ON}	35	Ω

Features

- Small 8 Pin DIP Package
- Low Drive Power Requirements (TTL/CMOS Compatible)
- No Moving Parts
- High Reliability
- Arc-Free With No Snubbing Circuits
- 3750V_{RMS} Input/Output Isolation
- No EMI/RFI Generation
- Machine Insertable, Wave Solderable
- Surface Mount and Tape & Reel Versions Available

Applications

- Telecommunications
 - Telecom Switching
 - Tip/Ring Circuits
 - Modem Switching (Laptop, Notebook, Pocket Size)
 - Hookswitch
 - Dial Pulsing
 - Ground Start
 - Ringer Injection
- Instrumentation
 - Multiplexers
 - Data Acquisition
 - Electronic Switching
 - I/O Subsystems
 - Meters (Watt-Hour, Water, Gas)
- Medical Equipment-Patient/Equipment Isolation
- Security
- Aerospace
- Industrial Controls

Description

TS120L is a 350V, 120mA, 35Ω 1-Form-A relay with an optocoupler in a single package. It is a more cost effective solution for telecom applications that do not require a high sensitivity relay.

Approvals


- UL Recognized: File Number E76270
- CSA Certified: File Number LR 43639-10
- Certified to:
 - EN 60950
 - EN 41003
 - IEC950
 - AS/NZS 3260

Ordering Information

Part #	Description
TS120L	8 Pin DIP (50/Tube)
TS120PL	8 Pin Flatpack (50/Tube)
TS120PLTR	8 Pin Flatpack (1000/Reel)
TS120LS	8 Pin Surface Mount (50/Tube)
TS120LSTR	8 Pin Surface Mount (1000/Reel)

Pin Configuration

TS120L Pinout



Absolute Maximum Ratings (@ 25° C)

Parameter	Min	Typ	Max	Units
Input Power Dissipation	-	-	150 ¹	mW
Input Control Current	-	-	50	mA
Peak (10ms)	-	-	1	A
Reverse Input Voltage	-	-	5	V
Relay Blocking Voltage	-	-	350	V
Total Power Dissipation	-	-	800 ²	mW
Isolation Voltage Input to Output	3750	-	-	V_{RMS}
Operational Temperature	-40	-	+85	°C
Storage Temperature	-40	-	+125	°C
Soldering Temperature DIP Package	-	-	+260	°C
Flatpack/Surface Mount Package (10 Seconds Max.)	-	-	+220	°C

¹ Derate Linearly 1.33 mw/°C² Derate Linearly 6.67 mw/°C

Absolute Maximum Ratings are stress ratings. Stresses in excess of these ratings can cause permanent damage to the device. Functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this data sheet is not implied. Exposure of the device to the absolute maximum ratings for an extended period may degrade the device and effect its reliability.













Electrical Characteristics

Parameter	Conditions	Symbol	Min	Typ	Max	Units
Relay Portion (Pins 7, 8) Output Characteristics @ 25°C						
Load Current (Continuous)	-	I_L	-	-	120	mA
Peak Load Current	10ms	I_{LPK}	-	-	350	mA
On-Resistance	$I_F=120\text{mA}$	R_{ON}	-	-	35	Ω
Off-State Leakage Current	$V_L=350\text{V}$	I_{LEAK}	-	-	1	μA
Switching Speeds						
Turn-On	$I_F=5\text{mA}$, $V_L=10\text{V}$	T_{ON}	-	-	2.5	ms
Turn-Off	$I_F=5\text{mA}$, $V_L=10\text{V}$	T_{OFF}	-	-	2.5	ms
Output Capacitance	50V; f=1MHz	C_{OUT}	-	25	-	pF
Current Limit	$I_F=5\text{mA}$	I_{CL}	130	170	210	mA
Relay Portion (Pins 1, 2) Input Characteristics @ 25°C						
Input Control Current	$I_L=120\text{mA}$	I_F	5	-	50	mA
Input Dropout Current	-	I_F	0.4	0.7	-	mA
Input Voltage Drop	$I_F=5\text{mA}$	V_F	0.9	1.2	1.4	V
Reverse Input Voltage	-	V_R	-	-	5	V
Reverse Input Current	$V_R=5\text{V}$	I_R	-	-	10	μA












Electrical Characteristics (Continued)

Parameter	Conditions	Symbol	Min	Typ	Max	Units
Detector Portion (Pins 3, 4)						
Output Characteristics @ 25°C						
Phototransistor Blocking Voltage	$I_C=10\mu A$	BV_{CEO}	20	50	-	V
Phototransistor Output Current	$V_{CE}=5V, I_F=0mA$	I_{CEO}	-	100	1000	nA
Saturation Voltage	$I_C=0.15mA, I_F=.05mA$	V_{SAT}	-	0.5	0.8	V
Current Transfer Ratio	$I_F=0.05mA, V_{CE}=0.8V$	CTR	300	1000	-	%
Detector Portion (Pins 5, 6)						
Input Characteristics @ 25°C						
Input Control Current	$I_C=2mA, V_{CE}=0.5V$	I_F	2	1	100	mA
Input Voltage Drop	$I_F=5mA$	V_F	0.9	1.2	1.4	V
Input to Output Capacitance (Relay Only)	-	$C_{I/O}$	-	3	-	pF
Capacitance Input to Output	-	-	-	3	-	pF
Input to Output Isolation	-	$V_{I/O}$	3750	-	-	V _{RM}

PERFORMANCE DATA*









* The Performance data shown in the graphs above is typical of device performance. For guaranteed parameters not indicated in the written specifications, please contact our application department.

PERFORMANCE DATA*


* The Performance data shown in the graphs above is typical of device performance. For guaranteed parameters not indicated in the written specifications, please contact our application department.


MECHANICAL DIMENSIONS

8 Pin DIP Through Hole (Standard)

**PC Board Pattern
(Top View)**

8 Pin DIP Surface Mount ("S" Suffix)

**PC Board Pattern
(Top View)**

8 Pin Flatpack ("P" Suffix)

**PC Board Pattern
(Top View)**



Dimensions
mm
(inches)

MECHANICAL DIMENSIONS

Tape and Reel Packaging for 8 Pin Surface Mount Package



Tape and Reel Packaging for 8 Pin Flatpack Package



Dimensions
mm
(inches)



CLARE

For additional information please visit our website at: www.clare.com

Clare, Inc. makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Neither circuit patent licenses nor indemnity are expressed or implied. Except as set forth in Clare's Standard Terms and Conditions of Sale, Clare, Inc. assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including, but not limited to, the implied warranty of merchantability, fitness for a particular purpose, or infringement of any intellectual property right.

The products described in this document are not designed, intended, authorized or warranted for use as components in systems intended for surgical implant into the body, or in other applications intended to support or sustain life, or where malfunction of Clare's product may result in direct physical harm, injury, or death to a person or severe property or environmental damage. Clare, Inc. reserves the right to discontinue or make changes to its products at any time without notice.

Specification: DS-TS120L-R1.0
©Copyright 2002, Clare, Inc.
All rights reserved. Printed in USA.
6/21/02