

# E-Series Coupler

## 5 - 40 MHz

# EMDC-17-2-75

V3.00

### Features

- Coupling: +17 dB Typical
- Surface Mount

### Specifications @ 25°C

Frequency Range	5 - 40 MHz	
Coupling	17 ±1 dB Nominal	
5 - 40 MHz		
Main Line Loss	Typical	Maximum
5 - 40 MHz	0.45 dB	0.8 dB
Directivity	Typical	Minimum
5 - 40 MHz	28 dB	22 dB
Return Loss	Typical	Minimum
	25 dB	20 dB

### Operating Characteristics

Impedance	75 Ohms Nominal
-----------	-----------------


### Ordering Information

Part No.	Packaging
EMDC-17-2-75	Tube
EMDC-17-2-75TR	Forward Tape & Reel

### Absolute Maximum Ratings

Parameter	Absolute Maximum
RF Power	250 mW
DC Current	30 mA
Operating/Storage Temp.	-20°C to +85°C

### SM-22



### Pin Configuration

Function	Pin. No.
Input	5
Output	1
Coupled	4
Ground	2
External 75 Ohms	3

Specifications Subject to Change Without Notice.

S 1132 A

**M/A-COM, Inc.**

**1**

North America: Tel. (800) 366-2266 ■ Asia/Pacific: Tel. +81 (03) 3226-1671 ■ Europe: Tel. +44 (1344) 869 595  
Fax (800) 618-8883 Fax +81 (03) 3226-1451 Fax +44 (1344) 300 020