



8XC196KD/8XC196KD20 COMMERCIAL CHMOS MICROCONTROLLER

87C196KD/32 Kbytes of On-Chip OTPROM
83C196KD/32 Kbytes of ROM

- 16 MHz and 20 MHz Available
- 1000 Byte Register RAM
- Register-to-Register Architecture
- 28 Interrupt Sources/16 Vectors
- Peripheral Transaction Server
- 1.4 μ s 16 x 16 Multiply (20 MHz)
- 2.4 μ s 32/16 Divide (20 MHz)
- Powerdown and Idle Modes
- Five 8-Bit I/O Ports
- 16-Bit Watchdog Timer
- Dynamically Configurable 8-Bit or 16-Bit Buswidth
- Full Duplex Serial Port
- High Speed I/O Subsystem
- 16-Bit Timer
- 16-Bit Up/Down Counter with Capture
- 3 Pulse-Width-Modulated Outputs
- Four 16-Bit Software Timers
- 8- or 10-Bit A/D Converter with Sample/Hold
- $\overline{\text{HOLD}}/\overline{\text{HLDA}}$ Bus Protocol
- OTP One-Time Programmable Version
- Extended Temperature Available

The 8XC196KD 16-bit microcontroller is a high performance member of the MCS[®] 96 microcontroller family. The 8XC196KD is an enhanced 80C196KC device with 1000 bytes RAM, 16 MHz operation and an optional 32 Kbytes of ROM/EPROM. Intel's CHMOS III process provides a high performance processor along with low power consumption.

The 8XC196KD has a maximum guaranteed frequency of 16 MHz. The 8XC196KD20 has a maximum guaranteed frequency of 20 MHz. Unless otherwise noted, all references to the 8XC196KD also refer to the 8XC196KD20.

Four high-speed capture inputs are provided to record times when events occur. Six high-speed outputs are available for pulse or waveform generation. The high-speed output can also generate four software timers or start an A/D conversion. Events can be based on the timer or up/down counter.

With the commercial (standard) temperature option, operational characteristics are guaranteed over the temperature range of the 0°C to +70°C. With the extended (express) temperature range option, operational characteristics are guaranteed over the temperature range of -40°C to +85°C. Unless otherwise noted, the specifications are the same for both options.

See the packaging information for extended temperature designators.

*Other brands and names may be claimed as the property of others.
Information in this document is provided in connection with Intel products. Intel assumes no liability whatsoever, including infringement of any patent or copyright, for sale and use of Intel products except as provided in Intel's Terms and Conditions of Sale for such products. Intel retains the right to make changes to these specifications at any time, without notice. Microcomputer Products may have minor variations to this specification known as errata.

COPYRIGHT © INTEL CORPORATION, 2004

July 2004

Order Number: 272146-006




Figure 1. 8XC196KD Block Diagram

87C196KD ENHANCED FEATURE SET OVER THE 87C196KC

1. The 87C196KD has twice the RAM and twice the OTPROM space of the 87C196KC.
2. The vertical windowing scheme has been extended to allow all 1000 bytes of register RAM to be windowed into the lower register file.




Figure 2. 87C196KD New SFR Bit (CLKOUT Disable)

8XC196KD VERTICAL WINDOWING MAP

Table 1. 128-Byte Windows

| Address to Remap | Device Series | WSR Contents |
|------------------|---------------|------------------|
| 0380H | KD | X001 0111B = 17H |
| 0300H | KD | X001 0110B = 16H |
| 0280H | KD | X001 0101B = 15H |
| 0200H | KD | X001 0100B = 14H |
| 0180H | KC, KD | X001 0011B = 13H |
| 0100H | KC, KD | X001 0010B = 12H |
| 0080H | KC, KD | X001 0001B = 11H |
| 0000H | KC, KD | X001 0000B = 10H |

Window in Lower Register File: 80H±FFH

Table 2. 64-Byte Windows

| Address to Remap | Device Series | WSR Contents |
|------------------|---------------|------------------|
| 03C0H | KD | X010 1111B = 2FH |
| 0380H | KD | X010 1110B = 2EH |
| 0340H | KD | X010 1101B = 2DH |
| 0300H | KD | X010 1100B = 2CH |
| 02C0H | KD | X010 1011B = 2BH |
| 0280H | KD | X010 1010B = 2AH |
| 0240H | KD | X010 1001B = 29H |
| 0200H | KD | X010 1000B = 28H |
| 01C0H | KC, KD | X010 0111B = 27H |
| 0180H | KC, KD | X010 0110B = 26H |
| 0140H | KC, KD | X010 0101B = 25H |
| 0100H | KC, KD | X010 0100B = 24H |
| 00C0H | KC, KD | X010 0011B = 23H |
| 0080H | KC, KD | X010 0010B = 22H |
| 0040H | KC, KD | X010 0001B = 21H |
| 0000H | KC, KD | X010 0000B = 20H |

Window in Lower Register File: C0H±FFH

Table 3. 32-Byte Windows

| Address to Remap | Device Series | WSR Contents |
|------------------|---------------|------------------|
| 03E0H | KD | X101 1111B = 5FH |
| 03C0H | KD | X101 1110B = 5EH |
| 03A0H | KD | X101 1101B = 5DH |
| 0380H | KD | X101 1100B = 5CH |
| 0360H | KD | X101 1011B = 5BH |
| 0340H | KD | X101 1010B = 5AH |
| 0320H | KD | X101 1001B = 59H |
| 0300H | KD | X101 1000B = 58H |
| 02E0H | KD | X101 0111B = 57H |
| 02C0H | KD | X101 0110B = 56H |
| 02A0H | KD | X101 0101B = 55H |
| 0280H | KD | X101 0100B = 54H |
| 0260H | KD | X101 0011B = 53H |
| 0240H | KD | X101 0010B = 52H |
| 0220H | KD | X101 0001B = 51H |
| 0200H | KD | X101 0000B = 50H |
| 01E0H | KC, KD | X100 1111B = 4FH |
| 01C0H | KC, KD | X100 1110B = 4EH |
| 01A0H | KC, KD | X100 1101B = 4DH |
| 0180H | KC, KD | X100 1100B = 4CH |
| 0160H | KC, KD | X100 1011B = 4BH |
| 0140H | KC, KD | X100 1010B = 4AH |
| 0120H | KC, KD | X100 1001B = 49H |
| 0100H | KC, KD | X100 1000B = 48H |
| 00E0H | KC, KD | X100 0111B = 47H |
| 00C0H | KC, KD | X100 0110B = 46H |
| 00A0H | KC, KD | X100 0101B = 45H |
| 0080H | KC, KD | X100 0100B = 44H |
| 0060H | KC, KD | X100 0011B = 43H |
| 0040H | KC, KD | X100 0010B = 42H |
| 0020H | KC, KD | X100 0001B = 41H |
| 0000H | KC, KD | X100 0000B = 40H |

Window in Lower Register File: E0H±FFH

PROCESS INFORMATION

This device is manufactured on PX29.5 or PX29.9, a CHMOS III process. Additional process and reliability information is available in the Intel® Quality System Handbook:
<http://developer.intel.com/design/quality/quality.htm>




Figure 3. The 8XC196KD Family Nomenclature

Table 4. Thermal Characteristics

| Package Type | θ_{ja} | θ_{jc} |
|--------------|---------------|---------------|
| PLCC | 35°C/W | 13°C/W |
| QFP | 56°C/W | 12°C/W |
| SQFP | 68°C/W | 15.5°C/W |

All thermal impedance data is approximate for static air conditions at 1W of power dissipation. Values will change depending on operation conditions and application. See the Intel *Packaging Handbook* (order number 240800) for a description of Intel's thermal impedance test methodology.

Table 5. 8XC196KD Memory Map

| Description | Address |
|-----------------------------------------------------------|------------------|
| External Memory or I/O | 0FFFFH 0A000H |
| Internal ROM/OTPROM or External Memory (Determined by EA) | 9FFFFH 2080H |
| Reserved. Must contain FFH. (Note 5) | 207FH 205EH |
| PTS Vectors | 205DH 2040H |
| Upper Interrupt Vectors | 203FH 2030H |
| ROM/OTPROM Security Key | 202FH 2020H |
| Reserved. Must contain FFH. (Note 5) | 201FH 201AH |
| Reserved. Must Contain 20H (Note 5) | 2019H |
| CCB | 2018H |
| Reserved. Must contain FFH. (Note 5) | 2017H 2014H |
| Lower Interrupt Vectors | 2013H 2000H |
| Port 3 and Port 4 | 1FFFFH 1FFE0H |
| External Memory | 1FFDH 0400H |
| 1000 Bytes Register RAM (Note 1) | 03FFFH 0018H |
| CPU SFR's (Notes 1, 3) | 0017H 0000H |

NOTES:

- Code executed in locations 0000H to 03FFFH will be forced external.
- Reserved memory locations must contain 0FFH unless noted.
- Reserved SFR bit locations must contain 0.
- Refer to 8XC196KC for SFR descriptions.
- WARNING:** Reserved memory locations must not be written or read. The contents and/or function of these locations may change with future revisions of the device. Therefore, a program that relies on one or more of these locations may not function properly.






Figure 4. 68-Pin PLCC Package




Figure 5. 80-Pin QFP Package




Figure 6. 80-Pin SQFP Package

PIN DESCRIPTIONS

| Symbol | Name and Function |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| V _{CC} | Main supply voltage (5V). |
| V _{SS} | Digital circuit ground (0V). There are multiple V _{SS} pins, all of which must be connected. |
| V _{REF} | Reference voltage for the A/D converter (5V). V _{REF} is also the supply voltage to the analog portion of the A/D converter and the logic used to read Port 0. Must be connected for A/D and Port 0 to function. |
| ANGND | Reference ground for the A/D converter. Must be held at nominally the same potential as V _{SS} . |
| V _{PP} | Timing pin for the return from powerdown circuit. This pin also supplies the programming voltage on the EPROM device. |
| XTAL1 | Input of the oscillator inverter and of the internal clock generator. |
| XTAL2 | Output of the oscillator inverter. |
| CLKOUT | Output of the internal clock generator. The frequency of CLKOUT is 1/2 the oscillator frequency. |
| RESET | Reset input and open drain output. |
| BUSWIDTH | Input for buswidth selection. If CCR bit 1 is a one, this pin selects the bus width for the bus cycle in progress. If BUSWIDTH is a 1, a 16-bit bus cycle occurs. If BUSWIDTH is a 0 an 8-bit cycle occurs. If CCR bit 1 is a 0, the bus is always an 8-bit bus. |
| NMI | A positive transition causes a vector through 203EH. |
| INST | Output high during an external memory read indicates the read is an instruction fetch. INST is valid throughout the bus cycle. INST is activated only during external memory accesses and output low for a data fetch. |
| EA | Input for memory select (External Access). EA equal high causes memory accesses to locations 2000H through 9FFFH to be directed to on-chip ROM/E PROM. EA equal low causes accesses to those locations to be directed to off-chip memory. Also used to enter programming mode. |
| ALE/ADV | Address Latch Enable or Address Valid output, as selected by CCR. Both pin options provide a signal to demultiplex the address from the address/data bus. When the pin is ADV, it goes inactive high at the end of the bus cycle. ALE/ADV is activated only during external memory accesses. |
| RD | Read signal output to external memory. RD is activated only during external memory reads. |
| WR/WRL | Write and Write Low output to external memory, as selected by the CCR. WR will go low for every external write, while WRL will go low only for external writes where an even byte is being written. WR/WRL is activated only during external memory writes. |
| BHE/WRH | Bus High Enable or Write High output to external memory, as selected by the CCR. BHE will go low for external writes to the high byte of the data bus. WRH will go low for external writes where an odd byte is being written. BHE/WRH is activated only during external memory writes. |
| READY | Ready input to lengthen external memory cycles, for interfacing to slow or dynamic memory, or for bus sharing. When the external memory is not being used, READY has no effect. |
| HSI | Inputs to High Speed Input Unit. Four HSI pins are available: HSI.0, HSI.1, HSI.2 and HSI.3. Two of them (HSI.2 and HSI.3) are shared with the HSO Unit. |
| HSO | Outputs from High Speed Output Unit. Six HSO pins are available: HSO.0, HSO.1, HSO.2, HSI.3, HSO.4 and HSO.5. Two of them (HSO.4 and HSO.5) are shared with the HSI Unit. |



PIN DESCRIPTIONS (Continued)

| Symbol | Name and Function |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Port 0 | 8-bit high impedance input-only port. These pins can be used as digital inputs and/or as analog inputs to the on-chip A/D converter. |
| Port 1 | 8-bit quasi-bidirectional I/O port. |
| Port 2 | 8-bit multi-functional port. All of its pins are shared with other functions in the 8XC196KD. Pins 2.6 and 2.7 are quasi-bidirectional. |
| Ports 3 and 4 | 8-bit bidirectional I/O ports with open drain outputs. These pins are shared with the multiplexed address/data bus which has strong internal pullups. |
| $\overline{\text{HOLD}}$ | Bus Hold input requesting control of the bus. |
| $\overline{\text{HLDA}}$ | Bus Hold acknowledge output indicating release of the bus. |
| $\overline{\text{BREQ}}$ | Bus Request output activated when the bus controller has a pending external memory cycle. |
| PMODE | Determines the EPROM programming mode. |
| $\overline{\text{PACT}}$ | A low signal in Auto Programming mode indicates that programming is in process. A high signal indicates programming is complete. |
| $\overline{\text{PALE}}$ | A falling edge in Slave Programming Mode and Auto Configuration Byte Programming Mode indicates that ports 3 and 4 contain valid programming address/command information (input to slave). |
| $\overline{\text{PROG}}$ | A falling edge in Slave Programming Mode indicates that ports 3 and 4 contain valid programming data (input to slave). |
| PVER | A high signal in Slave Programming Mode and Auto Configuration Byte Programming Mode indicates the byte programmed correctly. |
| CPVER | Cummulative Program Output Verification. Pin is high if all locations have programmed correctly since entering a programming mode. |
| $\overline{\text{AINC}}$ | Auto Increment. Active low input enables the auto increment mode. Auto increment allows reading or writing sequential EPROM locations without address transactions across the PBUS for each read or write. |

ELECTRICAL CHARACTERISTICS

ABSOLUTE MAXIMUM RATINGS*

| | |
|------------------------------------|--------------------------------|
| Ambient Temperature | |
| Under Bias..... | – 55°C to +125°C |
| Storage Temperature..... | – 65°C to +150°C |
| Voltage On Any Pin to V_{SS} | |
| Except EA and V_{PP} | – 0.5V to +7.0V ⁽¹⁾ |
| Voltage from \overline{EA} or | |
| V_{PP} to V_{SS} or ANGND..... | – 0.5V to +13.00V |
| Power Dissipation..... | 1.5W ⁽²⁾ |

NOTES:

1. This includes V_{PP} and \overline{EA} on ROM or CPU only devices.
2. Power dissipation is based on package heat transfer limitations, not device power consumption.

NOTICE: This data sheet contains information on products in the sampling and initial production phases of development. It is valid for the devices indicated in the revision history. The specifications are subject to change without notice.

**WARNING: Stressing the device beyond the "Absolute Maximum Ratings" may cause permanent damage. These are stress ratings only. Operation beyond the "Operating Conditions" is not recommended and extended exposure beyond the "Operating Conditions" may affect device reliability.*

OPERATING CONDITIONS

| Symbol | Description | Min | Max | Units |
|-----------|--------------------------------------------------------|----------------|----------------|------------------|
| T_A | Ambient Temperature Under Bias Commercial Temp. | 0 | +70 | °C |
| T_A | Ambient Temperature Under Bias Extended Temp. | -40 | +85 | °C |
| V_{CC} | Digital Supply Voltage | 4.50 | 5.50 | V |
| V_{REF} | Analog Supply Voltage | 4.00 | 5.50 | V |
| ANGND | Analog Ground Voltage | $V_{SS} - 0.4$ | $V_{SS} + 0.4$ | V ⁽¹⁾ |
| F_{OSC} | Oscillator Frequency (8XC196KD) | 8 | 16 | MHz |
| F_{OSC} | Oscillator Frequency (8XC196KD20) | 8 | 20 | MHz |

NOTE:

1. ANGND and V_{SS} should be nominally at the same potential.

DC CHARACTERISTICS (Over Specified Operating Conditions)

| Symbol | Description | Min | Max | Units | Test Conditions |
|-----------|------------------------------------------------------------|----------------------------------------------------|--------------------|-------------|----------------------------------------------------------------------|
| V_{IL} | Input Low Voltage | –0.5 | 0.8 | V | |
| V_{IH} | Input High Voltage (Note 1) | $0.2 V_{CC} + 1.0$ | $V_{CC} + 0.5$ | V | |
| V_{HYS} | Hysteresis on \overline{RESET} | 300 | | mV | $V_{CC} = 5.0V$ |
| V_{IH1} | Input High Voltage on XTAL 1 | $0.7 V_{CC}$ | $V_{CC} + 0.5$ | V | |
| V_{IH2} | Input High Voltage on RESET | 2.2 | $V_{CC} + 0.5$ | V | |
| V_{OL} | Output Low Voltage | | 0.3 0.45 1.5 | V V V | $I_{OL} = 200 \mu A$ $I_{OL} = 2.8 mA$ $I_{OL} = 7 mA$ |
| V_{OL1} | Output Low Voltage in RESET on P2.5 (Note 2) | | 0.8 | V | $I_{OL} = +0.4 mA$ |
| V_{OH} | Output High Voltage (Standard Outputs) (Note 4) | $V_{CC} - 0.3$ $V_{CC} - 0.7$ $V_{CC} - 1.5$ | | V V V | $I_{OH} = -200 \mu A$ $I_{OH} = -3.2 mA$ $I_{OH} = -7 mA$ |
| V_{OH1} | Output High Voltage (Quasi-bidirectional Outputs) (Note 3) | $V_{CC} - 0.3$ $V_{CC} - 0.7$ $V_{CC} - 1.5$ | | V V V | $I_{OH} = -10 \mu A$ $I_{OH} = -30 \mu A$ $I_{OH} = -60 \mu A$ |


DC CHARACTERISTICS (Over Specified Operating Conditions) (Continued)

| Symbol | Description | Min | Typ | Max | Units | Test Conditions |
|------------|---------------------------------------------------------------------------------------------------------------------------|------|-----|----------|----------|------------------------------------------------------|
| I_{OH1} | Logical 1 Output Current in Reset on P2.0. Do not exceed this or device may enter test modes. | -0.8 | | | mA | $V_{IH} = V_{CC} - 1.5V$ |
| I_{IL2} | Logical 0 Input Current in Reset on P2.0. Maximum current that must be sunk by external device to ensure test mode entry. | | | -12.0 | mA | $V_{IN} = 0.45V$ |
| I_{IH1} | Logical 1 Input Current. Maximum current that external device must source to initiate NMI. | | | +200 | μA | $V_{IN} = 2.4V$ |
| I_{LI} | Input Leakage Current (Std. Inputs) (Note 5) | | | ± 10 | μA | $0 < V_{IN} < V_{CC} - 0.3V$ |
| I_{LI1} | Input Leakage Current (Port 0) | | | ± 3 | μA | $0 < V_{IN} < V_{REF}$ |
| I_{TL} | 1 to 0 Transition Current (QBD Pins) | | | -650 | μA | $V_{IN} = 2.0V$ |
| I_{IL} | Logical 0 Input Current (QBD Pins) | | | -70 | μA | $V_{IN} = 0.45V$ |
| I_{IL1} | AD Bus in Reset | | | -70 | μA | $V_{IN} = 0.45V$ |
| I_{CC} | Active Mode Current in Reset (8XC196KD) | | 65 | 75 | mA | XTAL1 = 16 MHz $V_{CC} = V_{PP} = V_{REF} = 5.5V$ |
| I_{CC} | Active Mode Current in Reset (8XC196KD20) | | 80 | 92 | mA | XTAL1 = 20 MHz $V_{CC} = V_{PP} = V_{REF} = 5.5V$ |
| I_{IDLE} | Idle Mode Current (8XC196KD) | | 17 | 25 | mA | XTAL1 = 16 MHz $V_{CC} = V_{PP} = V_{REF} = 5.5V$ |
| I_{IDLE} | Idle Mode Current (8XC196KD20) | | 21 | 30 | mA | XTAL1 = 20 MHz $V_{CC} = V_{PP} = V_{REF} = 5.5V$ |
| I_{PD} | Powerdown Mode Current | | 8 | 15 | μA | $V_{CC} = V_{PP} = V_{REF} = 5.5V$ |
| I_{REF} | A/D Converter Reference Current | | 2 | 5 | mA | $V_{CC} = V_{PP} = V_{REF} = 5.5V$ |
| R_{RST} | Reset Pullup Resistor | 6K | | 65K | Ω | $V_{CC} = 5.5V, V_{IN} = 4.0V$ |
| C_S | Pin Capacitance (Any Pin to V_{SS}) | | | 10 | pF | |

NOTES:

- All pins except RESET and XTAL1.
- Violating these specifications in Reset may cause the part to enter test modes.
- QBD (Quasi-bidirectional) pins include Port 1, P2.6 and P2.7.
- Standard Outputs include $AD0\pm15$, \overline{RD} , \overline{WR} , ALE, \overline{BHE} , INST, HSO pins, PWM/P2.5, CLKOUT, RESET, Ports 3 and 4, TXD/P2.0 and RXD (in serial mode 0). The V_{OH} specification is not valid for RESET. Ports 3 and 4 are open-drain outputs.
- Standard Inputs include HSI pins, READY, BUSWIDTH, RXD/P2.1, EXTINT/P2.2, T2CLK/P2.3 and T2RST/P2.4.
- Maximum current per pin must be externally limited to the following values if V_{OL} is held above 0.45V or V_{OH} is held below $V_{CC} - 0.7V$:
 - I_{OL} on Output pins: 10 mA
 - I_{OH} on quasi-bidirectional pins: self limiting
 - I_{OH} on Standard Output pins: 10 mA
- Maximum current per bus pin (data and control) during normal operation is ± 3.2 mA.
- During normal (non-transient) conditions the following total current limits apply:

| | | |
|------------------------------------------------|------------------|---------------------------|
| Port 1, P2.6 | I_{OL} : 29 mA | I_{OH} is self limiting |
| HSO, P2.0, RXD, \overline{RESET} | I_{OL} : 29 mA | I_{OH} : 26 mA |
| P2.5, P2.7, \overline{WR} , \overline{BHE} | I_{OL} : 13 mA | I_{OH} : 11 mA |
| $AD0\pm AD15$ | I_{OL} : 52 mA | I_{OH} : 52 mA |
| \overline{RD} , ALE, INST \pm CLKOUT | I_{OL} : 13 mA | I_{OH} : 13 mA |

Figure 7. I_{CC} and I_{IDLE} vs Frequency

AC CHARACTERISTICS

For use over specified operating conditions.

Test Conditions: Capacitive load on all pins = 100 pF, Rise and fall times = 10 ns, $F_{OSC} = 16/20$ MHz

The system must meet these specifications to work with the 80C196KD:

| Symbol | Description | Min | Max | Units | Notes |
|------------|--------------------------------------------|----------------|------------------|-------|----------|
| T_{AVYV} | Address Valid to READY Setup | | $2 T_{OSC} - 68$ | ns | |
| T_{YLYH} | Non READY Time | No upper limit | | ns | |
| T_{CLYX} | READY Hold after CLKOUT Low | 0 | $T_{OSC} - 30$ | ns | (Note 1) |
| T_{LLYX} | READY Hold after ALE Low | $T_{OSC} - 15$ | $2 T_{OSC} - 40$ | ns | (Note 1) |
| T_{AVGV} | Address Valid to Buswidth Setup | | $2 T_{OSC} - 68$ | ns | |
| T_{CLGX} | Buswidth Hold after CLKOUT Low | 0 | | ns | |
| T_{AVDV} | Address Valid to Input Data Valid | | $3 T_{OSC} - 55$ | ns | (Note 2) |
| T_{RLDV} | \overline{RD} Active to Input Data Valid | | $T_{OSC} - 22$ | ns | (Note 2) |
| T_{CLDV} | CLKOUT Low to Input Data Valid | | $T_{OSC} - 45$ | ns | |
| T_{RHDZ} | End of \overline{RD} to Input Data Float | | T_{OSC} | ns | |
| T_{RXDX} | Data Hold after \overline{RD} Inactive | 0 | | ns | |

NOTES:

- If max is exceeded, additional wait states will occur.
- If wait states are used, add $2 T_{OSC} * N$, where N = number of wait states.

AC CHARACTERISTICS (Continued)

For use over specified operating conditions.

 Test Conditions: Capacitive load on all pins = 100 pF, Rise and fall times = 10 ns, $F_{OSC} = 16/20$ MHz


The 80C196KD will meet these specifications:

| Symbol | Description | Min | Max | Units | Notes |
|-------------------|-----------------------------------------------------------|-----------------------|-----------------------|-------|----------|
| F _{XTAL} | Frequency on XTAL1 (8XC196KD) | 8 | 16 | MHz | (Note 1) |
| F _{XTAL} | Frequency on XTAL1 (8XC196KD20) | 8 | 20 | MHz | (Note 1) |
| T _{OSC} | I/F _{XTAL} (8XC196KD) | 62.5 | 125 | ns | |
| T _{OSC} | I/F _{XTAL} (8XC196KD20) | 50 | 125 | ns | |
| T _{XHCH} | XTAL1 High to CLKOUT High or Low | +20 | +110 | ns | |
| T _{CLCL} | CLKOUT Cycle Time | 2 T _{OSC} | | ns | |
| T _{CHCL} | CLKOUT High Period | T _{OSC} - 10 | T _{OSC} + 15 | ns | |
| T _{CLLH} | CLKOUT Falling Edge to ALE Rising | -5 | +15 | ns | |
| T _{LLCH} | ALE Falling Edge to CLKOUT Rising | -20 | +15 | ns | |
| T _{LHLH} | ALE Cycle Time | 4 T _{OSC} | | ns | (Note 4) |
| T _{LHLL} | ALE High Period | T _{OSC} - 10 | T _{OSC} + 10 | ns | |
| T _{AVLL} | Address Setup to ALE Falling Edge | T _{OSC} - 15 | | | |
| T _{LLAX} | Address Hold after ALE Falling Edge | T _{OSC} - 35 | | ns | |
| T _{LLRL} | ALE Falling Edge to \overline{RD} Falling Edge | T _{OSC} - 30 | | ns | |
| T _{RLCL} | \overline{RD} Low to CLKOUT Falling Edge | +4 | +30 | ns | |
| T _{RLRH} | \overline{RD} Low Period | T _{OSC} - 5 | | ns | (Note 4) |
| T _{RHLH} | \overline{RD} Rising Edge to ALE Rising Edge | T _{OSC} | T _{OSC} + 25 | ns | (Note 2) |
| T _{RLAZ} | \overline{RD} Low to Address Float | | +5 | ns | |
| T _{LLWL} | ALE Falling Edge to \overline{WR} Falling Edge | T _{OSC} - 10 | | ns | |
| T _{CLWL} | CLKOUT Low to \overline{WR} Falling Edge | 0 | +25 | ns | |
| T _{QVWH} | Data Stable to \overline{WR} Rising Edge | T _{OSC} - 23 | | | (Note 4) |
| T _{CHWH} | CLKOUT High to \overline{WR} Rising Edge | -5 | +15 | ns | |
| T _{WLWH} | \overline{WR} Low Period | T _{OSC} - 20 | | ns | (Note 4) |
| T _{WHQX} | Data Hold after \overline{WR} Rising Edge | T _{OSC} - 25 | | ns | |
| T _{WHLH} | \overline{WR} Rising Edge to ALE Rising Edge | T _{OSC} - 10 | T _{OSC} + 15 | ns | (Note 2) |
| T _{WHBX} | \overline{BHE} , INST after \overline{WR} Rising Edge | T _{OSC} - 10 | | ns | |
| T _{WHAX} | AD8±15 HOLD after \overline{WR} Rising | T _{OSC} - 30 | | ns | (Note 3) |
| T _{RHBX} | \overline{BHE} , INST after \overline{RD} Rising Edge | T _{OSC} - 10 | | ns | |
| T _{RHAX} | AD8±15 HOLD after \overline{RD} Rising | T _{OSC} - 25 | | ns | (Note 3) |


NOTES:

1. Testing performed at 8 MHz. However, the device is static by design and will typically operate below 1 Hz.
2. Assuming back-to-back bus cycles.
3. 8-Bit bus only.
4. If wait states are used, add 2 T_{OSC} * N, where N = number of wait states.


System Bus Timings



READY Timings (One Wait State)



Buswidth Timings



HOLD/HLDA TIMINGS


| Symbol | Description | Min | Max | Units | Notes |
|--------------------|------------------------------------------------------|------|------|-------|----------|
| T _{HVCH} | HOLD Setup | + 55 | | ns | (Note 1) |
| T _{CLHAL} | CLKOUT Low to HLD \bar{A} Low | - 15 | + 15 | ns | |
| T _{CLBRL} | CLKOUT Low to BRE \bar{Q} Low | - 15 | + 15 | ns | |
| T _{HALAZ} | HLD \bar{A} Low to Address Float | | + 15 | ns | |
| T _{HALBZ} | HLD \bar{A} Low to BHE, INST, RD, WR Weakly Driven | | + 20 | ns | |
| T _{CLHAH} | CLKOUT Low to HLD \bar{A} High | - 15 | + 15 | ns | |
| T _{CLBRH} | CLKOUT Low to BRE \bar{Q} High | - 15 | + 15 | ns | |
| T _{HAHAX} | HLD \bar{A} High to Address No Longer Float | - 15 | | ns | |
| T _{HAHBV} | HLD \bar{A} High to BHE, INST, RD, WR Valid | - 10 | + 15 | ns | |
| T _{CLLH} | CLKOUT Low to ALE High | - 5 | + 15 | ns | |

NOTE:

1. To guarantee recognition at next clock.

DC SPECIFICATIONS IN HOLD

| Description | Min | Max | Units |
|---------------------------------------------------------------------------|-----|------|-------------------------------------------------|
| Weak Pullups on \bar{ADV} , \bar{RD} , \bar{WR} , \bar{WRL} , BHE | 50K | 250K | V _{CC} = 5.5V, V _{IN} = 0.45V |
| Weak Pulldowns on ALE, INST | 10K | 50K | V _{CC} = 5.5V, V _{IN} = 2.4 |



MAXIMUM HOLD LATENCY

| Bus Cycle Type | |
|---------------------------|------------|
| Internal Execution | 1.5 States |
| 16-Bit External Execution | 2.5 States |
| 8-Bit External Execution | 4.5 States |


EXTERNAL CLOCK DRIVE (8XC196KD)

| Symbol | Parameter | Min | Max | Units |
|---------------------|----------------------|------|------|-------|
| 1/T _{XLXL} | Oscillator Frequency | 8 | 16.0 | MHz |
| T _{XLXL} | Oscillator Period | 62.5 | 125 | ns |
| T _{XHXX} | High Time | 20 | | ns |
| T _{XLXX} | Low Time | 20 | | ns |
| T _{XLXH} | Rise Time | | 10 | ns |
| T _{XHXL} | Fall Time | | 10 | ns |


EXTERNAL CLOCK DRIVE (8XC196KD20)

| Symbol | Parameter | Min | Max | Units |
|---------------------|----------------------|-----|------|-------|
| 1/T _{XLXL} | Oscillator Frequency | 8 | 20.0 | MHz |
| T _{XLXL} | Oscillator Period | 50 | 125 | ns |
| T _{XHXX} | High Time | 17 | | ns |
| T _{XLXX} | Low Time | 17 | | ns |
| T _{XLXH} | Rise Time | | 8 | ns |
| T _{XHXL} | Fall Time | | 8 | ns |


EXTERNAL CLOCK DRIVE WAVEFORMS




EXTERNAL CRYSTAL CONNECTIONS




EXTERNAL CLOCK CONNECTIONS



AC TESTING INPUT, OUTPUT WAVEFORMS



FLOAT WAVEFORMS



EXPLANATION OF AC SYMBOLS

Each symbol is two pairs of letters prefixed by "T" for time. The characters in a pair indicate a signal and its condition, respectively. Symbols represent the time between the two signal/condition points.

Conditions:

- H - High
- L - Low
- V - Valid
- X - No Longer Valid
- Z - Floating

Signals:

- A - Address
- B - \overline{BHE}
- C - CLKOUT
- D - DATA
- G - Buswidth
- H - \overline{HOLD}
- HA - \overline{HLDA}
- L - $\overline{ALE/ADV}$
- BR - \overline{BREQ}
- R - \overline{RD}
- W - $\overline{WR/WRH/WRL}$
- X - XTAL1
- Y - READY
- Q - Data Out




AC CHARACTERISTICS-SERIAL PORT-SHIFT REGISTER MODE

SERIAL PORT TIMING-SHIFT REGISTER MODE (MODE0)

| Symbol | Parameter | Min | Max | Units |
|-------------------|-------------------------------------------------------------|-------------------------|-------------------------|-------|
| T _{XLXL} | Serial Port Clock Period (BRR ≥ 8002H) | 6 T _{OSC} | | ns |
| T _{XLXH} | Serial Port Clock Falling Edge to Rising Edge (BRR ≥ 8002H) | 4 T _{OSC} - 50 | 4 T _{OSC} + 50 | ns |
| T _{XLXL} | Serial Port Clock Period (BRR = 8001H) | 4 T _{OSC} | | ns |
| T _{XLXH} | Serial Port Clock Falling Edge to Rising Edge (BRR = 8001H) | 2 T _{OSC} - 50 | 2 T _{OSC} + 50 | ns |
| T _{QVXH} | Output Data Valid to Clock Rising Edge | 2 T _{OSC} - 50 | | ns |
| T _{XHQX} | Output Data Hold after Clock Rising Edge | 2 T _{OSC} - 50 | | ns |
| T _{XHQV} | Next Output Data Valid after Clock Rising Edge | | 2 T _{OSC} + 50 | ns |
| T _{DVXH} | Input Data Setup to Clock Rising Edge | T _{OSC} + 50 | | ns |
| T _{XHDX} | Input Data Hold after Clock Rising Edge | 0 | | ns |
| T _{XHQZ} | Last Clock Rising to Output Float | | 1 T _{OSC} | ns |

WAVEFORM-SERIAL PORT-SHIFT REGISTER MODE

SERIAL PORT WAVEFORM-SHIFT REGISTER MODE (MODE 0)



A to D CHARACTERISTICS

The A/D converter is ratiometric, so absolute accuracy is dependent on the accuracy and stability of V_{REF} .

10-BIT MODE A/D OPERATING CONDITIONS

| Symbol | Description | Min | Max | Units |
|------------|---------------------------------------------|-----------------|-----------------|---------------|
| T_A | Ambient Temperature Commercial Temp. | 0 | +70 | °C |
| T_A | Ambient Temperature Extended Temp. | -40 | +85 | °C |
| V_{CC} | Digital Supply Voltage | 4.50 | 5.50 | V |
| V_{REF} | Analog Supply Voltage | 4.00 | 5.50 | V |
| ANGND | Analog Ground Voltage | $V_{SS} - 0.40$ | $V_{CC} + 0.40$ | V |
| T_{SAM} | Sample Time | 1.0 | | $\mu s^{(1)}$ |
| T_{CONV} | Conversion Time | 10 | 20 | $\mu s^{(1)}$ |
| F_{OSC} | Oscillator Frequency (8XC196KD) | 8.0 | 16.0 | MHz |
| F_{OSC} | Oscillator Frequency (8XC196KD20) | 8.0 | 20.0 | MHz |

NOTE:

1. The value of AD_TIME is selected to meet these specifications.

10-BIT MODE A/D CHARACTERISTICS (Over Specified Operating Conditions)

| Parameter | Typical ⁽¹⁾ | Minimum | Maximum | Units* | Notes |
|----------------------------------|------------------------|-------------|-----------------|----------------|-------|
| Resolution | | 1024 10 | 1024 10 | Levels Bits | |
| Absolute Error | | 0 | ± 3 | LSBs | |
| Full Scale Error | 0.25 ± 0.5 | | | LSBs | |
| Zero Offset Error | 0.25 ± 0.5 | | | LSBs | |
| Non-Linearity | 1.0 ± 2.0 | 0 | ± 3 | LSBs | |
| Differential Non-Linearity Error | | > -1 | +2 | LSBs | |
| Channel-to-Channel Matching | ± 0.1 | 0 | ± 1 | LSBs | |
| Repeatability | ± 0.25 | | | LSBs | |
| Temperature Coefficients: | | | | | |
| Offset | 0.009 | | | LSB/°C | |
| Full Scale | 0.009 | | | LSB/°C | |
| Differential Non-Linearity | 0.009 | | | LSB/°C | |
| Off Isolation | | -60 | | dB | 2, 3 |
| Feedthrough | -60 | | | dB | 2 |
| V_{CC} Power Supply Rejection | -60 | | | dB | 2 |
| Input Series Resistance | | 750 | 1.2K | Ω | 4 |
| Voltage on Analog Input Pin | | ANGND - 0.5 | $V_{REF} + 0.5$ | V | 5, 6 |
| DC Input Leakage | | 0 | ± 3.0 | μA | |
| Sampling Capacitor | 3 | | | pF | |

NOTES:

*An "LSB" as used here has a value of approximately 5 mV. (See Embedded Microcontrollers and Processors Handbook for A/D glossary of terms.)

- These values are expected for most parts at 25°C but are not tested or guaranteed.
- DC to 100 KHz.
- Multiplexer Break-Before-Make is guaranteed.
- Resistance from device pin, through internal MUX, to sample capacitor.
- These values may be exceeded if the pin current is limited to ± 2 mA.
- Applying voltages beyond these specifications will degrade the accuracy of other channels being converted.
- All conversions performed with processor in IDLE mode.

8-BIT MODE A/D OPERATING CONDITIONS

| Symbol | Description | Min | Max | Units |
|-------------------|---------------------------------------------|------------------------|------------------------|-------------------|
| T _A | Ambient Temperature Commercial Temp. | 0 | +70 | °C |
| T _A | Ambient Temperature Extended Temp. | -40 | +85 | °C |
| V _{CC} | Digital Supply Voltage | 4.50 | 5.50 | V |
| V _{REF} | Analog Supply Voltage | 4.00 | 5.50 | V |
| ANGND | Analog Ground Voltage | V _{SS} - 0.40 | V _{SS} + 0.40 | V |
| T _{SAM} | Sample Time | 1.0 | | μs ⁽¹⁾ |
| T _{CONV} | Conversion Time | 7 | 20 | μs ⁽¹⁾ |
| F _{OSC} | Oscillator Frequency (8XC196KD) | 8.0 | 16.0 | MHz |
| F _{OSC} | Oscillator Frequency (8XC196KD20) | 8.0 | 20.0 | MHz |

NOTE:

1. The value of AD_TIME is selected to meet these specifications.

8-BIT MODE A/D CHARACTERISTICS (Over Specified Operating Conditions)

| Parameter | Typical ⁽¹⁾ | Minimum | Maximum | Units* | Notes |
|----------------------------------------|------------------------|-----------------------|------------------------|----------------|-------|
| Resolution | | 256 8 | 256 8 | Levels Bits | |
| Absolute Error | | 0 | ±1 | LSBs | |
| Full Scale Error | ±0.5 | | | LSBs | |
| Zero Offset Error | ±0.5 | | | LSBs | |
| Non-Linearity | | 0 | ±1 | LSBs | |
| Differential Non-Linearity Error | | > -1 | +1 | LSBs | |
| Channel-to-Channel Matching | | | ±1 | LSBs | |
| Repeatability | ±0.25 | | | LSBs | |
| Temperature Coefficients: | | | | | |
| Offset | 0.003 | | | LSB/°C | |
| Full Scale | 0.003 | | | LSB/°C | |
| Differential Non-Linearity | 0.003 | | | LSB/°C | |
| Off Isolation | | -60 | | dB | 2, 3 |
| Feedthrough | -60 | | | dB | 2 |
| V _{CC} Power Supply Rejection | -60 | | | dB | 2 |
| Input Series Resistance | | 750 | 1.2K | Ω | 4 |
| Voltage on Analog Input Pin | | V _{SS} - 0.5 | V _{REF} + 0.5 | V | 5, 6 |
| DC Input Leakage | | 0 | ±3.0 | μA | |
| Sampling Capacitor | 3 | | | pF | |

NOTES:

*An "LSB" as used here has a value of approximately 20 mV. (See Embedded Microcontrollers and Processors Handbook for A/D glossary of terms).

1. These values are expected for most parts at 25°C but are not tested or guaranteed.
2. DC to 100 KHz.
3. Multiplexer Break-Before-Make is guaranteed.
4. Resistance from device pin, through internal MUX, to sample capacitor.
5. These values may be exceeded if pin current is limited to ±2 mA.
6. Applying voltages beyond these specifications will degrade the accuracy of other channels being converted.
7. All conversions performed with processor in IDLE mode.

OTPROM SPECIFICATIONS

OPERATING CONDITIONS

| Symbol | Description | Min | Max | Units |
|-----------|---------------------------------------------------------------|-------|-------|-------|
| T_A | Ambient Temperature During Programming | 20 | 30 | C |
| V_{CC} | Supply Voltage During Programming | 4.5 | 5.5 | V(1) |
| V_{REF} | Reference Supply Voltage During Programming | 4.5 | 5.5 | V(1) |
| V_{PP} | Programming Voltage | 12.25 | 12.75 | V(2) |
| V_{EA} | EA Pin Voltage | 12.25 | 12.75 | V(2) |
| F_{OSC} | Oscillator Frequency during Auto and Slave Mode Programming | 6.0 | 8.0 | MHz |
| F_{OSC} | Oscillator Frequency during Run-Time Programming (8XC196KD) | 6.0 | 16.0 | MHz |
| F_{OSC} | Oscillator Frequency during Run-Time Programming (8XC196KD20) | 6.0 | 20.0 | MHz |

NOTES:

- V_{CC} and V_{REF} should nominally be at the same voltage during programming.
- V_{PP} and V_{EA} must never exceed the maximum specification, or the device may be damaged.
- V_{SS} and $ANGND$ should nominally be at the same potential (0V).
- Load capacitance during Auto and Slave Mode programming = 150 pF.

AC OTPROM PROGRAMMING CHARACTERISTICS (SLAVE MODE)

| Symbol | Description | Min | Max | Units |
|------------------|------------------------------------------------------|------|-----|-----------|
| T_{SHLL} | Reset High to First \overline{PALE} Low | 1100 | | T_{OSC} |
| T_{LLLH} | \overline{PALE} Pulse Width | 50 | | T_{OSC} |
| T_{AVLL} | Address Setup Time | 0 | | T_{OSC} |
| T_{LLAX} | Address Hold Time | 100 | | T_{OSC} |
| T_{PLDV} | \overline{PROG} Low to Word Dump Valid | | 50 | T_{OSC} |
| T_{PHDX} | Word Dump Data Hold | | 50 | T_{OSC} |
| T_{DVPL} | Data Setup Time | 0 | | T_{OSC} |
| T_{PLDX} | Data Hold Time | 400 | | T_{OSC} |
| $T_{PLPH}^{(1)}$ | \overline{PROG} Pulse Width | 50 | | T_{OSC} |
| T_{PHLL} | \overline{PROG} High to Next \overline{PALE} Low | 220 | | T_{OSC} |
| T_{LHPL} | \overline{PALE} High to \overline{PROG} Low | 220 | | T_{OSC} |
| T_{PHPL} | \overline{PROG} High to Next \overline{PROG} Low | 220 | | T_{OSC} |
| T_{PHIL} | \overline{PROG} High to \overline{AINC} Low | 0 | | T_{OSC} |
| T_{ILIH} | \overline{AINC} Pulse Width | 240 | | T_{OSC} |
| T_{ILVH} | \overline{PVER} Hold after \overline{AINC} Low | 50 | | T_{OSC} |
| T_{ILPL} | \overline{AINC} Low to \overline{PROG} Low | 170 | | T_{OSC} |
| T_{PHVL} | \overline{PROG} High to \overline{PVER} Valid | | 220 | T_{OSC} |

NOTE:

- This specification is for the Word Dump Mode. For programming pulses, use the Modified Quick Pulse Algorithm.

DC OTPROM PROGRAMMING CHARACTERISTICS


| Symbol | Description | Min | Max | Units |
|----------|--------------------------------------------|-----|-----|-------|
| I_{PP} | V_{PP} Supply Current (When Programming) | | 100 | mA |

NOTE:

Do not apply V_{PP} until V_{CC} is stable and within specifications and the oscillator/clock has stabilized or the device may be damaged.


OTPROM PROGRAMMING WAVEFORMS

SLAVE PROGRAMMING MODE DATA PROGRAM MODE WITH SINGLE PROGRAM PULSE




NOTE:
P3.0 must be high ('1')

SLAVE PROGRAMMING MODE IN WORD DUMP WITH AUTO INCREMENT



SLAVE PROGRAMMING MODE TIMING IN DATA PROGRAM WITH REPEATED PROG PULSE AND AUTO INCREMENT



8XC196KC TO 8XC196KD DESIGN CONSIDERATIONS

1. Memory Map. The 8XC196KD has 1024 bytes of RAM/SFRs and 32K of OTPROM. The extra 512 bytes of RAM reside in locations 0200H to 03FFH, and the extra 16 Kbytes of OTPROM reside in locations 6000H to 9FFFH. On the 87C196KC these locations are always external, so KC code may have to be modified to run on the KD.
2. The vertical window scheme has been extended to include all on-chip RAM.
3. IOC3.1 controls the CLKOUT signal. This bit must be 0 to enable CLKOUT.
4. The 87C196KD has a different autoprogramming algorithm to support 32K of on-chip OTPROM.

8XC196KD ERRATA

1. 83C196KD can possibly miss interrupts on P0.7. See techbit MC0893.

DATA SHEET REVISION HISTORY

This data sheet is valid for devices with a "D" and "E" at the end of the topside tracking number. Data sheets are changed as new device information becomes available. Verify with your local Intel sales office that you have the latest version before finalizing a design or ordering devices.

The following are important differences between the 272145-004 and 272145-005 datasheets:

1. Package prefix variables have been changed.

Variables are now indicated with an "x".

The following are important differences between the 272145-002 and 272145-003 data sheets:

1. I_{IL1} specification (logic 0 input current in reset) was misnamed. It is renamed I_{IL2} .
2. T_{LLYV} and T_{LLGV} were removed. These specifications are not necessary for high-speed system designs.
3. An errata with 83C196KD P0.7 EXTINT was added to the errata section.

The following are important differences between the 272145-001 and 272145-002 data sheets:

1. Added 20 MHz specifications.
2. Added 80-lead SQFP package pinout.

3. Changed QFP Package θ_{JA} to 56°C/W from 42°C/W.
4. Changed V_{HYS} to 300 mV from 150 mV.
5. Changed I_{CC} Typical specification at 16 MHz to 65 mA from 50 mA.
6. Changed I_{CC} Maximum specification at 16 MHz to 75 mA from 70 mA.
7. Changed I_{IDLE} Typical specification to 17 mA from 15 mA.
8. Changed I_{IDLE} Maximum specification to 25 mA from 30 mA.
9. Changed I_{PD} Typical specification to 8 μ A from 15 μ A.
10. Added I_{PD} Maximum specification.
11. Changed T_{CLDV} Maximum specification to $T_{OSC} - 45$ from $T_{OSC} - 50$.
12. Changed T_{LLAX} Minimum specification to $T_{OSC} - 35$ from $T_{OSC} - 40$.
13. Changed T_{CHWH} Minimum specification to -5 from -10 .
14. Changed T_{RHAX} Minimum specification to $T_{OSC} - 25$ from $T_{OSC} - 30$.
15. Changed T_{HALAZ} Maximum specification to $+15$ from $+10$.
16. Changed T_{HALBZ} Maximum specification to $+20$ from $+15$.
17. Added T_{HAHBV} Maximum specification.
18. Changed T_{SAM} for 10-bit mode to 1 μ s from 3 μ s.
19. Changed T_{SAM} for 8-bit mode to 1 μ s from 2 μ s.
20. Changed I_{IH1} test condition to $V_{IN} = 2.4V$ from 5.5V.
21. Changed I_{IH1} maximum specification to $+200 \mu$ A from $+100 \mu$ A.
22. Removed NMI from list of standard inputs.
23. Updated I_{CC} and I_{IDLE} vs frequency graph.
24. Updated note under DC EPROM Programming Characteristics.
25. Changed I_{LL1} maximum specification to -12 mA from -6 mA.

