

SMD Type

Multi Layer Ceramic Capacitors

Introduction

SAMWHA's series of multilayer ceramic(MLC) chip capacitors is designed to meet a wide variety of need. Multilayer ceramic chip capacitors are available in both class I and class II formulations. Temperature compensation formulations are class I and temperature stable and general application formulations are classified at class II. The class I multilayer ceramic capacitors are COG with negligible dependence of electrical properties on temperature, voltage, frequency. The most of commonly used class II dielectric are X7R, X5R and Y5V. The X7R provides intermediate capacitance values which vary $\pm 15\%$ over the temperature range of -55°C to 125°C. The X5R provides intermediate capacitance values which vary $\pm 15\%$ over the temperature range of -55°C to 85°C. The Y5V provides the highest capacitance value which vary from 22% to -82% over the temperature range of -30°C to 85°C. All class II capacitors vary in capacitance value under the influence of temperature, operating voltage and frequency. We offer a complete line of products for both class I and II.

Features

- Samwha's high density ceramic bodies offer superior performance and reliability
- Samwha offer various temperature characteristics, rated voltage and packing method
- Material with high dielectric constant and superior manufacturing technology allows very high values in a small size
- Solder coated terminals offer superior solderability


Applications

Wide applications throughout commercial and industrial market.

- Communication products like Cellular Phone, Pager, Codeless phone
- Multimedia products like DVD, CD-ROM, FDD, HDD, Game machine, Computer, Note book, Digital camera, LCD
- Audio visual products like TV, Camcorder, Minidisk, MP3 Player
- Communication products like Electronic tuner, Duplexer, VCXO, TCXO, Modem
- OA equipment products like Printer, Copy Machine, Fax Machine

SMD Type

Shape & Dimensions



Code(inch)	Dimensions				T1(min)
	L	Tol(±)	W	Tol(±)	
0603(0201)	0.60	0.03	0.30	0.03	0.05
1005(0402)	1.00	0.05	0.50	0.05	0.05
1608(0603)	1.60	0.15	0.80	0.10	0.10
2012(0805)	2.00	0.20	1.25	0.15	0.10
3216(1206)	3.20	0.30	1.60	0.20	0.15
3225(1210)	3.20	0.40	2.50	0.25	0.15
4520(1808)	4.50	0.40	2.00	0.25	0.20
4532(1812)	4.50	0.40	3.20	0.30	0.20
5750(2300)	5.70	0.50	5.00	0.40	0.30

*1608 Size $\geq 10\mu F \Rightarrow W: 0.8 \pm 0.15, T: 0.8 \pm 0.15$

How to Order (Product Identification)

CS 1608 X7R 104 K 160 N R B

1 2 3 4 5 6 7 8 9

1 Type

CS : SMD
SA : ARRAY

2 Size Code

This is expressed in tens of a millimeter.
The first two digits are the length, the last two digits are width.

Size(mm)	0603	1005	1608	2012	3216	3225	4520	4532	5750
----------	------	------	------	------	------	------	------	------	------

3 Temperature Coefficient Code

Temperature Characteristic	Temperature Range	Capacitance Change or Temperature Coefficient	Operating Temperature Range
COG	-55 to 125°C	$0 \pm 30\text{ppm}/^\circ\text{C}$	-55 to 125°C
X7R	-55 to 125°C	$\pm 15\%$	-55 to 125°C
X5R	-55 to 85°C	$\pm 15\%$	-55 to 85°C
Y5V	-30 to 85°C	+22, -82%	-30 to 85°C

4 Capacitance Code(Pico Farads)

The nominal capacitance value in pF is expressed by three digit numbers.
The first two digits represents significant figures and the last digit denotes the number of zero
Ex.) 104 = 100000pF R denotes decimal 8R2 = 8.2pF

5 Capacitance Tolerance Code

Code	Tolerance	Code	Tolerance
B	$\pm 0.1\text{pF}$	M	$\pm 20\%$
C	$\pm 0.25\text{pF}$	P	$+100, -0\%$
D	$\pm 0.5\text{pF}$	Z	$+80, -20\%$
F	$\pm 1.0\%$	H	$+0.25/-0.05\text{pF}$
G	$\pm 2.0\%$	I	$+0/-0.25\text{pF}$
J	$\pm 5\%$	U	$+5/-0\%$
K	$\pm 10\%$	V	$+0/-5\%$

6 Voltage Code

Code	6R3	100	160	250	500	101	201	251	631	302
Vol.	DC 6.3V	DC 10V	DC 16V	DC 25V	DC 50V	DC 100V	DC 200V	DC 250V	DC 630V	DC 3000V

7 Termination Code

Ex.) N : Ni-Sn (Nickel-Tin Plate)

8 Packing Code

Ex.) R : Reel Type B : Bulk Type

9 Thickness Option

(Unit : mm)

Code	Thickness(mm)		Dimensions		Code	Thickness(mm)		Dimensions	
	L	Tol(±)	W	Tol(±)		W	Tol(±)	W	Tol(±)
Blank	0.30	0.05	E	1.30	0.20				
Blank	0.50	0.05	H	1.35	0.20				
A	0.60	0.10	I	1.60	0.20				
B	0.80	0.10	J	1.80	0.20				
B	0.85	0.15	K	2.00	0.25				
E	1.00	0.15	L	2.50	0.25				
E	1.10	0.15	M	2.80	0.30				
E	1.15	0.15	N	3.20	0.30				
E	1.25	0.15	O	5.00	0.40				

Typical Performance Characteristics


COG

Application

Suited for precision circuits, requiring stable dielectric characteristics, negligible dependence of capacitance and dissipation factor on time, voltage and frequency.

Dielectric Characteristics

Temperature Characteristic	$0 \pm 30\text{ppm}/^\circ\text{C}$
Operating Temperature	-55~125°C
Capacitance Tolerance	$>10\text{pF} : \pm 5\%, \pm 10\%, (\pm 1\%, \pm 2\%, \pm 20\%)$ $\leq 10\text{pF} : \pm 0.1\text{pF}, \pm 0.25\text{pF}, \pm 0.5\text{pF}$
Dissipation Factor & Q	$\geq 30\text{pF} : \text{DF} \leq 0.1\%, Q \geq 1000$ $< 30\text{pF} : Q \geq 400 \times 20 \times C$
Insulation Resistance	More than 10,000MΩ or 500GΩ (Whichever is smaller)
Dielectric Strength	$> 3 \times \text{RVDC}$
Test Voltage	0.5 to 5Vrms ($\leq 1000\text{pF}$), $1 \pm 0.2\text{Vrms} (> 1000\text{pF})$
Test Frequency	$1 \pm 0.1\text{MHz} (\leq 1000\text{pF}), 1 \pm 0.1\text{kHz} (> 1000\text{pF})$




X7R

Application

Stable class II dielectric properties, suited for by-pass and coupling purposes, filtering, frequency discrimination, DC blockage, and as voltage transient suppression elements.

Dielectric Characteristics

Temperature Characteristic	$\pm 15\%$
Operating Temperature	-55~125°C
Capacitance Tolerance	$\pm 10\%, \pm 20\%, (\pm 5\%, +80\%-20\%)$
Dissipation Factor & Q	50V Min. : 2.5% Max. 25V Min. : 3.0% Max. 16V Min. : 3.5% Max. 10V Min. : 5.0% Max. 6.3V Min. : 5.0% Max. ($< 3.3\mu\text{F}$), 10% Max. ($\geq 3.3\mu\text{F}$) Thin layer large capacitors type 10% Max.
Insulation Resistance	More than 10,000MΩ or 500GΩ (Whichever is smaller) Thin layer large capacitors type 50GΩ Min.
Dielectric Strength	$> 2.5 \times \text{RVDC}$
Test Voltage	$1 \pm 0.2\text{Vrms} (\leq 10\mu\text{F}, 10\text{V Min.})$ $0.5 \pm 0.1\text{Vrms} (\leq 10\mu\text{F}, 6.3\text{V Max.})$ $0.5 \pm 0.1\text{Vrms} (> 10\mu\text{F})$
Test Frequency	$1 \pm 0.1\text{kHz} (\leq 10\mu\text{F}, 10\text{V Min.})$ $1 \pm 0.1\text{kHz} (\leq 10\mu\text{F}, 6.3\text{V Max.})$ $120 \pm 24\text{Hz} (> 10\mu\text{F})$




X5R

Application

Stable class II dielectric properties, suited for by-pass and coupling purposes, filtering, frequency discrimination, DC blockage, and as voltage transient suppression elements.

Dielectric Characteristics

Temperature Characteristic	$\pm 15\%$
Operating Temperature	-55~85°C
Capacitance Tolerance	$\pm 10\%$, $\pm 20\%$, ($\pm 5\%$, +80~-20%)
Dissipation Factor & Q	50V Min.: 2.5% Max. 25V Min.: 3.0% Max. 16V Min.: 3.5% Max. 10V Min.: 5.0% Max. 6.3V Min.: 5.0% Max. ($<3.3\mu F$), 10% Max. ($\geq 3.3\mu F$) Thin layer large capacitors type 10% Max.
Insulation Resistance	More than 10,000MΩ or 500μF (Whichever is smaller) Thin layer large capacitors type 50μF Min.
Dielectric Strength	>2.5×RVDC
Test Voltage	1±0.2Vrms($\leq 10\mu F$, 10V Min.) 0.5±0.1Vrms($\leq 10\mu F$, 6.3V Max.) 0.5±0.1Vrms($> 10\mu F$)
Test Frequency	1±0.1kHz($\leq 10\mu F$, 10V Min.) 1±0.1kHz($\leq 10\mu F$, 6.3V Max.), 120±24Hz($> 10\mu F$)




Y5V

Application

The Hi-K(Y5V) dielectrics deliver high capacitance density and are ideally suited for applications where space is at a premium, or as replacement for tantalum capacitors. Typically applications include use as by-pass or decoupling elements. Best performance is obtained at or near room temperature, with low DC bias.

Dielectric Characteristics

Temperature Characteristic	+22%~+82%
Operating Temperature	-30~85°C
Capacitance Tolerance	-20~+80% ($\pm 20\%$)
Dissipation Factor & Q	50V Min.: 5% Max. 25V Min.: 7% Max. 16V Min.: 9% Max. 10V Min.: 12.5% Max. 6.3V Min.: 15% Max. Thin layer large capacitors type 20% Max.
Insulation Resistance	More than 10,000MΩ or 500μF (Whichever is smaller) Thin layer large capacitors type 50μF Min.
Dielectric Strength	>2.5×RVDC
Test Voltage	1±0.2Vrms($\leq 10\mu F$, 10V Min.) 0.5±0.1Vrms($\leq 10\mu F$, 6.3V Max.) 0.5±0.1Vrms($> 10\mu F$)
Test Frequency	1±0.1kHz($\leq 10\mu F$, 10V Min.) 1±0.1kHz($\leq 10\mu F$, 6.3V Max.), 120±24Hz($> 10\mu F$)



Appendix I

COG-Temperature Compensating Type(0603~3216)

Type Size(inch) Cap. Vol(V)	0603(0201)	COG				2012(0805)	3216(1206)	
		25	25	50	25		25	50
0.5μF(085)								
1μF(010)								
2μF(020)								
3μF(030)								
4μF(040)								
5μF(050)								
6μF(060)								
7μF(070)								
8μF(080)								
9μF(090)								
10μF(100)								
12μF(120)								
15μF(150)								
18μF(180)								
22μF(220)								
27μF(270)								
35μF(350)								
39μF(390)								
47μF(470)								
56μF(560)								
68μF(680)								
82μF(820)								
100μF(101)								
120μF(121)								
150μF(151)								
180μF(181)								
220μF(221)								
270μF(271)								
350μF(351)								
390μF(391)								
470μF(471)								
560μF(561)								
680μF(681)								
820μF(821)								
1000μF(102)								
1200μF(122)								
1500μF(152)								
1800μF(182)								
2200μF(222)								
2700μF(272)								
3500μF(352)								
3900μF(392)								
4700μF(472)								
5600μF(562)								
6800μF(682)								
8200μF(822)								
10000μF(103)								
12000μF(123)								
15000μF(153)								
18000μF(183)								
22000μF(223)								
27000μF(273)								
35000μF(353)								
47000μF(473)								
56000μF(563)								
68000μF(683)								
82000μF(823)								
0.1μF(104)								

Temperature Compensating Type : Dissipation Factor Page 22 (No.5)

Y5V-High Dielectric Constant Type(0603~3225) & Thin Layer Large-Capacitance Type

Type Size(inch) Vol(V) Cap.	Y5V																							
	1005(0402)				1608(0603)				2012(0805)				3216(1206)				3225(1210)							
6.3	10	16	25	50	6.3	10	16	25	50	6.3	10	16	25	50	6.3	10	16	25	50	6.3	10	16	25	50
1000pF(102)																								
2200pF(222)																								
4700pF(472)																								
10000pF(103)																								
15000pF(153)																								
22000pF(223)																								
33000pF(333)																								
47000pF(473)																								
68000pF(683)																								
0.1pF(104)																								
0.15pF(154)																								
0.22pF(224)																								
0.33pF(334)																								
0.47pF(474)																								
0.68pF(684)																								
1.0pF(105)																								
1.5pF(155)																								
2.2pF(225)																								
3.3pF(335)																								
4.7pF(475)																								
6.8pF(685)																								
10pF(106)																								
22pF(226)																								
47pF(476)																								
100pF(107)																								

- [Light Blue Box] General Type : Dissipation Factor Page 22 (No.5)
- [Grey Box] *General Type : Dissipation Factor Page 22 (No.5)
- [Blue Box] Thin Layer Large-Capacitance Type : Dissipation Factor Page 22 (No.5)

SMD Type-High Voltage

SMD Type-High Voltage

Product Offering

SAMWHA high voltage MLCC products with COG(NPO) and X7R temperature characteristic are designed for commercial and industrial applications.

The products are power supply and voltage multiplier circuits applications in various sizes with working voltages up to DC 3.0 KV .

These high voltage capacitors feature a special internal electrode design which reduces voltage concentrations by distributing voltage gradients throughout the entire capacitor.

This unique design also affords that capacitance value is increased in a given case size and voltage rating.

Features

- High reliability
- High voltage ratings
- Wide voltage level : from 100V to 3000V
- Surface mount suited for Wave and Reflow Soldering
- Tape & reel surface mount assembly
- Suitable for Back-Lighting Inverter, DC-DC Converters, Ballast, Modems & Power Supply, LAN/WLAN interface... etc.

How to Order (Product Identification)

CS 4520 COG 150 J 302 N R E

1 2 3 4 5 6 7 8 9

1 Type

CS : SMD

2 Size Code

Size(mm)	1608	2012	3216	3225	4520	4532
----------	------	------	------	------	------	------

3 Dielectric (Temp. Coefficient)

COG, X7R

4 Capacitance

1st two digits are value, 3rd digit denotes number of zeros;
 33 = 330pF, 104 = 100000pF, 8R2C = 8.2pF

SMD Type-High Voltage

5 Tolerance

Code	Tolerance	Code	Tolerance
B	$\pm 0.1\text{pF}$	C	$\pm 0.25\text{pF}$
D	$\pm 0.50\text{pF}$	F	$\pm 1\%$
G	$\pm 2\%$	J	$\pm 5\%$
K	$\pm 10\%$	M	$\pm 20\%$
Z	+80~−20%		

6 Rated Voltage Code

1st two digits are value, 3rd digit denotes number of zeros; 302 = 3000V, 251 = 250V

7 Plating

Ni / Sn Plated

8 Packing


B : Bulk Pack R : Reel Pack

9 Thickness Option

(Unit : mm)

Code	Thickness(mm)	Dimensions		Code	Thickness(mm)	Dimensions	
		L	Tol(±)			W	Tol(±)
Blank	0.30	0.03		E	1.30	0.20	
Blank	0.50	0.05		H	1.35	0.20	
A	0.60	0.10		I	1.60	0.20	
B	0.80	0.10		J	1.80	0.20	
B	0.85	0.15		K	2.00	0.25	
E	1.00	0.15		L	2.50	0.25	
E	1.10	0.15		M	2.80	0.30	
E	1.15	0.15		N	3.20	0.30	
E	1.25	0.15		O	5.00	0.40	

Shape & Dimensions



(Unit : mm)

Code	Dimensions				T1(min)
	L	Tol(±)	W	Tol(±)	
1608(0603)	1.60	0.15	0.80	0.10	0.10
2012(0805)	2.00	0.20	1.25	0.15	0.10
3216(1206)	3.20	0.30	1.60	0.20	0.15
3225(1210)	3.20	0.40	2.50	0.25	0.15
4520(1808)	4.50	0.40	2.00	0.25	0.20
4532(1812)	4.50	0.40	3.20	0.30	0.20
5750(2300)	5.70	0.50	5.00	0.40	0.30

*1608 Size $\geq 10\mu\text{F} \Rightarrow W : 0.8 \pm 0.15, T : 0.8 \pm 0.15$

Typical Performance Characteristics

Dielectric Characteristics

Dielectric Classification	Ultra Stable
Rated temperature range	-55°C to +125°C
TCC(Temperature Characteristics Coefficient)	$0 \pm 30\text{ppm}$
Dissipation Factor(tan δ)	$C \geq 30\text{pF} : Q \geq 1,000 (\text{DF} \leq 0.1\%)$ $C < 30\text{pF} : Q \geq 400+20C (\text{DF} \leq 1/(400+20C))$
IR(Insulation Resistance)	500V Below : Rated voltage 60sec 500V Above : 500V 60sec More than 10,000 MΩ
Capacitance Tolerance	$< 10\text{pF} : \pm 0.25\text{pF}, \pm 0.5\text{pF}$ $\geq 10\text{pF} : \pm 5\%, \pm 0\%$
Dielectric strength	630V:150% Rated Voltage 1kV-3.15kV:120% Rated Voltage
Aging characteristics	0%


X7R

Stable
-55°C to +125°C
±15%
2.5% Max.
500V Below: Rated voltage 60sec 500V Above: 500V 60sec -DC100V-1KV : $C \geq 0.01\mu\text{F}$: More than $100\text{M}\mu\text{F}$: $C < 0.01\mu\text{F}$: More than $10,000\text{M}\mu\text{F}$ -DC2-3KV: More than $6,000\text{M}\mu\text{F}$
±10%, ±20%
100V:150% Rated Voltage 630V:150% Rated Voltage 1kV-3.15kV: 120% Rated Voltage 2.5% per decade hr, typical

SMD Type-High Voltage


Application(Typical circuit)

DC-DC Converter




C2 : X7R ; 250V 10nF~47nF
C3 : COG ; 630V 47pF~100pF

Switching Power Supply




C3 : COG, X7R ; 2kV 100pF~1000pF
C4 : COG, X7R ; 2kV 100pF~1000pF

Primary circuit and Snubber switching power supply



C1, C2 : COG or X7R 1000pF~4700pF
C4 : COG ; 2kV 100pF~330pF
C5 : COG ; 1kV/2kV 100pF~470pF

LCD back light Inverter



Caution(Rating)

1. Operating Voltage

When DC-rated capacitors are to be used in AC or ripple current circuits, be sure to maintain the V_{p-p} Value of the applied voltage or the V_{0-p} which contains DC bias within the rated voltage range.

When the voltage is applied to the circuit, starting or stopping may generate irregular voltage for a transit period because of resonance or switching. Be sure to use a capacitor with a rated voltage range that includes these irregular voltages.

Voltage	DV Voltage	DC+AC Voltage	AC Voltage	Pulse Voltage(1)	Pulse Voltage(2)
Positional Measurement	V _{0-p}	V _{0-p}	V _{p-p}	V _{p-p}	V _{p-p}


2. Test condition for AC withstandning Voltage

(1) Test Equipment

Tests for AC withstandning voltage should be made with equipment capable of creating a wave similar to a 50/60 Hz sine wave. If the distorted sine wave or overload exceeding the specified voltage value is applied, a defect may be caused.

(2) Voltage applied method

The capacitor's leads or terminals should be firmly connected to the output of the withstandning voltage test equipment, and then the voltage should be raised from near zero to the test voltage. If the test voltage is applied directly to the capacitor without raising it from near zero, it should be applied with the *zero cross*. At the end of the test time, the test voltage should be reduced to near zero, and then the capacitor's leads or terminals should be taken off the output of the withstandning voltage test equipment. If the test voltage is applied directly to the capacitor without raising it from near zero, surge voltage may occur and cause a defect. *ZERO CROSS* is the point where voltage sine wave



(3) Dielectric strength testing method

In case of dielectric strength test, the capacitor's is applied between the terminations for 1 to 5 sec., provided the charge/discharge current is less than 50mA.

3. Soldering

If a chip component is heated or cooled abruptly during soldering, it may crack due to the thermal shock. To prevent this, follow our recommendations below for adequate soldering conditions. Carefully perform preheating so that temperature difference (ΔT) between the solder and component surface is in the following range. The smaller the temperatures difference (ΔT) between the solder and component surface is, the smaller the influence on the chip is.

Chip Size Soldering Method	3.2×1.6mm and under	3.2×2.5mm and over
Reflow Method or Soldering Iron Method	$\Delta T \leq 190^{\circ}\text{C}$	$\Delta T \leq 130^{\circ}\text{C}$

SMD Type

SAMWHA CAPACITOR CO., LTD offers a line of MLCC(Multilayer Ceramic Capacitor). These parts are rated at 3kV dc and safety approved and certified to UL (Underwriters Laboratories Inc. ®)

ONLINE CERTIFICATIONS DIRECTORY

OCD Home Quick Guide Contact Us UL.com

NWGQ8.E304146
Information Technology Equipment Including Electrical Business Equipment Certified for Canada - Component

[Page Bottom](#)

Information Technology Equipment Including Electrical Business Equipment Certified for Canada - Component

See General Information for Information Technology Equipment Including Electrical Business Equipment Certified for Canada - Component

SANWHA CAPACITOR CO LTD E304146
124 BUJ-01
NANSA-MTEUN
YONGIN-SI, KYONGGI-DO 449-880 REPUBLIC OF KOREA

Component Recognition, Model(s) CS45XYYTTA302NRE.

Marking: Company name, model designation and Recognized Component Mark for Canada, 
Last Updated on 2006-04-28

[Questions?](#) [Notice of Disclaimer](#) [Page Top](#)

Copyright © 2006 Underwriters Laboratories Inc. ®


The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Design and/or Listings (file) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2006 Underwriters Laboratories Inc. ®"

Reliability and Test Conditions(General Type)

No.	Item	Characteristic						Test Methods and Conditions
		Temperature Compensating Type		High Dielectric Constant Type				
1	Operating Temperature Range	C0G : -55 to +125°C	X7R : -55 to +125°C	X5R : -55 to +85°C	Y5V : -30 to +85°C			
2	Insulation Resistance	More than 10,000MΩ or 500ΩF (Whichever is smaller)						- Applied the rated voltage for 2 minutes of charging. - The charge/discharge current is less than 50mA.
3	Dielectric Strength	No defects or abnormalities						- C0G : The rated voltage ×300% - X7R, X5R, Y5V : ×250% - Applied between the terminations for 1 to 5 seconds. - The charge/discharge current is less than 50mA.
4	Capacitance	Within the specified tolerance						
5	Dissipation Factor	30pF Min. : Q≥1,000 (DF≤0.1%)	X7R : ≤25%/ X5R : ≤5%/ Y5V : ≤9%	25V : ≤3%/ *≤7%/ *≤10%	16V : ≤3.5%/ *≤7%/ *≤10%	10V : ≤5%/ *≤10%	6.3V : ≤5%/ *≤10%	The capacitance/Q.D.F. should be measured at 25°C at the frequency and voltage shown in the table.
		30pF Max. : Q≥400+20C (DF≤1/(400+20C))	Y5V : ≤58%/ *≤9%	25V : ≤7%/ *≤9%	16V : ≤9%/ *≤12.5%	10V : ≤12.5%/ *≤15%	6.3V : ≤15%	* You can check the specification at the appendix for each product with mark
6	Solderability of Termination	Termination should be covered with more than 75% of new solder						- Pb-Free Type Solder : 96.5Sn-3Ag-0.5Cu Solder Temperature : 240±5°C Immersion Time : 3±0.1sec - Pre-Heating : at 80-120°C for 10-30sec
7	Resistance to Soldering Heat	Appearance	No marked defect					
		Capacitance Change	Within ±2.5% or ±0.25pF (whichever is larger)	X7R, X5R : ≤ ±7.5%	Y5V : ≤ ±20%			- Preheat the capacitor at 120 to 150°C for 1 minute. (Preheating for 3225, 4520, 4532 Step1 : 100°C to 120°C, 1min Step2 : 170°C to 200°C, 1min) Immense the capacitor in a eutectic solder solution - Soldering Temp. : 260±5°C - Immersion Time : 10±0.5sec
		Dissipation Factor (or Q)	30pF Min. : Q≥1,000 (DF≤0.1%)	X7R : ≤25%/ X5R : ≤5%/ Y5V : ≤5%/ *≤9%	25V : ≤3%/ *≤7%/ *≤10%	16V : ≤3.5%/ *≤7%/ *≤10%	10V : ≤5%/ *≤10%	- Initial measurement Perform a heat treatment at 150±10°C for one hour and then let sit for 48±4 hours at room temperature. Perform the initial measurement. - Measurement after test Take it out and set it for 24±2 hours (temperature compensating type) or 48±4 hours (high dielectric constant type) then measure
	I.R.	More than 10,000MΩ or 500ΩF (Whichever is smaller)						

No.	Item	Characteristic		Test Methods and Conditions															
		Temperature Compensating Type	High Dielectric Constant Type																
8	Temperature Cycle	Appearance	No marking defects	<p>Perform the five cycles according to the four heat treatments listed in the following table.</p> <table border="1"> <thead> <tr> <th>Step</th> <th>1</th> <th>2</th> <th>3</th> <th>4</th> </tr> </thead> <tbody> <tr> <td>Temp. (°C)</td> <td>Min. Temp. +0, -3</td> <td>Room Temp.</td> <td>Max. Operating Temp. +3, -0</td> <td>Room Temp.</td> </tr> <tr> <td>Time (Min.)</td> <td>30±3</td> <td>2 to 3</td> <td>30±3</td> <td>2 to 3</td> </tr> </tbody> </table> <p>-Initial measurement Perform a heat treatment at 150+0, -10°C for one hour and then let sit for 48±4 hours at room temperature. -Measurement after test Take it out and set it for 24±2 hours (temperature compensating) or 48±4 hours(high dielectric constant type) at room temperature, then measure.</p>	Step	1	2	3	4	Temp. (°C)	Min. Temp. +0, -3	Room Temp.	Max. Operating Temp. +3, -0	Room Temp.	Time (Min.)	30±3	2 to 3	30±3	2 to 3
Step	1	2	3	4															
Temp. (°C)	Min. Temp. +0, -3	Room Temp.	Max. Operating Temp. +3, -0	Room Temp.															
Time (Min.)	30±3	2 to 3	30±3	2 to 3															
Capacitance Change	Within ±2.5% or ±0.25μF (whichever is larger) X7R, X5R : Within ±7.5% Y5V : Within ±20%																		
Dissipation Factor (or Q)	30μF Min. : Q≥1,000 (DF≤0.1%) 30μF Max. : Q≥400+20C (DF≤1/(400+20C))																		
I.R.	More than 10,000MΩ or 500F (Whichever is smaller)																		
9	Humidity Load	Appearance	No marking defects	<ul style="list-style-type: none"> -Temperature : 40±2°C -Humidity : 90~95% -Hour : 500±12hrs -Test Voltage : The rated voltage -Take it out and set it for 24±2 hours (temperature compensating) or 48±4 hours(high dielectric constant type) at room temperature, then measure. The charge/discharge current is less than 50mA 															
		Capacitance Change	Within ±7.5% or ±0.75μF (whichever is larger) X7R, X5R : Within ±12.5% Y5V : Within ±30% (30%, -40% (Y5V/1.0μF, 2.2μF, 4.7μF/10V)) Within ±30% (others)																
		Dissipation Factor (or Q)	30μF Min. : Q≥200 (DF≤0.5%) 30μF Max. : Q≥100+10/3C (DF≤1/(100+10/3C))																
		I.R.	More than 500MΩ or 25Q, F (Whichever is smaller)																
10	High Temperature Load	Appearance	No marking defects	<ul style="list-style-type: none"> - Testing time : 1000±12hrs - Applied voltage : Rated voltage < DC250V : ×200% - Temperature : COG, X7R → 125±3°C X5R, Y5V → 85±3°C - Measurement after test Take it out and set it for 24±2 hours (temperature compensating type) or 48±4 hours (high dielectric constant type) at room temperature, then measure. The charge/discharge current is less than 50mA. 															
		Capacitance Change	Within ±3% or ±0.3μF (whichever is larger) X7R, X5R : Within ±12.5% Y5V : Within ±30% (Cap. < 1.0μF) Within +30%, -40% (Cap. ≥ 1.0μF)																
		Dissipation Factor (or Q)	30μF Min. : Q≥350 (DF≤0.3%) 10μF ≤ Cp ≤ 30μF : Q≥275+5/2C (DF≤1/(275+5/2C)) 10μF Max. : Q≥200+10C (DF≤1/(200+10C))																
		I.R.	More than 10,000MΩ or 500F (Whichever is Smaller)																

No.	Item	Characteristic		Test Methods and Conditions																											
		Temperature Compensating Type	High Dielectric Constant Type																												
11	Bending Strength		<p>No cracking or marking defects shall occur</p> <table border="1"> <thead> <tr> <th>Char.</th> <th>50V Min.</th> <th>25V</th> <th>16V</th> <th>10V</th> <th>6.3V</th> </tr> </thead> <tbody> <tr> <td>X7R</td> <td>≤25%</td> <td>≤3%</td> <td>≤35%</td> <td>≤5%</td> <td>≤55%</td> </tr> <tr> <td>X5R</td> <td>*≤5%</td> <td>*≤7%</td> <td>*≤7%</td> <td>*≤10%</td> <td>*≤10%</td> </tr> <tr> <td>Y5V</td> <td>≤5%</td> <td>≤7%</td> <td>≤9%</td> <td>≤12.5%</td> <td>≤15%</td> </tr> </tbody> </table>	Char.	50V Min.	25V	16V	10V	6.3V	X7R	≤25%	≤3%	≤35%	≤5%	≤55%	X5R	*≤5%	*≤7%	*≤7%	*≤10%	*≤10%	Y5V	≤5%	≤7%	≤9%	≤12.5%	≤15%	<ul style="list-style-type: none"> -Substrate Material : Glass EPOXY Board -Board Thickness : 1.6mm -0.8mm(0603/1005size) * Test Condition -Bending Limit : 1mm -Pressurizing Speed : 1mm/sec 			
Char.	50V Min.	25V	16V	10V	6.3V																										
X7R	≤25%	≤3%	≤35%	≤5%	≤55%																										
X5R	*≤5%	*≤7%	*≤7%	*≤10%	*≤10%																										
Y5V	≤5%	≤7%	≤9%	≤12.5%	≤15%																										
12	Vibration Resistance	<ul style="list-style-type: none"> Appearance : No defects or abnormalities Capacitance : Within the specified tolerance 	<table border="1"> <thead> <tr> <th>Q/DF</th> <th>30μF Min. : Q 1,000 (DF 0.1%)</th> <th>30μF Max. : Q 400+20C (DF 1/(400+20C))</th> <th>Char.</th> <th>50V Min.</th> <th>25V</th> <th>16V</th> <th>10V</th> <th>6.3V</th> </tr> </thead> <tbody> <tr> <td>X7R</td> <td>XTR ≤25% XSR *≤5%</td> <td>X7R ≤25% XSR *≤5%</td> <td>X7R</td> <td>≤25%</td> <td>≤3%</td> <td>≤35%</td> <td>≤5%</td> <td>≤55%</td> </tr> <tr> <td>Y5V</td> <td>Y5V ≤5% *≤7% *≤9%</td> <td>Y5V ≤5% *≤12.5% *≤15%</td> <td>Y5V</td> <td>≤5%</td> <td>≤7%</td> <td>≤9%</td> <td>≤12.5%</td> <td>≤15%</td> </tr> </tbody> </table>	Q/DF	30μF Min. : Q 1,000 (DF 0.1%)	30μF Max. : Q 400+20C (DF 1/(400+20C))	Char.	50V Min.	25V	16V	10V	6.3V	X7R	XTR ≤25% XSR *≤5%	X7R ≤25% XSR *≤5%	X7R	≤25%	≤3%	≤35%	≤5%	≤55%	Y5V	Y5V ≤5% *≤7% *≤9%	Y5V ≤5% *≤12.5% *≤15%	Y5V	≤5%	≤7%	≤9%	≤12.5%	≤15%	<ul style="list-style-type: none"> * Shown in Fig. After soldering and then let sit for 24±4hr (temperature compensating type), 48±4hr (high dielectric constant type) at room temperature. The capacitor should be subjected to a simple harmonic motion having a total amplitude of 1.5mm, the frequency being varied uniformly between the approximate limits of 10 and 55Hz, shall be traversed (from 10Hz to 55Hz then 10Hz again) in approximately 1 minute. This motion shall be applied for a period of 2 hours in each 3 mutually perpendicular directions (total is 6 hours).
Q/DF	30μF Min. : Q 1,000 (DF 0.1%)	30μF Max. : Q 400+20C (DF 1/(400+20C))	Char.	50V Min.	25V	16V	10V	6.3V																							
X7R	XTR ≤25% XSR *≤5%	X7R ≤25% XSR *≤5%	X7R	≤25%	≤3%	≤35%	≤5%	≤55%																							
Y5V	Y5V ≤5% *≤7% *≤9%	Y5V ≤5% *≤12.5% *≤15%	Y5V	≤5%	≤7%	≤9%	≤12.5%	≤15%																							
13	Humidity Steady State	<ul style="list-style-type: none"> Appearance : No marking defects Capacitance Change : Within ±5% or ±0.5μF (whichever is larger) 	<table border="1"> <thead> <tr> <th>Dissipation (or Q)</th> <th>30μF Min. : Q≥350 (DF≤0.3%)</th> <th>10μF ≤ Cp ≤ 30μF : Q≥275+5/2C (DF≤1/(275+5/2C))</th> <th>Char.</th> <th>50V Min.</th> <th>25V</th> <th>16V</th> <th>10V</th> <th>6.3V</th> </tr> </thead> <tbody> <tr> <td>X7R</td> <td>XTR ≤55% XSR *≤75% *≤10%</td> <td>X7R ≤55% XSR *≤10% *≤12.5% *≤15%</td> <td>X7R</td> <td>≤55%</td> <td>≤5%</td> <td>≤75%</td> <td>≤10%</td> <td>≤75%</td> </tr> <tr> <td>Y5V</td> <td>Y5V ≤12.5% *≤12.5% *≤15%</td> <td>Y5V ≤12.5% *≤15% *≤20%</td> <td>Y5V</td> <td>≤12.5%</td> <td>≤15%</td> <td>≤20%</td> <td>≤20%</td> <td>≤20%</td> </tr> </tbody> </table>	Dissipation (or Q)	30μF Min. : Q≥350 (DF≤0.3%)	10μF ≤ Cp ≤ 30μF : Q≥275+5/2C (DF≤1/(275+5/2C))	Char.	50V Min.	25V	16V	10V	6.3V	X7R	XTR ≤55% XSR *≤75% *≤10%	X7R ≤55% XSR *≤10% *≤12.5% *≤15%	X7R	≤55%	≤5%	≤75%	≤10%	≤75%	Y5V	Y5V ≤12.5% *≤12.5% *≤15%	Y5V ≤12.5% *≤15% *≤20%	Y5V	≤12.5%	≤15%	≤20%	≤20%	≤20%	<ul style="list-style-type: none"> -Temperature : 40±2°C -Humidity : 90~95% -Hour : 500±12hours -Measurement after test Take it out and set it for 24±2 hours (temperature compensating type) or 48±4 hours (high dielectric constant type) at room temperature, then measure.
Dissipation (or Q)	30μF Min. : Q≥350 (DF≤0.3%)	10μF ≤ Cp ≤ 30μF : Q≥275+5/2C (DF≤1/(275+5/2C))	Char.	50V Min.	25V	16V	10V	6.3V																							
X7R	XTR ≤55% XSR *≤75% *≤10%	X7R ≤55% XSR *≤10% *≤12.5% *≤15%	X7R	≤55%	≤5%	≤75%	≤10%	≤75%																							
Y5V	Y5V ≤12.5% *≤12.5% *≤15%	Y5V ≤12.5% *≤15% *≤20%	Y5V	≤12.5%	≤15%	≤20%	≤20%	≤20%																							

No.	Item	Characteristic				Test Methods and Conditions
		Temperature Compensating Type		High Dielectric Constant Type		
14	Capacitance Temperature Characteristics					<p>(1) Temperature Compensating Type: The temperature coefficient is determined using the capacitance measured in step 3 as a reference. When cycling the temperature sequentially from step 1 through 5, (COG: +25 to 125°C) the capacitance shall be within the specified tolerance for the temperature coefficient. The capacitance drift is calculated by dividing the difference between the maximum measured values in the step 1, 3 and 5 by the Cap. value in step 3</p>
15	Preservation(keeping)					<p>(1) When solderability is considered, capacitors are recommended to be used in 12 months (2) Relative Humidity : Below 70% RH</p>
16	The regulation of environmental pollution materials.					Never use materials mentioned below in MLCC products regulated this document. Pb, Cd, Hg, Cr+6, PBB(polybromide biphenyl), PBDE(polybrominated diphenyl ethers), asbestos.

- In case of high Voltage and thin layer type Capacitor, it can be different from normal specification.
So Please ask to our sales person.

Radial & Axial

Features

This widely used ceramic capacitors includes both monolithic and multilayer types to provide a wide capacitance range of 1pF through 1μF in respectively one standard size and shape(Radial & Axial).


Applications

The class1 temperature compensating(COG) products can be used in circuits to stabilize frequency and temperature characteristics.
The X7R, Z5U, Y5V dielectrics are optimum for by pass capacitors.

Shape and Dimensions

Bulk Type


Radial Type




CODE	L Max.	W Max.	T Max.	H Max.	P ±0.7	Ød	Color	Marking
051B	5.5	5.5	3.2	6.4		5	0.5	Orange or Gold
077B	7.7	7.6		9.2				Ex) 104

Flat Type

Radial Type



Axial Type



Radial & Axial

Code	Dimensions	Tolerance	Code	Dimensions	Tolerance
D(Ø)	4	±0.3	P1	3.85	±0.7
H	16	±0.5	P2	6.35	±1.3
H1	9	+0.76, -0.5	T	0.9	Max.
H2	0	±2	W1	18	±0.5
L	11	Max.	W2	0	+0.6 Max.
L1	1.5	Max.	S	5	±0.7
P	12.7	±0.3	*	No adhesive may be exposed	

Code	Dimensions	Tolerance
F	64.8	-0, +2
G	50.8-53.3	
H	=J	±1.2
J	=H	±1.2
K	0.8	Max.
N	5	±0.4
R	3.2	Min.

How to Order (Product Identification)

CA 2633 Y5V 104 Z 500 F



1 Type

CR : Radial Lead Type
CA : Axial Lead Type

2 Dimension Code

The number shows the maximum length of "L" by 1/10 in millimeter, and the alphabet means lead difference.(Refer to above diagram)

3 Temperature Coefficient Code

Temperature Characteristic	Temperature Range	Capacitance Change or Temperature Coefficient
COG	-55 to 125°C	0±30ppm/°C
X7R	-55 to 125°C	±15%
Z5U	10°C to 85°C	+22, -56%
Y5V	-30 to 85°C	+22, -82%

4 Capacitance Code(Pico Farads)

First two digits are significant; third digit denotes number of zeros.
Ex.) 101 = 100pF, 1R5 = 1.5pF, 103 = 10,000pF

5 Capacitance Tolerance Code

Code	Tolerance	Remark
J	± 5.0 %	COG
K	±10 %	X7R, COG
M	± 20 %	Z5U, X7R
Z	+80, -20%	Z5U, Y5V

6 Rated Voltage Code

Code	250	500	101
Volt	DC 25V	DC 50V	DC 100V

7 Packing Code

Code	B	R	F
Packing	Bulk	Reel Pack	Flat Pack

Reliability and Test Conditions

No.	Item	Characteristic					Test Methods and Conditions
		Temperature Compensating Type	High Dielectric Constant Type				
1.	Operating Temperature Range	COG : -55 to +125°C X7R : -55 to +125°C Z5U : 10°C to 85°C Y5V : -30 to 85°C	X7R : -55 to +125°C Z5U : +10 to +85°C Y5V : -30 to 85°C				
2.	Insulation Resistance	More than 10,000MΩ or 500Ω, F (whichever is smaller)					Applied the rated voltage for 2 minute
3.	Dielectric Strength	No detects or abnormalities					- COG : The rated voltage × 300% - X7R, Z5U, Y5V : × 250%
4.	Capacitance	Within the specified tolerance					Temperature Compensating Type
5.	Dissipation Factor	30pF Min. : Q ≥ 1,000 (DF ≤ 0.1%) 30pF Max. : Q ≥ 400+20C (DF ≤ 1/(400+20C))	Char. 50V Min. 25V 16V 10V X7R ≤ 25% ≤ 3% ≤ 35% ≤ 50% Z5U ≤ 4.0% - - - Y5V ≤ 5% (≤ 220fF) ≤ 9% (≥ 220fF) ≤ 12.5% (≥ 220fF) ≤ 7% (≥ 220fF) ≤ 12.5% (≥ 220fF)	Cap. COG (C ≤ 1000pF) COG (C) 1000pF X7R, Z5U, Y5V (C ≤ 10fF 10V Min.)	Testing Frequency 1±0.1MHz 1±0.1kHz 1±0.2V rms 1±0.1kHz 1±0.2V rms	Testing Voltage 0.5 to 5V ms 1±0.2V ms 1±0.2V ms	
6.	Terminal Strength	No evidence of damage to body of device or looseness of terminals.					A static load of 10N(1kgf) : applied to one terminal in the axial direction and acting in a direction away from the body for 1 to 5 secs.

Capacitance Range

Type Char. Cap(pF) \ Volt	Radial								Axial			
	COG		X7R		Z5U		Y5V		COG		X7R	
	50	100	50	100	50	16	50	50	50	50	50	50
1												
2												
3												
4												
5												
6												
7												
8												
9												
10												
12												
15												
16												
18												
20												
22												
24												
27												
30												
33												
36												
39												
43												
47												
51												
56												
62												
68												
75												
82												
91												
100												
120												
150												
180												
220												
270												
330												
390												
470												
560												
680												
820												
1.000												
1.200												
1.500												
1.800												
2.200												
2.700												
3.300												
3.900												
4.700												
5.600												
6.800												
8.200												
10.000												
15.000												
22.000												
33.000												
47.000												
68.000												
100.000												
150.000												
220.000												
330.000												
470.000												
680.000												
1.000.000												