FEATURES

* 0.4 inch (10 mm) DIGIT HEIGHT.
* CONTINUOUS UNIFORM SEGMENTS.
* LOW POWER REQUIREMENT.
* EXCELLENT CHARACTERS APPEARANCE.
* HIGH BRIGHTNESS & HIGH CONTRAST.
* WIDE VIEWING ANGLE.
* SOLID STATE RELIABILITY.
* CATEGORIZED FOR LUMINOUS INTENSITY.

DESCRIPTION

The LTC-4624HG-02 is a 0.4 inch (10 mm) digit height triple digit seven-segment display. This device utilizes green LED chips, which are made from GaP on a transparent GaP substrate, and has a gray face and white segments.

DEVICE

PART NO.	DESCRIPTION
GREEN	MULTIPLEX COMMON ANODE
LTC-4624HG-02	RT.HAND DECIMAL

Downloaded from Elcodis.com electronic components distributor

PACKAGE DIMENSIONS



NOTES: All dimensions are in millimeters. Tolerance is ± 0.25 mm (0.01“) unless otherwise noted.

INTERNAL CIRCUIT DIAGRAM



Downloaded from Elcodis.com electronic components distributor

PIN CONNECTION

No.	CONNECTION
1	COMMON ANODE DIGIT 1
2	CATHODE E
3	CATHODE C, L3
4	CATHODE D
5	COMMON ANODE DIGIT 2
6	CATHODE DP
7	COMMON ANODE DIGIT 3
8	CATHODE G
9	NO PIN
10	NO PIN
11	CATHODE B, L2
12	CATHODE A, L1
13	NO PIN
14	COMMON ANODE L1, L2, L3
15	CATHODE F

Downloaded from Elcodis.com electronic components distributor

ABSOLUTE MAXIMUM RATING AT Ta=25°C

PARAMETER	MAXIMUM RATING	UNIT
Power Dissipation Per Segment	75	mW
Peak Forward Current Per Segment (1/10 Duty Cycle, 0.1ms Pulse Width)	100	mA
Continuous Forward Current Per Segment Derating Linear From 25℃ Per Segment	25 0.28	mA mA/℃
Reverse Voltage Per Segment	5	V
Operating Temperature Range	-35℃ to +105℃	
Storage Temperature Range	-35℃ to +105℃	
Solder Temperature: max 260℃ for max 3sec at 1.6mm[1/16inch] below seating plane.		

ELECTRICAL / OPTICAL CHARACTERISTICS AT Ta=25°C

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Average Luminous Intensity	I_V	1300	3100		μcd	I_F=10mA
Peak Emission Wavelength	λp		565		nm	I_F=20mA
Spectral Line Half-Width	Δλ		30		nm	I_F=20mA
Dominant Wavelength	λd		569		nm	I_F=20mA
Forward Voltage Per Segment	V_F		2.1	2.6	V	I_F=20mA
Reverse Current Per Segment	I_R			100	μA	V_R=5V
Luminous Intensity Matching Ratio	I_V-m			2:1		I_F=10mA

Note: Luminous intensity is measured with a light sensor and filter combination that approximates the CIE (Commision Internationale De L'Eclairage) eye-response curve.

Downloaded from Elcodis.com electronic components distributor

TYPICAL ELECTRICAL / OPTICAL CHARACTERISTIC CURVES

(25°C Ambient Temperature Unless Otherwise Noted)



Fig1. RELATIVE INTENSITY VS. WAVELENGTH



Fig2. RELATIVE LUMINOUS EFFICIENCY (LUMINOUS INTENSITY PER UNIT CURRENT) VS. PEAK CURRENT



Fig3. FORWARD CURRENT VS. FORWARD VOLTAGE



Fig4. RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT



Fig5. MAX. ALLOWABLE DC CURRENT VS. AMBIENT TEMPERATURE.



Fig6. MAX. PEAK CURRENT VS. DUTY CYCLE % (REFRESH RATE 1KHz)

NOTE : G=GREEN (REFRESH RATE 1KHz)

Downloaded from Elcodis.com electronic components distributor