

FEATURES

- *0.4 inch (10.21 mm) DIGIT HEIGHT
- *EXCELLENT SEGMENT UNIFORMITY
- *LOW POWER REQUIREMENT
- *HIGH BRIGHTNESS AND HIGH CONTRAST
- *WIDE VIEWING ANGLE
- *SOLID STATE RELIABILITY


DESCRIPTION

The LTC-4620AHR is a 0.4 inch (10.21 mm) digit height quadruple display. This device uses HI-EFF. RED LED chips (GaAsP epi on GaP substrate). The display has gray face and red segments.

DEVICE


PART NO.	DESCRIPTION
HI-EFF. RED	Multiplex Common Anode
LTC-4620AHR	

PACKAGE DIMENSIONS



NOTES: All dimensions are in millimeters. Tolerances are ± 0.25 mm (0.01") unless otherwise noted.

INTERNAL CIRCUIT DIAGRAM



PIN CONNECTION

NO.	CONNECTION
1	Common Anode Digit 4
2	Cathode C
3	Cathode E
4	Cathode G
5	Cathode A
6	Common Anode Digit 3
7	Cathode UC,LC
8	Common Anode Digit 2
9	Cathode F
10	Cathode B
11	Cathode D
12	Common Anode Digit 1

ABSOLUTE MAXIMUM RATING

PARAMETER	MAXIMUM RATING	UNIT
Power Dissipation Per Segment	75	mW
Peak Forward Current Per Segment (Frequency 1Khz, 10% duty cycle)	100*	mA
Continuous Forward Current Per Segment	25	mA
Derating Linear From 25°C Per Segment	0.33	mA/°C
Reverse Voltage Per Segment	5	V
Operating Temperature Range	-35°C to +105°C	
Storage Temperature Range	-35°C to +105°C	
Solder Temperature: max 260°C for max 3sec at 1.6mm below seating plane.		

* see figure 5 to establish pulsed condition

ELECTRICAL / OPTICAL CHARACTERISTICS AT Ta=25°C

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Average Luminous Intensity	I _v	1300	3100		μcd	I _F =10mA
Peak Emission Wavelength	λ _p		635		nm	I _F =20mA
Spectral Line Half-Width	Δλ		40		nm	I _F =20mA
Dominant Wavelength	λ _d		623		nm	I _F =20mA
Forward Voltage Per Segment	V _F		2.1	2.6	V	I _F =20mA
Reverse Current Per Segment	I _R			100	μA	V _R =5V
Luminous Intensity Matching Ratio	I _v -m			2:1		I _F =10mA

Note: Luminous intensity is measured with a light sensor and filter combination that approximates the CIE (Commision Internationale De L'Eclairage) eye-response curve.

TYPICAL ELECTRICAL / OPTICAL CHARACTERISTIC CURVES

(25°C Ambient Temperature Unless Otherwise Noted)

