

**FEATURES**

- \*0.264 INCH (6.7 mm ) DIGIT HEIGHT.
- \*CONTINUOUS UNIFORM SEGMENTS.
- \*LOW POWER REQUIREMENT.
- \*EXCELLENT CHARACTERS APPEARANCE.
- \*HIGH BRIGHTNESS & HIGH CONTRAST.
- \*WIDE VIEWING ANGLE.
- \*SOLID STATE RELIABILITY.
- \*CATEGORIZED FOR LUMINOUS INTENSITY.


**DESCRIPTION**

The LTC-3710HR-03 is a 0.264 inch (6.7 mm) height quadruple digit seven-segment display. This device utilizes high efficiency red LED chips, which are made from GaAsP on a transparent GaP substrate, and has a red face and red segments. The device covers with protective film.

**DEVICE**


PART NO.	DESCRIPTION
HI. – EFF. RED	Multiplex
LTC-3710HR-03	Common Cathode

## PACKAGE DIMENSIONS



NOTES: All dimensions are in millimeters( inches). Tolerance:  $\pm 0.25$  mm (0.01") unless otherwise noted. The device covers with protective film.

## INTERNAL CIRCUIT DIAGRAM



**PIN CONNECTION**

NO	CONNECTION	NO	CONNECTION
1	Anode L3	13	Cathode U.D.P
2	Common Cathode Digit 1	14	Cathode D.P.2
3	Anode D, Digit 1,2,3,4	15	Anode U.D.P
4	Anode L2	16	Cathode D.P.I
5	Common Cathode Digit 2	17	Anode A, Digit 1,2,3,4
6	Cathode UC, LC	18	Anode F, Digit 1,2,3,4
7	Anode UC, LC	19	Anode B, Digit 1,2,3,4
8	Common Cathode Digit 3	20	Anode C, Digit 1,2,3,4
9	Anode D.P.I	21	Anode E, Digit 1
10	Common Cathode Digit 4	22	Anode G, Digit 1,2,3,4
11	Anode E Digit 2,3,4	23	Anode L1
12	Anode D.P.2	24	Cathode L1,L2,L3

**ABSOLUTE MAXIMUM RATING AT Ta=25°C**

PARAMETER	MAXIMUM RATING	UNIT
Power Dissipation Per Segment	75	mW
Peak Forward Current Per Segment (1/10 Duty Cycle, 0.1ms Pulse Width )	100	mA
Continuous Forward Current Per Segment	25	mA
Derating Linear From 25°C Per Segment	0.33	mA/°C
Reverse Voltage Per Segment	5	V
Operating Temperature Range	-35°C to +85°C	
Storage Temperature Range	-35°C to +85°C	
Solder Temperature: max 260°C for max 3sec at 1.6mm[1/16inch] below seating plane.		

**ELECTRICAL / OPTICAL CHARACTERISTICS AT Ta=25°C**

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Average Luminous Intensity	I <sub>v</sub>	800	2000		μcd	I <sub>F</sub> =10mA
Peak Emission Wavelength	λ <sub>p</sub>		635		nm	I <sub>F</sub> =20mA
Spectral Line Half-Width	Δλ		40		nm	I <sub>F</sub> =20mA
Dominant Wavelength	λ <sub>d</sub>		623		nm	I <sub>F</sub> =20mA
Forward Voltage. Per Segment	V <sub>F</sub>		2.0	2.6	V	I <sub>F</sub> =20mA
Reverse Current, Per Segment	I <sub>R</sub>			100	μA	V <sub>R</sub> =5V
Luminous Intensity Matching Ratio	I <sub>v</sub> -m			2:1		I <sub>F</sub> =10mA

Note: Luminous intensity is measured with a light sensor and filter combination that approximates the CIE ( Commission Internationale De L'Eclairage ) eye-response curve.

## TYPICAL ELECTRICAL / OPTICAL CHARACTERISTIC CURVES

(25°C Ambient Temperature Unless Otherwise Noted)




Fig.1. RELATIVE INTENSITY VS. WAVELENGTH




Fig.2. RELATIVE LUMINOUS EFFICIENCY (LUMINOUS INTENSITY PER UNIT CURRENT) VS. PEAK CURRENT (REFRESH RATE 1KHz)




Fig.3. FORWARD CURRENT VS. FORWARD VOLTAGE




Fig.4. RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




Fig.5. MAX. ALLOWABLE DC CURRENT VS. AMBIENT TEMPERATURE.




Fig.6. MAX. PEAK CURRENT VS. DUTY CYCLE % (REFRESH RATE 1KHz)

NOTE: HR=HL - EFF. RED