




Model Number

NCB10-30GM40-Z1-3G-3D

Features

- Comfort series
- 10 mm embeddable
- ATEX-approval for zone 2 and zone 22

Connection




Accessories

BF 30

Mounting flange, 30 mm

Dimensions



Technical Data

General specifications

| | | | |
|----------------------------|-------|--------------|----|
| Switching element function | | DC | NC |
| Rated operating distance | s_n | 10 mm | |
| Installation | | embeddable | |
| Output polarity | | DC | |
| Assured operating distance | s_a | 0 ... 8.1 mm | |
| Reduction factor r_{Al} | | 0.32 | |
| Reduction factor r_{Cu} | | 0.28 | |
| Reduction factor r_{V2A} | | 0.7 | |

Nominal ratings

| | | |
|-----------------------------------|-------|---------------------------|
| Operating voltage | U_B | 5 ... 60 V |
| Switching frequency | f | 0 ... 150 Hz |
| Hysteresis | H | 1 ... 10 typ. 5 % |
| Reverse polarity protected | | tolerant |
| Short-circuit protection | | pulsing |
| Voltage drop | U_d | ≤ 5 V |
| Operating current | I_L | 2 ... 100 mA |
| Lowest operating current | I_m | 2 mA |
| Off-state current | I_r | 0 ... 0.5 mA typ. |
| Indication of the switching state | | all direction LED, yellow |

Ambient conditions

| | |
|---------------------|--------------------------------|
| Ambient temperature | -25 ... 70 °C (-13 ... 158 °F) |
| Storage temperature | -40 ... 85 °C (-40 ... 185 °F) |

Mechanical specifications

| | |
|--------------------|----------------------|
| Connection type | cable PVC , 2 m |
| Cable version | PA |
| Core cross-section | 0.34 mm ² |
| Housing material | Stainless steel |
| Sensing face | PBT |
| Protection degree | IP67 |

General information

| | |
|---------------------------|-------------------------|
| Use in the hazardous area | see instruction manuals |
| Category | 3G; 3D |

Compliance with standards and directives

| | |
|---------------------|---|
| Standard conformity | |
| Standards | EN 60947-5-2:2007 IEC 60947-5-2:2007 |

Approvals and certificates

| | |
|--------------|--|
| UL approval | cULus Listed, General Purpose |
| CSA approval | cCSAus Listed, General Purpose |
| CCC approval | Products with a maximum operating voltage of ≤ 36 V do not bear a CCC marking because they do not require approval. |

ATEX 3G (nA)

| | |
|--|---|
| Instruction | Manual electrical apparatus for hazardous areas |
| Device category 3G (nA) | for use in hazardous areas with gas, vapour and mist |
| Directive conformity | 94/9/EG |
| Standard conformity | EN 60079-0:2006, EN 60079-15:2005 |
| | Ignition protection category "n" |
| | Use is restricted to the following stated conditions |
| CE symbol | CE |
| Ex-identification | Ex II 3G Ex nA IIC T6 X |
| General | The apparatus has to be operated according to the appropriate data in the data sheet and in this instruction manual. The data stated in the data sheet are restricted by this operating instruction! The special conditions must be observed! |
| Installation, Commissioning | Laws and/or regulations and standards governing the use or intended usage goal must be observed. |
| Maintenance | No changes can be made to apparatus, which are operated in hazardous areas. Repairs to these apparatus are not possible. |
| Special conditions | |
| Maximum operating current I_L | The maximum permissible load current must be restricted to the values given in the following list. High load currents and load short-circuits are not permitted. |
| Maximum operating voltage U_{Bmax} | The maximum permissible operating voltage U_B max is restricted to the values in the following list. Tolerances are not permissible. |
| Maximum permissible ambient temperature T_{Umax} | dependant of the load current I_L and the max. operating voltage U_{Bmax} . Information can be taken from the following list. |
| at $U_{Bmax}=60$ V, $I_L=100$ mA | 53 °C (127.4 °F) |
| at $U_{Bmax}=60$ V, $I_L=50$ mA | 58 °C (136.4 °F) |
| at $U_{Bmax}=60$ V, $I_L=25$ mA | 61 °C (141.8 °F) |
| Protection from mechanical danger | The sensor must not be exposed to ANY FORM of mechanical danger. |
| Protection from UV light | The sensor and the connection cable must be protected from damaging UV-radiation. This can be achieved when the sensor is used in internal areas. |
| Electrostatic charging | Electrostatic charges must be avoided on the mechanical housing components. Dangerous electrostatic charges on the mechanical housing components can be avoided by incorporating these in the equipotential bonding. |
| Protection of the connection cable | The connection cable must be prevented from being subjected to tension and torsional loading. |

ATEX 3D (tD)

| | |
|--|---|
| Instruction | Manual electrical apparatus for hazardous areas |
| Device category 3D | for use in hazardous areas with combustible dust |
| Directive conformity | 94/9/EG |
| Standard conformity | EN 61241-0:2006, EN 61241-1:2004 |
| CE symbol | Protection via housing "tD" Use is restricted to the following stated conditions CE |
| Ex-identification | Ex II 3D Ex tD A22 IP67 T80°C X |
| General | The apparatus has to be operated according to the appropriate data in the data sheet and in this instruction manual. The maximum surface temperature has been determined in accordance with method A without a dust layer on the equipment. The data stated in the data sheet are restricted by this operating instruction! The special conditions must be adhered to! |
| Installation, Commissioning | Laws and/or regulations and standards governing the use or intended usage goal must be observed. |
| Maintenance | No changes can be made to apparatus, which are operated in hazardous areas. Repairs to these apparatus are not possible. |
| Special conditions | |
| Maximum operating current I_L | The maximum permissible load current must be restricted to the values given in the following list. High load currents and load short-circuits are not permitted. |
| Maximum operating voltage U_{Bmax} | The maximum permissible operating voltage U_{Bmax} must be restricted to the values given in the following list. Tolerances are not permitted. |
| Maximum permissible ambient temperature T_{Umax} | dependant of the load current I_L and the max. operating voltage U_{Bmax} . Information can be taken from the following list. |
| at $U_{Bmax}=60\text{ V}$, $I_L=100\text{ mA}$ | 53 °C (127.4 °F) |
| at $U_{Bmax}=60\text{ V}$, $I_L=50\text{ mA}$ | 58 °C (136.4 °F) |
| at $U_{Bmax}=60\text{ V}$, $I_L=25\text{ mA}$ | 61 °C (141.8 °F) |
| Protection from mechanical danger | The sensor must not be exposed to ANY FORM of mechanical danger. |
| Protection from UV light | The sensor and the connection cable must be protected from damaging UV-radiation. This can be achieved when the sensor is used in internal areas. |
| Electrostatic charging | Electrostatic charges must be avoided on the mechanical housing components. Dangerous electrostatic charges on the mechanical housing components can be avoided by incorporating these in the equipotential bonding. Sliding contact discharges must be avoided. |
| Protection of the connection cable | The connection cable must be prevented from being subjected to tension and torsional loading. |