



SPECIFICATIONS

RESISTANCE VALUE AND TOLERANCE:
 $R_{25C} = 100 \text{ OHMS } \pm 1\%$
 MIL-R-23648/1 QUALIFIED

OTHER ELECTRICAL CHARACTERISTICS:
 RATIO 19:8 (A)

LEADS:
 #24 AWG TPC
 QTC-4F

HOUSING:
 DIALYL PHTHALATE HOUSING
 QT01005-008

OTHER MECHANICAL SPECIFICATIONS:

NOTES:

DISSIPATION CONST=5mW/C MIN
 TIME CONSTANT=80 SEC. MAX
 POWER RATING: 0.5 W @25C MIN.
 DIMENSION IN INCHES,
 (MILLIMETERS IN PARENTHESES)



QUALITY THERMISTOR INC.
 2108 CENTURY WAY
 BOISE, ID 83709
 PH: 208-377-3373
 FAX: 208-376-4754

DESCRIPTION: Y, 100 OHMS, 1%,
 QTI PART NUMBER: RTH06AS101F
 REV: -

SCALE 2" = 1"

NOTE: DRAWING FOR REFERENCE ONLY. IN THE EVENT OF CONFLICT BETWEEN THIS DRAWING AND MIL-R-23648/1, MIL-R-23648/1 SHALL TAKE PRECEDENCE.

THIS DRAWING AND THE INFORMATION IS THE PROPERTY OF QUALITY THERMISTOR AND ALL UNAUTHORIZED USE AND REPRODUCTION IS PROHIBITED

ND.	DATE	REVISION	APPROVAL
1	6-28-00	-	JK

TOLERANCES:	JOB NUMBER:	PAGE
X = 0, 1"		1 / 1
XX = 0, 02"		
XXX = 0, 001"		