


NOTE: DRAWING FOR REFERENCE ONLY. IN THE EVENT OF CONFLICT BETWEEN THIS DRAWING AND MIL-R-23648/1, MIL-R-23648/1 SHALL TAKE PRECEDENCE.

SCALE 2" = 1"

THIS DRAWING AND THE INFORMATION IS THE PROPERTY OF QUALITY THERMISTOR AND ALL UNAUTHORIZED USE AND REPRODUCTION IS PROHIBITED

ND.	DATE	REVISION	APPROVAL
1	6-28-00	-	JK

		QUALITY THERMISTOR INC. 2108 CENTURY WAY BOISE, ID 83709 PH: 208-377-3373 FAX: 208-376-4754	
DRAWING FILE NAME: 06ASS201J		ORIGINATOR:	DATE:
ENGINEER:		ENGINEER:	DATE:
SALES MGR.:		SALES MGR.:	DATE:
QUALITY MGR.:		QUALITY MGR.:	DATE:
PRDD. MGR.:		PRDD. MGR.:	DATE:
DESCRIPTION:	Y, 200 DHMS, 5%,		
TOLERANCES:	X = 0, 1"	JOB NUMBER:	RTH06ASS201J
	XX = 0, 02"		
	XXX = 0, 001"	PAGE	1 / 1

SPECIFICATIONS
RESISTANCE VALUE AND TOLERANCE: R@25C = 200 DHMS +/- 5% MIL-R-23648/1 QUALIFIED
OTHER ELECTRICAL CHARACTERISTICS: RATID 19.8 (A)
LEADS: #24 AWG TPC QTC-4F
HOUSING: DIALYL PHTHALATE HOUSING QT01005-008
OTHER MECHANICAL SPECIFICATIONS:
NOTES: DISSIPATION CONST=5mW/C MIN TIME CONSTANT=80 SEC. MAX POWER RATING: 0.5 W @25C MIN. DIMENSION IN INCHES, (MILLIMETERS IN PARENTHESES)