


NOTE: DRAWING FOR REFERENCE ONLY. IN THE EVENT OF CONFLICT BETWEEN THIS DRAWING AND MIL-R-23648/1, MIL-R-23648/1 SHALL TAKE PRECEDENCE.

SCALE 2" = 1"

THIS DRAWING AND THE INFORMATION IS THE PROPERTY OF QUALITY THERMISTOR AND ALL UNAUTHORIZED USE AND REPRODUCTION IS PROHIBITED

ND.	DATE	REVISION	APPROVAL
1	6-28-00	-	JK

		QUALITY THERMISTOR INC. 2108 CENTURY WAY BOISE, ID 83709 PH: 208-377-3373 FAX: 208-376-4754	
DRAWING FILE NAME: 06BS122K		DESCRIPTION: Z, 1200 OHMS, 10%,	
ORIGINATOR:		DATE:	
ENGINEER:		DATE:	
SALES MGR.:		DATE:	
QUALITY MGR.:		DATE:	
PRD. MGR.:		DATE:	
QTI PART NUMBER: RTH06BS122K		REV: -	
TOLERANCES:		JOB NUMBER:	
X = 0, 1" XX = 0, 02" XXX = 0, 001"		PAGE 1 / 1	

**SPECIFICATIONS**  
 RESISTANCE VALUE AND TOLERANCE:  
 R@25C = 1200 OHMS +/- 10%  
 MIL-R-23648/1 QUALIFIED

**OTHER ELECTRICAL CHARACTERISTICS:**  
 RATIO 29.4 (B)

**LEADS:**  
 #24 AWG TPC  
 QTC-4F

**HOUSING:**  
 DIALYL PHTHALATE HOUSING  
 QT01005-008

**OTHER MECHANICAL SPECIFICATIONS:**

**NOTES:**  
 DISSIPATION CONST=5mW/C MIN  
 TIME CONSTANT=80 SEC. MAX  
 POWER RATING: 0.5 W @25C MIN.  
 DIMENSION IN INCHES,  
 (MILLIMETERS IN PARENTHESES)