




- Repetitive Avalanche Rated**
- Fast Switching Speed**
- Simple Drive Requirement**
- RoHS Compliant**




BV_{DSS}	700V
$R_{DS(ON)}$	4.4
I_D	2.5A

Description

AP03N70 series are specially designed as main switching devices for universal 90~265VAC off-line AC/DC converter applications. TO-220FM type provide high blocking voltage to overcome voltage surge and sag in the toughest power system with the best combination of fast switching, ruggedized design and cost-effectiveness.

The TO-220FM package is universally preferred for all commercial-industrial applications. The device is suited for switch mode power supplies, DC-AC converters and high current high speed switching circuits.



TO-220FM(F)

Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	700	V
V_{GS}	Gate-Source Voltage	± 30	V
$I_D @ T_c = 25$	Continuous Drain Current, $V_{GS} @ 10V$	2.5	A
$I_D @ T_c = 100$	Continuous Drain Current, $V_{GS} @ 10V$	1.6	A
I_{DM}	Pulsed Drain Current ¹	8	A
$P_D @ T_c = 25$	Total Power Dissipation	29	W
	Linear Derating Factor	0.23	W/
E_{AS}	Single Pulse Avalanche Energy ²	32	mJ
I_{AR}	Avalanche Current	2.5	A
T_{STG}	Storage Temperature Range	-55 to 150	
T_J	Operating Junction Temperature Range	-55 to 150	

Thermal Data

Symbol	Parameter	Value	Units
R_{thj-c}	Thermal Resistance Junction-case	Max. 4.3	/W
R_{thj-a}	Thermal Resistance Junction-ambient	Max. 65	/W



Electrical Characteristics@ $T_j=25^\circ\text{C}$ (unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}$, $I_D=1\text{mA}$	700	-	-	V
$\text{BV}_{\text{DSS}}/T_j$	Breakdown Voltage Temperature Coefficient	Reference to 25°C , $I_D=1\text{mA}$	-	0.6	-	V/
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{\text{GS}}=10\text{V}$, $I_D=1.6\text{A}$	-	-	4.4	
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{\text{DS}}=V_{\text{GS}}$, $I_D=250\mu\text{A}$	2	-	4	V
g_{fs}	Forward Transconductance	$V_{\text{DS}}=10\text{V}$, $I_D=1.6\text{A}$	-	2	-	S
I_{DSS}	Drain-Source Leakage Current ($T_j=25^\circ\text{C}$)	$V_{\text{DS}}=600\text{V}$, $V_{\text{GS}}=0\text{V}$	-	-	10	μA
	Drain-Source Leakage Current ($T_j=150^\circ\text{C}$)	$V_{\text{DS}}=480\text{V}$, $V_{\text{GS}}=0\text{V}$	-	-	100	μA
I_{GSS}	Gate-Source Leakage	$V_{\text{GS}}=\pm 30\text{V}$	-	-	± 100	nA
Q_g	Total Gate Charge ³	$I_D=1\text{A}$ $V_{\text{DS}}=480\text{V}$	-	12	20	nC
Q_{gs}	Gate-Source Charge		-	3	-	nC
Q_{gd}	Gate-Drain ("Miller") Charge	$V_{\text{GS}}=10\text{V}$	-	4	-	nC
$t_{\text{d(on)}}$	Turn-on Delay Time ³	$V_{\text{DD}}=300\text{V}$ $I_D=2.5\text{A}$ $R_G=10\Omega$, $V_{\text{GS}}=10\text{V}$ $R_D=120\Omega$	-	8.5	-	ns
t_r	Rise Time		-	6	-	ns
$t_{\text{d(off)}}$	Turn-off Delay Time		-	19	-	ns
t_f	Fall Time		-	8	-	ns
C_{iss}	Input Capacitance	$V_{\text{GS}}=0\text{V}$ $V_{\text{DS}}=25\text{V}$ $f=1.0\text{MHz}$	-	590	950	pF
C_{oss}	Output Capacitance		-	50	-	pF
C_{rss}	Reverse Transfer Capacitance		-	6	-	pF

Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_{SD}	Forward On Voltage ³	$I_S=3\text{A}$, $V_{\text{GS}}=0\text{V}$	-	-	1.5	V
t_{rr}	Reverse Recovery Time ²	$I_S=3\text{A}$, $V_{\text{GS}}=0\text{V}$, $dI/dt=100\text{A}/\mu\text{s}$	-	407	-	ns
			-	2110	-	nC

Notes:

- 1.Pulse width limited by safe operating area.
- 2.Starting $T_j=25^\circ\text{C}$, $V_{\text{DD}}=50\text{V}$, $L=15\text{mH}$, $R_G=25\Omega$, $I_{\text{AS}}=3\text{A}$.
- 3.Pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics



Fig 3. Normalized BV_{DSS} v.s. Junction Temperature

Fig 4. Normalized On-Resistance v.s. Junction Temperature




Fig 5. Forward Characteristic of Reverse Diode




Fig 6. Gate Threshold Voltage v.s. Junction Temperature




Fig 7. Gate Charge Characteristics




Fig 8. Typical Capacitance Characteristics




Fig 9. Maximum Safe Operating Area




Fig 10. Effective Transient Thermal Impedance




Fig 11. Switching Time Waveform




Fig 12. Gate Charge Waveform