

NB4L16M

2.5V/3.3V, 5 Gb/s Multi Level Clock/Data Input to CML Driver / Receiver / Buffer/ Translator with Internal Termination

Description

The NB4L16M is a differential driver/receiver/buffer/translator which can accept LVPECL, LVDS, CML, HSTL, LVCMOS/LVTTL and produce 400 mV CML output. The device is capable of receiving, buffering, and translating a clock or data signal that is as small as 75 mV operating up to 3.5 GHz or 5.0 Gb/s, respectively. As such, it is ideal for SONET, GigE, Fiber Channel and backplane applications (see Table 6 and Figures 20, 21 22, and 23).

Differential inputs incorporate internal 50 Ω termination resistors and accept LVPECL (Positive ECL), LVTTL/LVCMOS, CML, HSTL or LVDS. The differential 16 mA CML output provides matching internal 50 Ω termination, and 400 mV output swing when externally receiver terminated, 50 Ω to V_{CC} (see Figure 19). These features provide transmission line termination on chip, at the receiver and driver end, eliminating any use of additional external components.

The V_{BB} , an internally generated voltage supply, is available to this device only. For single-ended input configuration, the unused complementary differential input is connected to V_{BB} as a switching reference voltage. The V_{BB} reference output can be used also to re-bias capacitor coupled differential or single-ended output signals. For the capacitor coupled input signals, V_{BB} should be connected to the V_{TD} pin and bypassed to ground with a 0.01 μ F capacitor. When not used V_{BB} should be left open.

This device is housed in a 3x3 mm 16 pin QFN package. Application notes, models, and support documentation are available at www.onsemi.com.


Features

- Maximum Input Clock Frequency up to 3.5 GHz
- Maximum Input Data Rate up to 5.0 Gb/s
- < 0.7 ps Maximum Clock RMS Jitter
- < 10 ps Maximum Data Dependent Jitter at 2.5 Gb/s
- 220 ps Typical Propagation Delay
- 60 ps Typical Rise and Fall Times
- CML Output with Operating Range:
 $V_{CC} = 2.375$ V to 3.6 V with $V_{EE} = 0$ V
- CML Output Level (400 mV Peak-to-Peak Output),
Differential Output Only
- 50 Ω Internal Input and Output Termination Resistors
- Functionally Compatible with Existing 2.5 V / 3.3 V LVEL, LVEP, EP, and SG Devices
- Pb-Free Packages are Available



ON Semiconductor®

<http://onsemi.com>



(Note: Microdot may be in either location)

*For additional marking information, refer to Application Note AND8002/D.




Figure 1. Functional Block Diagram

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 11 of this data sheet.

NB4L16M




Figure 2. Pin Configuration (Top View)

Table 1. PIN DESCRIPTION

| Pin | Name | I/O | Description |
|--------------|---------------------|---|--|
| 1 | \overline{V}_{TD} | - | Internal 50 Ω termination pin. See Table 4 (Note 1). |
| 2 | \overline{D} | LVPECL, CML, HSTL, LVCMOS, LVDS, LVTTTL Input | Inverted differential input. Internal 36.5 k Ω to V_{CC} and 73 k Ω to V_{EE} (Note 1). |
| 3 | D | LVPECL, CML, HSTL, LVCMOS, LVDS, LVTTTL Input | Noninverted differential input. Internal 73 k Ω to V_{CC} and 36.5 k Ω to V_{EE} (Note 1). |
| 4 | V_{TD} | - | Internal 50 Ω termination pin. See Table 4. (Note 1) |
| 15 | V_{BB} | - | Internally generated reference voltage supply. |
| 6 | NC | | No Connect pin. The No Connect (NC) pin is electrically connected to the die and MUST be left open. |
| 10 | Q | CML Output | Noninverted differential output. Typically receiver terminated with 50 Ω resistor to V_{CC} . |
| 11 | \overline{Q} | CML Output | Inverted differential output. Typically receiver terminated with 50 Ω resistor to V_{CC} . |
| 7, 8, 13, 14 | V_{EE} | - | Negative supply voltage |
| 5, 9, 12, 16 | V_{CC} | - | Positive supply voltage |
| - | EP | - | Exposed pad (EP). EP on the package bottom is thermally connected to the die for improved heat transfer out of the package. The pad is not electrically connected to the die, but is recommended to be soldered to V_{EE} on the PC Board. |

1. In the differential configuration when the input termination pins (V_{TD} , \overline{V}_{TD}) are connected to a common termination voltage and if no signal is applied on D/ \overline{D} input then the device will be susceptible to self-oscillation.

NB4L16M

Table 2. ATTRIBUTES

| Characteristics | | Value | |
|--|------------------------|----------------------|-------------|
| Input Default State Resistors | R1 | 37.5 k Ω | |
| | R2 | 73 k Ω | |
| ESD Protection | Human Body Model | > 2 kV | |
| | Machine Model | > 200 V | |
| | Charged Device Model | > 1 kV | |
| Moisture Sensitivity (Note 2) | | Pb Pkg | Pb-Free Pkg |
| | QFN-16 | Level 1 | Level 1 |
| Flammability Rating | Oxygen Index: 28 to 34 | UL 94 V-0 @ 0.125 in | |
| Transistor Count | | 157 | |
| Meets or exceeds JEDEC Spec EIA/JESD78 IC Latchup Test | | | |

2. For additional information, see Application Note AND8003/D.

Table 3. MAXIMUM RATINGS

| Symbol | Parameter | Condition 1 | Condition 2 | Rating | Unit |
|-------------------|---|-----------------------|----------------------------------|-----------------------------------|----------------|
| V _{CC} | Positive Power Supply | V _{EE} = 0 V | | 6 | V |
| V _{EE} | Negative Power Supply | V _{CC} = 0 V | | -6 | V |
| V _I | Positive Input Negative Input | V _{EE} = 0 V | V _I = V _{CC} | 6 | V |
| | | V _{CC} = 0 V | V _I = V _{EE} | -6 | V |
| V _{INPP} | Differential Input Voltage | D - \bar{D} | | V _{CC} - V _{EE} | V |
| I _{IN} | Input Current Through R _T (50 Ω Resistor) | Static Surge | | 45 | mA |
| | | | | 80 | mA |
| I _{OUT} | Output Current | Continuous Surge | | 25 | mA |
| | | | | 50 | mA |
| I _{BB} | V _{BB} Sink/Source | | | ± 0.5 | mA |
| T _A | Operating Temperature Range | | | -40 to +85 | $^{\circ}$ C |
| T _{stg} | Storage Temperature Range | | | -65 to +150 | $^{\circ}$ C |
| θ_{JA} | Thermal Resistance (Junction-to-Ambient) (Note 3) | 0 lfpm | QFN-16 | 42 | $^{\circ}$ C/W |
| | | 500 lfpm | QFN-16 | 35 | $^{\circ}$ C/W |
| θ_{JC} | Thermal Resistance (Junction-to-Case) | 1S2P (Note 3) | QFN-16 | 4 | $^{\circ}$ C/W |
| T _{sol} | Wave Solder | | | Pb | 265 |
| | | | | Pb-Free | 265 |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

3. JEDEC standard multilayer board - 1S2P (1 signal, 2 power) with 8 filled thermal vias under exposed pad.

NB4L16M

Table 4. DC CHARACTERISTICS, CLOCK INPUTS, CML OUTPUTS $V_{CC} = 2.375\text{ V to }3.8\text{ V}$, $V_{EE} = 0\text{ V}$, $T_A = -40^\circ\text{C to }+85^\circ\text{C}$

| Symbol | Characteristic | Min | Typ | Max | Unit |
|----------|--|----------------|----------------|----------------|------|
| I_{CC} | Power Supply Current (Inputs and Outputs Open) | 30 | 45 | 55 | mA |
| V_{OH} | Output HIGH Voltage (Note 4) | $V_{CC} - 40$ | $V_{CC} - 10$ | V_{CC} | mV |
| V_{OL} | Output LOW Voltage (Note 4) | $V_{CC} - 500$ | $V_{CC} - 400$ | $V_{CC} - 300$ | mV |

DIFFERENTIAL INPUT DRIVEN SINGLE-ENDED (Figures 15 and 17)

| | | | | | |
|----------|--|-----------------|-----------------|-----------------|----|
| V_{TH} | Input Threshold Reference Voltage Range (Note 6) | 1050 | | $V_{CC} - 150$ | mV |
| V_{IH} | Single-ended Input HIGH Voltage | $V_{th} + 150$ | | V_{CC} | mV |
| V_{IL} | Single-ended Input LOW Voltage | V_{EE} | | $V_{th} - 150$ | mV |
| V_{BB} | Internally Generated Reference Voltage Supply (Loaded with $-100\ \mu\text{A}$) | $V_{CC} - 1500$ | $V_{CC} - 1400$ | $V_{CC} - 1300$ | mV |

DIFFERENTIAL INPUTS DRIVEN DIFFERENTIALLY (Figures 16 and 18)

| | | | | | | |
|------------------|---|---------------------|--------------|-------------------|---------------------------------|---------------|
| V_{IHD} | Differential Input HIGH Voltage | 1200 | | V_{CC} | mV | |
| V_{ILD} | Differential Input LOW Voltage | V_{EE} | | $V_{CC} - 150$ | mV | |
| V_{CMR} | Input Common Mode Range (Differential Configuration) | 950 | | $V_{CC} - 75$ | mV | |
| V_{ID} | Differential Input Voltage ($V_{IHD} - V_{ILD}$) | 150 | | $V_{CC} - V_{EE}$ | mV | |
| I_{IH} | Input HIGH Current ($V_{TD}/\sqrt{V_{TD}}$ Open) | $\frac{D}{\bar{D}}$ | 0 50 | 100 100 | μA | |
| I_{IL} | Input LOW Current ($V_{TD}/\sqrt{V_{TD}}$ Open) | $\frac{D}{\bar{D}}$ | -100 -150 | -50 -100 | 0 0 | μA |
| R_{TIN} | Internal Input Termination Resistor | 40 | 50 | 60 | Ω | |
| R_{TOUT} | Internal Output Termination Resistor | 40 | 50 | 60 | Ω | |
| $R_{Temp\ Coef}$ | Internal I/O Termination Resistor Temperature Coefficient | | 16 | | $\text{m}\Omega/^\circ\text{C}$ | |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfpm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

4. CML outputs require $50\ \Omega$ receiver termination resistors to V_{CC} for proper operation. See Figure 14.
5. Input and output parameters vary 1:1 with V_{CC} .
6. V_{th} is applied to the complementary input when operating in single-ended mode.
7. $V_{CMR\ min}$ varies 1:1 with V_{EE} , $V_{CMR\ max}$ varies 1:1 with V_{CC} . The V_{CMR} range is referenced to the most positive side of the differential input signal.

NB4L16M

Table 5. AC CHARACTERISTICS $V_{CC} = 2.375\text{ V to }3.8\text{ V}$, $V_{EE} = 0\text{ V}$; (Note 8)

| Symbol | Characteristic | -40°C | | | 25°C | | | 85°C | | | Unit |
|--------------------------|---|------------|--------------------------|-----------------------|------------|--------------------------|-----------------------|------------|--------------------------|-----------------------|------|
| | | Min | Typ | Max | Min | Typ | Max | Min | Typ | Max | |
| V_{OUTPP} | Output Voltage Amplitude (@ $V_{INPPmin}$) $f_{in} \leq 3.5\text{ GHz}$ (Figures 3 and 4) $f_{in} \leq 4.5\text{ GHz}$ | 280 150 | 400 300 | | 280 150 | 400 300 | | 280 150 | 400 300 | | mV |
| f_{DATA} | Maximum Operating Data Rate | 3.5 | 5.0 | | 3.5 | 5.0 | | 3.5 | 5.0 | | Gb/s |
| t_{PLH} , t_{PHL} | Propagation Delay to Output Differential @ 0.5 GHz (Figure 6) | 175 | 215 | 265 | 175 | 220 | 265 | 175 | 225 | 265 | ps |
| t_{SKEW} | Duty Cycle Skew (Note 9) Device-to-Device Skew (Note 13) | | 2.0 6.0 | 10 90 | | 2.0 6.0 | 10 90 | | 2.0 6.0 | 10 90 | ps |
| t_{JITTER} | RMS Random Clock Jitter (Note 11) $f_{in} \leq 4.5\text{ GHz}$ Peak-to-Peak Data Dependent Jitter (Note 12) $f_{DATA} = 2.5\text{ Gb/s}$ $f_{DATA} = 3.5\text{ Gb/s}$ $f_{DATA} = 5.0\text{ Gb/s}$ | | 0.2 1.5 2.0 9.0 | 0.7 10 12 25 | | 0.2 1.5 2.0 9.0 | 0.7 10 12 25 | | 0.2 1.5 2.0 9.0 | 0.7 10 12 25 | ps |
| V_{INPP} | Input Voltage Swing/Sensitivity (Differential Configuration) (Note 10) | 75 | | V_{CC} $-V_{EE}$ | 75 | | V_{CC} $-V_{EE}$ | 75 | V_{CC} $-V_{EE}$ | | mV |
| t_r t_f | Output Rise/Fall Times @ 0.5 GHz (Figure 5) (20% - 80%) | | 60 | 90 | | 60 | 90 | | 60 | 90 | ps |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lpm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

8. Measured by forcing $V_{INPP(MIN)}$ from a 50% duty cycle clock source. All loading with an external $R_L = 50\ \Omega$ to V_{CC} . Input edge rates 40 ps (20% - 80%). See Figure 12 and 14.
9. Duty cycle skew is measured between differential outputs using the deviations of the sum of T_{pw-} and T_{pw+} @ 0.5 GHz.
10. $V_{INPP(MAX)}$ cannot exceed $V_{CC} - V_{EE}$. Input voltage swing is a single-ended measurement operating in differential mode. See Figure 11.
11. Additive RMS jitter with 50% duty cycle input clock signal.
12. Additive peak-to-peak data dependent jitter with NRZ input data signal, PRBS 2²³-1 and K28.7 pattern. See Figures 7, 8, 9, 10, 11 and 12.
13. Device-to-device skew is measured between outputs under identical transition @ 0.5 GHz.

NB4L16M

TYPICAL OPERATING CHARACTERISTICS




Figure 3. Output Voltage Amplitude (V_{OUTPP}) vs. Input Clock Frequency (f_{in}) and Temperature at 3.3 V Power Supply




Figure 4. Output Voltage Amplitude (V_{OUTPP}) vs Input Clock Frequency (f_{in}) and Temperature at 2.5 V Power Supply




Figure 5. Rise/Fall Time vs Temperature and Power Supply




Figure 6. Propagation Delay vs Temperature and Power Supply




Figure 7. Typical Output Waveform at 2.488 Gb/s with PRBS $2^{23}-1$ ($V_{INPP} = 75$ mV; Input Signal DDJ = 12 ps)




Figure 8. Typical Output Waveform at 3.2 Gb/s with PRBS $2^{23}-1$ ($V_{INPP} = 75$ mV; Input Signal DDJ = 12 ps)




Figure 9. Typical Output Waveform at 2.488 Gb/s with PRBS $2^{23}-1$ ($V_{INPP} = 400$ mV; Input Signal DDJ = 12 ps)




Figure 10. Typical Output Waveform at 3.2 Gb/s with PRBS $2^{23}-1$ ($V_{INPP} = 400$ mV; Input Signal DDJ = 12 ps)




Figure 11. Typical Output Waveform at 5 Gb/s with PRBS $2^{23}-1$ ($V_{INPP} = 400$ mV; Input Signal DDJ = 13 ps)




Figure 12. Typical Output Waveform at 6.125 Gb/s with PRBS $2^{23}-1$ ($V_{INPP} = 400$ mV; Input Signal DDJ = 15 ps)

NB4L16M




Figure 13. AC Reference Measurement




Figure 14. Typical Termination for Output Driver and Device Evaluation




Figure 15. Differential Input Driven Single-Ended




Figure 16. Differential Inputs Driven Differentially




Figure 17. V_{th} Diagram




Figure 18. V_{CMR} Diagram

NOTE: $V_{EE} \leq V_{IN} \leq V_{CC}$; $V_{IH} > V_{IL}$

NB4L16M




Figure 19. CML Output Structure

Table 6. INTERFACING OPTIONS

| INTERFACING OPTIONS | CONNECTIONS |
|---------------------|---|
| CML | Connect V_{TD} and \bar{V}_{TD} to V_{CC} |
| LVDS | Connect V_{TD} and \bar{V}_{TD} Together |
| AC-COUPLED | Bias V_{TD} and \bar{V}_{TD} Inputs within Common Mode Range (V_{CMR}) |
| RSECL, PECL, NECL | Standard ECL Termination Techniques |
| LVTTL, LVCMOS | An External Voltage (V_{THR}) should be applied to the unused complementary differential input. Nominal V_{THR} is 1.5 V for LVTTL and $V_{CC}/2$ for LVCMOS inputs. This voltage must be within the V_{THR} specification. |

NB4L16M

Application Information

All NB4L16M inputs can accept LVPECL, CML, LVTTTL, LVCMOS and LVDS signal levels. The limitations for differential input signal (LVDS, PECL, or CML) are minimum input swing of 75 mV and the maximum input swing of 2500 mV. Within these conditions, the input voltage can range from V_{CC} to 1.2 V. Examples interfaces are illustrated below in a 50 Ω environment ($Z = 50 \Omega$).




Figure 20. CML to CML Interface




Figure 21. PECL to CML Receiver Interface

NB4L16M




Figure 22. LVDS to CML Receiver Interface




Figure 23. LVCMOS/LVTTL to CML Receiver Interface

ORDERING INFORMATION


| Device | Package | Shipping [†] |
|--------------|---------------------|-----------------------|
| NB4L16MMN | QFN-16 | 123 Units / Rail |
| NB4L16MMNG | QFN-16 (Pb-Free) | 123 Units / Rail |
| NB4L16MMNR2 | QFN-16 | 3000 / Tape & Reel |
| NB4L16MMNR2G | QFN-16 (Pb-Free) | 3000 / Tape & Reel |

[†]For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

NB4L16M

PACKAGE DIMENSIONS

16 PIN QFN
CASE 485G-01
ISSUE C




NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.25 AND 0.30 MM FROM TERMINAL.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.
5. L_{max} CONDITION CAN NOT VIOLATE 0.2 MM MINIMUM SPACING BETWEEN LEAD TIP AND FLAG

| DIM | MILLIMETERS | |
|-----|-------------|------|
| | MIN | MAX |
| A | 0.80 | 1.00 |
| A1 | 0.00 | 0.05 |
| A3 | 0.20 | REF |
| b | 0.18 | 0.30 |
| D | 3.00 | BSC |
| D2 | 1.65 | 1.85 |
| E | 3.00 | BSC |
| E2 | 1.65 | 1.85 |
| e | 0.50 | BSC |
| K | 0.18 | TYP |
| L | 0.30 | 0.50 |

SOLDERING FOOTPRINT*



*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P. O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/
Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5773-3850

ON Semiconductor Website: www.onsemi.com
Order Literature: <http://www.onsemi.com/orderlit>
For additional information, please contact your local
Sales Representative

NB4L16M/D