

FEATURES**4-input, 1-output multiplexed HDMI transceiver****HDMI 1.4 support****Audio return channel (ARC)****3D TV support****Content type bits****CEC 1.4-compatible (CEC_CPD and CEC_HPD)****High-Bandwidth Digital Content Protection (HDCP 1.4)****HDCP repeater support****225 MHz HDMI Rx and Tx support 36-/30-/24-bit Deep Color****Supports DVI RGB graphics up to 1600 × 1200 at 60 Hz****Ultralow jitter digital PLL (100% deskew)****Quad HDMI Rx input****Format details available on all unselected ports****Adaptive equalizer for cable lengths up to 30 meters****Internal extended display identification data (EDID) RAM****EDID replication (512 bytes per port)****EDID with HDMI cable 5 V power support****5 V detect inputs****Hot plug assertion control pins****Single HDMI Tx output****EDID data extraction****Hot plug detect (HPD) input****Audio support****HDMI 1.4-compatible audio interface****Dedicated flexible audio input/output port****S/PDIF (IEC 60958-compatible) digital audio input/output****Super audio CD (SACD) with DSD input/output interface****High bit rate (HBR) audio****Dolby® TrueHD****DTS-HD Master Audio™****Full audio input and output support****General****Interrupt controller with 3 interrupt outputs****STDI (standard identification circuit)****Software libraries, driver, and application available****2-layer PCB design supported****APPLICATIONS****AVRs****HTiB****Sound bar with HDMI repeater support****HBR enabled TVs****Other repeater applications****GENERAL DESCRIPTION**

The ADV7622 is a high performance, four-input, one-output, High-Definition Multimedia Interface (HDMI™) transceiver that integrates HDMI 1.4 receiver and transmitter functions with digital audio I/Os onto one chip. It supports all HDCP repeater functions through fully tested Analog Devices, Inc., repeater software libraries and drivers.

The ADV7622 supports all mandatory HDMI 1.4 3D TV formats in addition to all HDTV formats up to 1080p 36-bit Deep Color. The ADV7622 also features an integrated HDMI 1.4 CEC controller that supports capability, discovery, and control (CDC).

The ADV7622 offers a dedicated flexible audio output port and a dedicated audio input port to allow for easy extraction and insertion of audio data into and out of the HDMI stream. HDMI audio formats, including SACD via DSD and compressed high bit rate audio via HBR, are supported. The ADV7622 also features an audio return channel (ARC) receiver. ARC simplifies cabling by combining upstream audio capability in a conventional HDMI cable.

Fabricated in an advanced CMOS process, the ADV7622 is provided in a 144-lead, 20 mm × 20 mm, Pb-free LQFP and is specified over the 0°C to +70°C temperature range.

For more information on the ADV7622, contact a local Analog Devices sales office or email ATV_VIDEORX_INFO@analog.com.

Advantiv
Advanced Television Solutions
by Analog Devices

Rev. Sp0

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.
Tel: 781.329.4700 www.analog.com
Fax: 781.461.3113 ©2010 Analog Devices, Inc. All rights reserved.

ADV7622

NOTES