

### 1. PART NO. EXPRESSION :

$\frac{S}{(a)} \frac{D}{(b)} \frac{C}{(c)} \frac{1}{(d)} \frac{2}{(e)} \frac{0}{(e)} \frac{7}{(e)} - \frac{1}{(c)} \frac{R}{(c)} \frac{2}{(c)} \frac{Y}{(d)} \frac{F}{(d)}$

(a) Series code


(d) Tolerance code : M =  $\pm 20\%$ , Y =  $\pm 30\%$

(b) Dimension code

(e) F : RoHS Compliant

(c) Inductance code : 1R2 = 1.2 $\mu$ H

### 2. CONFIGURATION & DIMENSIONS :



Unit:m/m

A	B	C	D	E	F	G	H	L
12.8 Max.	12.8 max.	8.5 Max.	5.0 Ref.	2.2 Ref.	7.6 Ref.	7.0 Ref.	5.4 Ref.	12.6 Ref.

### 3. SCHEMATIC :



### 4. GENERAL SPECIFICATION :

- a) Temp. rise : 40°C Typ.
- b) Rated current : Base on temp. rise &  $\Delta L/L0A \leq 35\%$
- c) Operating temp. : -40°C to +85°C
- d) Storage temp. : -40°C to +85°C



**RoHS Compliant**

NOTE : Specifications subject to change without notice. Please check our website for latest information.

23.02.2010



**SUPERWORLD ELECTRONICS (S) PTE LTD**

PG. 1

## 5. ELECTRICAL CHARACTERISTICS :

Part No.	Inductance ( $\mu$ H)	Test Frequency (Hz)	DCR ( $\Omega$ ) Max.	IDC (A) Max.
SDC1207-1R2YF	1.2 $\pm$ 30%	1V / 100K	0.0070	9.80
SDC1207-2R4YF	2.4 $\pm$ 30%	1V / 100K	0.0115	8.00
SDC1207-3R5YF	3.5 $\pm$ 30%	1V / 100K	0.0135	7.50
SDC1207-4R7YF	4.7 $\pm$ 30%	1V / 100K	0.0158	6.80
SDC1207-6R1YF	6.1 $\pm$ 30%	1V / 100K	0.0176	6.60
SDC1207-7R6YF	7.6 $\pm$ 30%	1V / 100K	0.0200	5.90
SDC1207-100MF	10 $\pm$ 20%	1V / 1K	0.0216	5.40
SDC1207-120MF	12 $\pm$ 20%	1V / 1K	0.0243	4.90
SDC1207-150MF	15 $\pm$ 20%	1V / 1K	0.0270	4.50
SDC1207-180MF	18 $\pm$ 20%	1V / 1K	0.0392	3.90
SDC1207-220MF	22 $\pm$ 20%	1V / 1K	0.0432	3.60
SDC1207-270MF	27 $\pm$ 20%	1V / 1K	0.0459	3.40
SDC1207-330MF	33 $\pm$ 20%	1V / 1K	0.0648	3.00
SDC1207-390MF	39 $\pm$ 20%	1V / 1K	0.0729	2.75
SDC1207-470MF	47 $\pm$ 20%	1V / 1K	0.100	2.50
SDC1207-560MF	56 $\pm$ 20%	1V / 1K	0.110	2.35
SDC1207-680MF	68 $\pm$ 20%	1V / 1K	0.140	2.10
SDC1207-820MF	82 $\pm$ 20%	1V / 1K	0.160	1.95
SDC1207-101MF	100 $\pm$ 20%	1V / 1K	0.220	1.70
SDC1207-121MF	120 $\pm$ 20%	1V / 1K	0.250	1.60
SDC1207-151MF	150 $\pm$ 20%	1V / 1K	0.280	1.42
SDC1207-181MF	180 $\pm$ 20%	1V / 1K	0.350	1.30
SDC1207-221MF	220 $\pm$ 20%	1V / 1K	0.390	1.16
SDC1207-271MF	270 $\pm$ 20%	1V / 1K	0.560	1.06
SDC1207-331MF	330 $\pm$ 20%	1V / 1K	0.640	0.95
SDC1207-391MF	390 $\pm$ 20%	1V / 1K	0.700	0.88
SDC1207-471MF	470 $\pm$ 20%	1V / 1K	0.980	0.79
SDC1207-561MF	560 $\pm$ 20%	1V / 1K	1.070	0.73
SDC1207-681MF	680 $\pm$ 20%	1V / 1K	1.460	0.67
SDC1207-821MF	820 $\pm$ 20%	1V / 1K	1.640	0.60
SDC1207-102MF	1000 $\pm$ 20%	1V / 1K	1.820	0.55



RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.



23.02.2010




SUPERWORLD ELECTRONICS (S) PTE LTD

PG. 2

## 6. RELIABILITY AND TEST CONDITIONS :

ITEM	PERFORMANCE	TEST CONDITION															
Mechanical Performance Test																	
Solderability Test	More than 90% of the terminal electrode should be covered with solder.  	Preheat : 150°C, 60sec. Solder : Sn-Ag3.0-Cu0.5 Solder Temperature : 245±5°C Flux for lead free : rosin Dip Time : 4±1sec.															
Solder Heat Resistance	1. Appearance : No significant abnormality 2. Inductance change : Within ±20%  	Preheat : 150°C, 60sec. Solder : Sn-Ag3.0-Cu0.5 Solder Temperature : 260±5°C Flux for lead free : rosin Dip Time : 10±0.5sec.															
Reliability Test																	
High Temperature Life Test		Temperature : 85±2°C Time : 500 hours Applied current : rated current															
Thermal Shock	1. Appearance : No damage 2. Inductance : Within ±20% of initial value.	Conditions of 1 cycle. <table border="1" data-bbox="938 955 1279 1081"> <thead> <tr> <th>Step</th> <th>Temperature (°C)</th> <th>Times (min.)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>-25±2</td> <td>30±3</td> </tr> <tr> <td>2</td> <td>Room Temperature</td> <td>15</td> </tr> <tr> <td>3</td> <td>+85±2</td> <td>30±3</td> </tr> <tr> <td>4</td> <td>Room Temperature</td> <td>15</td> </tr> </tbody> </table> Total : 50 cycles	Step	Temperature (°C)	Times (min.)	1	-25±2	30±3	2	Room Temperature	15	3	+85±2	30±3	4	Room Temperature	15
Step	Temperature (°C)	Times (min.)															
1	-25±2	30±3															
2	Room Temperature	15															
3	+85±2	30±3															
4	Room Temperature	15															
Humidity Resistance	1. Appearance : No damage 2. Inductance : Within ±20% of initial value.	Temperature : 40±2°C Humidity : 90% to 95% Applied Current : Rated Current Time : 500 hours															
Random Vibration Test	Appearance : Cracking, chipping & any other defects harmful to the characteristics should not be allowed.	Frequency : 10-55-10Hz for 1 min. Amplitude : 1.52mm Directions & times : X, Y, Z directions for 2 hours. A period of 2 hours in each of 3 mutually perpendicular directions (Total 6 hours).															





**RoHS Compliant**

NOTE : Specifications subject to change without notice. Please check our website for latest information.


23.02.2010

## 7. PACKAGING INFORMATION :

### 7-1. Tape and Reel Dimension



Type	A(mm)	C(mm)	G(mm)	N(mm)
13" x 24mm	330	24.5±0.5	13.5±0.5	100±1



W(mm)	P(mm)	P2(mm)	D(mm)	Po(mm)	Quantity ( pcs )
24.0±0.3	16±0.1	2±0.1	1.5+0.25	4±0.1	450

## Application Notice

### 1. Storage Conditions :

To maintain the solderability of terminal electrodes :

- a) Temperature and humidity conditions : Less than 40°C and 70% RH.
- b) Recommended products should be used within 6 months from the time of delivery.
- c) The packaging material should be kept where no chlorine or sulfur exists in the air.

### 2. Transportation :

- a) Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
- b) The use of tweezers or vacuum pick up is strongly recommended for individual components.
- c) Bulk handling should ensure that abrasion and mechanical shock are minimized.



**RoHS Compliant**

NOTE : Specifications subject to change without notice. Please check our website for latest information.

23.02.2010



**SUPERWORLD ELECTRONICS (S) PTE LTD**

PG. 4