TOSHIBA CMOS Digital Integrated Circuit Silicon Monolithic

TC7WBD125FK

Dual Bus Switch with Level Shift

The TC7WBD125FK is a low on-resistance, high-speed CMOS 2-bit bus switch. This bus switch allows the connections or disconnections to be made with minimal propagation delay while maintaining Low power dissipation which is the feature of CMOS.

When output enable (\overline{OE}) is at low level, the switch is on; when at high level, the switch is off.

The internal diode which adds to power supply line is enable to realize the shift of signal level from 5 V to 3.3 V. (Note 1)

All inputs are equipped with protector circuits to protect the device from static discharge.





- Operating voltage: VCC = 4.5~5.5 V
- High speed operation: t_{pd} = 0.25 ns (max)
- Ultra-low on resistance: $RON = 5 \Omega$ (typ.)
- Electro-static discharge (ESD) performance: ±200 V or more (JEITA)

±2000 V or more (MIL)

- TTL level input (control input)
- Package: US8
 - Note 1: In case that over-shoot noise is detected, this device should be used with clamp diode to prevent the next stage device from over-stress.

Pin Assignment (top view)






Weight: 0.01 g (typ.)


TOSHIBA

Truth Table

Inputs	Function
ŌĒ	T unction
L	A port = B port
н	Disconnect

System Diagram





Maximum Ratings

Characteristics	Symbol	Rating	Unit	
Power supply voltage	V _{CC}	-0.5~7.0	V	
Control pin input voltage	V _{IN}	-0.5~7.0	V	
Switch terminal I/O voltage	VS	-0.5~7.0	V	
Clump diode current	I _{IK}	-50	mA	
Switch I/O current	I _S	128	mA	
Power dissipation	PD	200	mW	
DC V _{CC} /GND current	I _{CC} /I _{GND}	±100	mA	
Storage temperature	T _{stg}	-65~150	°C	

B1

Recommended Operating Conditions

Characteristics	Symbol	Rating	Unit
Power supply voltage	V _{CC}	4.5~5.5	V
Control pin input voltage	V _{IN}	0~5.5	V
Switch I/O voltage	VS	0~5.5	V
Operating temperature	T _{opr}	-40~85	°C
Control pin input rise/fall time	dt/dv	0~10	ns/V

Electrical Characteristics

DC Characteristics (Ta = -40~85°C)

Character	istics	Symbol	Test Condition		V _{CC} (V)	Min	Typ. (Note 2)	Max	Unit
Control pin input	"H" level	VIH	_		4.5~5.5	2.0	_	_	V
voltage	"L" level	VIL	_		4.5~5.5	_	_	0.8	v
High-level output	voltage	V _{OH}	Figure 4		_		_	_	_
Input leakage cur	rent	I _{IN}	V _{IN} = 0~5.5 V		4.5~5.5		_	±1.0	μΑ
Power off leakage	e current	IOFF	A, B, \overline{OE} = 0~5.5 V		0		_	±1.0	μΑ
Off-state leakage (switch		I _{SZ}	A, B = 0~5.5 V, $\overline{OE} = V_{CC}$		4.5~5.5	_	_	±1.0	μΑ
			VIS = 0 V	I _{IS} = 64 mA	4.5	_	5	7	
ON resistance	(Note 3)	R _{ON}	$v_{1S} = 0 v$	I _{IS} = 30 mA	4.5	_	5	7	Ω
			$V_{IS} = 2.4 \text{ V}, I_{IS} = 15 \text{ mA}$		4.5	_	35	50	
		laa	$V_{IN} = V_{CC}$ or GND	switch ON	5.5	_	—	1.5	mA
Quiescent supply	current	Icc	$I_{OUT} = 0$	switch OFF	5.5	_	_	10	μΑ
		Δl _{CC}	V _{IN} = 3.4 V (one input)		5.5	_	_	2.5	mA

Note 2: The typical values are at $V_{CC} = 5 V$, Ta = 25°C.

AC Characteristics (Ta = -40~85°C)

Characteristics	Symbol	Test Condition	V _{CC} (V)	Min	Max	Unit
Propagation delay time (bus to bus)	t _{pLH} t _{pHL}	Figure 1, Figure 2 (Note 4)	4.5	_	0.25	ns
Output enable time	t _{pZL} t _{pZH}	Figure 1, Figure 3	4.5	_	4.5	ns
Output disable time	t _{pLZ} t _{pHZ}	Figure 1, Figure 3	4.5		5.0	ns

Note 4: The propagation delay time is calculated by the RC (on-resistance and load capacitance) time constant.

Capacitive Characteristics (Ta = 25°C)


Characteristics	Symbol	Test Condition	V _{CC} (V)	Тур.	Unit
Control pin input capacitance	C _{IN}	(Note 5) 5.0	3	pF
Switch terminal capacitance	C _{I/O}	$\overline{OE} = V_{CC}$ (Note 5) 5.0	10	pF

Note 5: This parameter is guaranteed by design.

Note 3: Apply the specified current to the switch, then measure the voltages on pins A and B. The on-resistance is the lower of the two.

<u>TOSHIBA</u>

AC Test Circuit



Parameter	Switch
t _{pLH} , t _{pHL}	Open
t _{pLZ} , t _{pZL}	7.0 V
t _{pHZ} , t _{pZH}	Open



AC Waveform




Figure 2 t_{pLH}, t_{pHL}






Figure 3 $t_{pLZ}, t_{pHZ}, t_{pZL}, t_{pZH}$

V_{OH} – V_{CC} Characteristics (typ.)










Figure 4

Package Dimensions

SSOP8-P-0.50A

Unit : mm





Weight: 0.01 g (typ.)

6

RESTRICTIONS ON PRODUCT USE

- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor
 devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical
 stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of
 safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of
 such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
 - In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The products described in this document are subject to the foreign exchange and foreign trade laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.