

# DATA SHEET

## **NE522**

High-speed dual-differential  
comparator/sense amp

Product data  
Supersedes data of 1994 Aug 31  
File under Integrated Circuits, IC11 Handbook

2001 Aug 03

# High-speed dual-differential comparator/sense amp

# NE522

## FEATURES

- 15 ns maximum guaranteed propagation delay
- 20  $\mu$ A maximum input bias current
- TTL-compatible strobes and outputs
- Large common-mode input voltage range
- Operates from standard supply voltages

## APPLICATIONS

- MOS memory sense amp
- A-to-D conversion
- High-speed line receiver

## PIN CONFIGURATION




Figure 1. Pin Configuration

## BLOCK DIAGRAM




Figure 2. Block Diagram

## ORDERING INFORMATION

DESCRIPTION	TEMPERATURE RANGE	ORDER CODE	DWG #
14-Pin Plastic DIP	0 °C to +70 °C	NE522N	SOT27-1
14-Pin Plastic SO	0 °C to +70 °C	NE522D	SOT108-1

## ABSOLUTE MAXIMUM RATINGS

SYMBOL	PARAMETER	RATING	UNITS
V+	Single supply voltage	+7	V
V-	Negative	-7	V
V <sub>IDR</sub>	Differential input voltage	±6	V
V <sub>IN</sub>	Input voltage	±5	V
	Common-mode	+5.25	V
	Strobe/gate		
P <sub>D</sub>	Power dissipation	600	mW
T <sub>amb</sub>	Operating temperature range	0 to 70	°C
T <sub>stg</sub>	Storage temperature range	-65 to +150	°C
T <sub>sld</sub>	Lead soldering temperature (10 sec max)	+230	°C

# High-speed dual-differential comparator/sense amp

## NE522

### EQUIVALENT SCHEMATIC




Figure 3. Equivalent Schematic

## High-speed dual-differential comparator/sense amp

NE522

**DC ELECTRICAL CHARACTERISTICS** $V_{\pm} = \pm 5 \text{ V} \pm 5\%$ ;  $T_{\text{amb}} = 0 \text{ }^{\circ}\text{C}$  to  $+70 \text{ }^{\circ}\text{C}$ , unless otherwise stated.

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNITS
			MIN	TYP	MAX	
$V_{\text{OS}}$	Input offset voltage At 25 °C Over temperature range	$V_{+} = +4.75 \text{ V}$ ; $V_{-} = -4.75 \text{ V}$		6	7.5 10	mV mV
$I_{\text{BIAS}}$	Input bias current At 25 °C Over temperature range	$V_{+} = +5.25 \text{ V}$ ; $V_{-} = -5.25 \text{ V}$		7.5	20 40	$\mu\text{A}$ $\mu\text{A}$
$I_{\text{OS}}$	Input offset current At 25 °C Over temperature range	$V_{+} = +5.25 \text{ V}$ ; $V_{-} = -5.25 \text{ V}$		1.0	5 12	$\mu\text{A}$ $\mu\text{A}$
$V_{\text{CM}}$	Common-mode voltage range	$V_{+} = +4.75 \text{ V}$ ; $V_{-} = -4.75 \text{ V}$	-3		+3	V
$V_{\text{IL}}$	LOW-level input voltage At 25 °C Over temperature range				0.8 0.7	V V
$V_{\text{IH}}$	High level temperature		2.0			V
$I_{\text{IH}}$	HIGH-level input current 1G or 2G strobe Common strobe S	$V_{+} = +5.25 \text{ V}$ ; $V_{-} = -5.25 \text{ V}$ ; $V_{\text{IH}} = 2.7 \text{ V}$			50 100	$\mu\text{A}$ $\mu\text{A}$
$I_{\text{IL}}$	LOW-level input current 1G or 2G strobe Common strobe S	$V_{\text{IL}} = 0.5 \text{ V}$			-2.0 -4.0	mA mA
$V_{\text{OL}}$	LOW-level output voltage	$V_{+} = +5.25 \text{ V}$ ; $V_{-} = -5.25 \text{ V}$ ; $V_{\text{I(S)}} = 2.0 \text{ V}$ ; $I_{\text{LOAD}} = 20 \text{ mA}$			0.5	V
$I_{\text{OH}}$	HIGH-level output current	$V_{+} = +4.75 \text{ V}$ ; $V_{-} = -4.75 \text{ V}$ ; $V_{\text{OH}} = 5.25 \text{ V}$			250	$\mu\text{A}$
$V_{+}$ $V_{-}$	Supply voltage Positive Negative		4.75 -4.75	5.0 -5.0	5.25 -5.25	V V
$I_{\text{CC+}}$ $I_{\text{CC-}}$	Supply current Positive Negative	$V_{+} = +5.25 \text{ V}$ ; $V_{-} = -5.25 \text{ V}$ ; $T_{\text{amb}} = 25 \text{ }^{\circ}\text{C}$		27 -15	35 -28	mA

## High-speed dual-differential comparator/sense amp

NE522

**AC ELECTRICAL CHARACTERISTICS** $T_{amb} = 25\text{ }^{\circ}\text{C}$ ;  $R_L = 280\text{ }\Omega$ ;  $C_L = 15\text{ pF}$ ; unless otherwise stated.

SYMBOL	PARAMETER	FROM INPUT	TO OUTPUT	LIMITS			UNITS
				MIN	TYP	MAX	
$I_R$	Input resistance				4		$k\Omega$
$I_C$	Input capacitance				3		pF
<b>Large-signal switching speed</b>							
	Propagation delay						
$t_{PLH(D)}$	Low to high <sup>1</sup>	Amp	Output		10	15	ns
$t_{PHL(D)}$	High to low <sup>1</sup>	Amp	Output		8	12	
$t_{PLH(S)}$	Low to high <sup>2</sup>	Strobe	Output		6	13	
$t_{PHL(S)}$	High to low <sup>2</sup>	Strobe	Output		5	9	
$I_{MAX}$	Maximum operating frequency			25	35		MHz

**NOTES:**

- Response time measured from 0 V point of +100 mV<sub>p-p</sub> 10 MHz square wave to the 1.5 V point of the output.
- Response time measured from 1.5 V point of the input to 1.5 V point of the output.


**LOGIC FUNCTION TABLE**

$V_{ID} (A^+, B^-)$	STRS	STRG	OUTPUT TRANSISTOR
$< -V_{OS}$	H	H	ON
$-V_{OS} < V_{ID} < V_{OS}$	H	H	Undefined
$> V_{OS}$	H	H	OFF
X	L	X	OFF
X	X	L	OFF

# High-speed dual-differential comparator/sense amp

NE522

## TYPICAL PERFORMANCE CHARACTERISTICS



SL00249


Figure 4. Typical Performance Characteristics

# High-speed dual-differential comparator/sense amp

NE522

DIP14: plastic dual in-line package; 14 leads (300 mil)

SOT27-1



**DIMENSIONS (inch dimensions are derived from the original mm dimensions)**

UNIT	A max.	A <sub>1</sub> min.	A <sub>2</sub> max.	b	b <sub>1</sub>	c	D <sup>(1)</sup>	E <sup>(1)</sup>	e	e <sub>1</sub>	L	M <sub>E</sub>	M <sub>H</sub>	w	Z <sup>(1)</sup> max.
mm	4.2	0.51	3.2	1.73 1.13	0.53 0.38	0.36 0.23	19.50 18.55	6.48 6.20	2.54	7.62	3.60 3.05	8.25 7.80	10.0 8.3	0.254	2.2
inches	0.17	0.020	0.13	0.068 0.044	0.021 0.015	0.014 0.009	0.77 0.73	0.26 0.24	0.10	0.30	0.14 0.12	0.32 0.31	0.39 0.33	0.01	0.087

**Note**

1. Plastic or metal protrusions of 0.25 mm maximum per side are not included.


OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	EIAJ			
SOT27-1	050G04	MO-001	SC-501-14			95-03-11 99-12-27

# High-speed dual-differential comparator/sense amp

NE522

SO14: plastic small outline package; 14 leads; body width 3.9 mm

SOT108-1



**DIMENSIONS (inch dimensions are derived from the original mm dimensions)**

UNIT	A max.	A <sub>1</sub>	A <sub>2</sub>	A <sub>3</sub>	b <sub>p</sub>	c	D <sup>(1)</sup>	E <sup>(1)</sup>	e	H <sub>E</sub>	L	L <sub>p</sub>	Q	v	w	y	Z <sup>(1)</sup>	θ
mm	1.75	0.25 0.10	1.45 1.25	0.25	0.49 0.36	0.25 0.19	8.75 8.55	4.0 3.8	1.27	6.2 5.8	1.05	1.0 0.4	0.7 0.6	0.25	0.25	0.1	0.7 0.3	8° 0°
inches	0.069	0.010 0.004	0.057 0.049	0.01	0.019 0.014	0.0100 0.0075	0.35 0.34	0.16 0.15	0.050	0.244 0.228	0.041	0.039 0.016	0.028 0.024	0.01	0.01	0.004	0.028 0.012	

**Note**

1. Plastic or metal protrusions of 0.15 mm maximum per side are not included.

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	EIAJ			
SOT108-1	076E06	MS-012				97-05-22 99-12-27



---

High-speed dual-differential comparator/sense amp

NE522

---

**NOTES**

## High-speed dual-differential comparator/sense amp

NE522

## Data sheet status

Data sheet status <sup>[1]</sup>	Product status <sup>[2]</sup>	Definitions
Objective data	Development	This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice.
Preliminary data	Qualification	This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product.
Product data	Production	This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Changes will be communicated according to the Customer Product/Process Change Notification (CPCN) procedure SNW-SQ-650A.

[1] Please consult the most recently issued data sheet before initiating or completing a design.

[2] The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL <http://www.semiconductors.philips.com>.

## Definitions

**Short-form specification** — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

**Limiting values definition** — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

**Application information** — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

## Disclaimers

**Life support** — These products are not designed for use in life support appliances, devices or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

**Right to make changes** — Philips Semiconductors reserves the right to make changes, without notice, in the products, including circuits, standard cells, and/or software, described or contained herein in order to improve design and/or performance. Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no license or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

## Contact information

For additional information please visit  
<http://www.semiconductors.philips.com>. Fax: +31 40 27 24825

© Koninklijke Philips Electronics N.V. 2001  
 All rights reserved. Printed in U.S.A.

Date of release: 12-01

For sales offices addresses send e-mail to:  
[sales.addresses@www.semiconductors.philips.com](mailto:sales.addresses@www.semiconductors.philips.com)

Document order number:

9397 750 09202

*Let's make things better.*