

RF AMPLIFIER

MODEL *TM9502*

Available as: TM9502, 4 Pin TO-8 (T4)
 TN9502, 4 Pin Surface Mount (SM3)
 FP9502, 4 Pin Flatpack (FP4)
 BX9502, Connectrized Housing (H1)
 PN9502, Reduced Size Surface Mount (SM11)

Features

- Medium Gain: 10.5 dB Typical
- Frequency Range: 5 to 1500 MHz
- Operating Temp. -55 °C to + 85 °C
- Environmental Screening Available

Typical Intermodulation Performance at 25 °C

Second Order Harmonic Intercept Point.....+37 dBm (Typ.)
 Second Order Two Tone Intercept Point.....+32 dBm (Typ.)
 Third Order Two Tone Intercept Point.....+24 dBm (Typ.)

Specifications


CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = -55 °C to +85 °C
Frequency	5 - 1500 MHz	5 - 1500 MHz
Gain (dB)	10.5	8.5 Min.
Power @ 1 dB Comp. (dBm)	+9	+7 Min.
Reverse Isolation (dB)	-13.5	-12.5 Max.
VSWR In	<1.5:1	2.0:1 Max.
VSWR Out	<1.5:1	2.0:1 Max.
Noise Figure (dB)	4.0	5.5 Max.
Power Vdc	+15	+15
mA	23	25 Max.

Maximum Ratings

Ambient Operating Temperature-55°C to +100 °C
 Storage Temperature-62°C to +125 °C
 Case Temperature +125 °C
 DC Voltage +18 Volts
 Continuous RF Input Power +13 dBm
 Short Term RF Input Power..... 50 Milliwatts (1 Minute Max.)
 Maximum Peak Power..... 0.5 Watt (3 µsec Max.)

Note: Care should always be taken to effectively ground the case of each unit.

Typical Performance Data



Legend ——— +25 °C - - - +85 °C ····· -55 °C

Linear S-Parameters

FREQ. MHz	S11		S12		S21	
	Mag	Deg	Mag	Deg	Mag	Deg
5	.17	-142	3.39	-170	.16	12
50	.14	-178	3.40	176	.17	1
100	.14	178	3.41	170	.17	- 1
250	.15	167	3.40	153	.17	- 3
500	.16	155	3.41	126	.17	- 7
750	.17	141	3.43	100	.18	-12
1000	.18	134	4.43	73	.18	-15
1250	.24	123	4.59	42	.20	-23
1500	.30	111	3.44	12	.21	-28



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532 08/24/90

www.SpectrumMicrowave.com Spectrum Microwave · 2707 Black Lake Place · Philadelphia, Pennsylvania 19154 · PH (215) 464-4000 · Fax (215) 464-4001