

Fixed Attenuator Sets

MDI fixed attenuator sets contain standard values of attenuation and are available in various frequency ranges and connector types. Our standard kits are available in two different combinations of attenuation values, however, you may specify custom values to meet your needs.

MODEL	SPECIFICATIONS		
	Connector	Attenuation (dB)	Frequency Range (GHz)
A4400	N	3, 6, 10, 20	DC - 18.0 GHz
A4401	N	3, 6, 10, 20	DC - 12.4 GHz
A4402	N	3, 6, 10, 20	DC - 6.0 GHz
A4403	SMA	3, 6, 10, 20	DC - 18.0 GHz
A4404	SMA	3, 6, 10, 20	DC - 12.4 GHz
A4405	SMA	3, 6, 10, 20	DC - 6.0 GHz
A4406	N	1, 3, 6, 10, 20, 30	DC - 18.0 GHz
A4407	N	1, 3, 6, 10, 20, 30	DC - 12.4 GHz
A4408	N	1, 3, 6, 10, 20, 30	DC - 6.0 GHz
A4409	SMA	1, 3, 6, 10, 20, 30	DC - 18.0 GHz
A4410	SMA	1, 3, 6, 10, 20, 30	DC - 12.4 GHz
A4411	SMA	1, 3, 6, 10, 20, 30	DC - 6.0 GHz
A4412	7mm	3, 6, 10, 20, 30	DC - 18.0 GHz
A4413	7mm	1, 3, 6, 10, 20, 30	DC - 18.0 GHz
A4414	2.92mm	3, 6, 10, 20, 30	DC - 26.5 GHz
A4415	2.92mm	1, 3, 6, 10, 20, 30	DC - 26.5 GHz