

# LED780-66-60 epoxy lens type Infrared illuminator

LED780-66-60 is a wide viewing and extremely high output power illuminator assembled with a total of 60 high efficiency AlGaAs diode chips, mounted on a metal stem TO-66 with AlN ceramics and covered with double coated clear silicone and epoxy resin.

These devices are designed for high current operation with proper heat sinking to improve thermal conductive efficiency.

## Features

- 1) high reliability
- 2) compact TO-66 package
- 3) high output power at 780 nm


## Applications

- 1) For IR search light
- 2) For CCD lighting

## Specifications

- |                     |                               |
|---------------------|-------------------------------|
| 1) Product name     | IR illuminator                |
| 2) Spec. No.        | LED780-66-60                  |
| 3) Fast Chip        | tr, tf = typ. 100 ns @ 600 mA |
| (1) Material        | AlGaAs                        |
| (2) Peak wavelength | 780 nm                        |
| 4) Package          |                               |
| (1) Stem            | TO-66 stem with AlN           |
| (2) Lens            | Clear silicone and epoxy lens |

Outer dimension (Unit: mm)



## Absolute Maximum Ratings

Item	Symbol	Maximum Rated Value	Unit	Ambient Temperature
Power Dissipation	P <sub>D</sub>	7.8	W	T <sub>a</sub> = 25°C
Forward Current	I <sub>F</sub>	0.75	A	T <sub>a</sub> = 25°C
Pulse Forward Current	I <sub>FP</sub>	3.0	A	T <sub>a</sub> = 25°C
Reverse Voltage	V <sub>R</sub>	50	V	T <sub>a</sub> = 25°C
Operating Temperature	T <sub>OPR</sub>	-30 ~ +80	°C	
Storage Temperature	T <sub>STG</sub>	-30 ~ +110	°C	
Soldering Temperature	T <sub>SOL</sub>	240	°C	

‡ Pulse Forward Current condition: Duty = 1% and Pulse Width = 1 μs.

‡ Soldering condition : Soldering condition must be completed within 3 seconds at 260°C

## Electro-Optical Characteristics

Item	Symbol	Condition	Minimum	Typical	Maximum	Unit
Forward Voltage	V <sub>F</sub>	I <sub>F</sub> = 600 mA		9.0		V
Reverse Voltage	V <sub>R</sub>	I <sub>R</sub> = 10 μA	50			V
Total Radiated Power	P <sub>O</sub>	I <sub>F</sub> = 600 mA		1000		mW
Total Radiated Power	P <sub>O</sub>	I <sub>F</sub> = 3 A		4000		mW
Radiant Intensity	I <sub>E</sub>	I <sub>F</sub> = 600 mA		450		mW/sr
Brightness	I <sub>V</sub>	I <sub>F</sub> = 600 mA		-----		mcd
Peak Wavelength	I <sub>P</sub>	I <sub>F</sub> = 600 mA	770	780	790	nm
Half Width	DI	I <sub>F</sub> = 600 mA		40		nm
Viewing Half Angle	Q <sub>1/2</sub>	I <sub>F</sub> = 600 mA		±60		deg.

‡ Heat sink is required thermal resistance <8K/W