

**HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR****AP2122****General Description**

The AP2122 series are positive voltage regulator ICs fabricated by CMOS process. Each of these ICs consists of a voltage reference, an error amplifier, a resistor network for setting output voltage, a current limit circuit for current protection and a chip enable circuit.

The AP2122 series feature high ripple rejection, low dropout voltage, low noise, high output voltage accuracy, and low current consumption which make them ideal for use in various battery-powered devices.

The AP2122 series have 1.5V, 1.8V, 2.5V, 2.8V, 3.0V, 3.2V and 3.3V versions.

The AP2122 are available in standard SOT-23-5 package.

**Features**

- Low Dropout Voltage at  $I_{OUT}=100mA$ : 150mV Typical (Except 1.5V Version)
- Low Standby Current: 0.1 $\mu$ A Typical
- Low Quiescent Current: 25 $\mu$ A Typical
- High Ripple Rejection: 70dB Typical ( $f=10kHz$ )
- Maximum Output Current: More Than 150mA (300mA Limit)
- Extremely Low Noise: 30 $\mu$ Vrms (10Hz to 100kHz)
- Excellent Line Regulation: 4mV Typical
- Excellent Load Regulation: 12mV Typical
- High Output Voltage Accuracy:  $\pm 2\%$
- Excellent Line and Load Transient Response
- Compatible with Low ESR Ceramic Capacitor (as Low as 1 $\mu$ F)

**Applications**

- Mobile Phones, Cordless Phones
- MP3/4
- Portable Electronic Devices
- Cameras, Video Recorders
- Sub-board Power Supplies for Telecom Equipment
- Battery Powered Equipment




Figure 1. Package Type of AP2122

**HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR****AP2122****Pin Configuration**

K Package  
(SOT-23-5)




Figure 2. Pin Configuration of AP2122 (Top View)

**Pin Description**

Pin Number	Pin Name	Function
1	V <sub>OUT</sub>	Regulated output voltage
2	GND	Ground
3	V <sub>IN</sub>	Input voltage
4	CE	Active high enable input pin. Logic high=enable, logic low=shutdown
5	NC	No connection


**HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR****AP2122****Functional Block Diagram**


Figure 3. Functional Block Diagram of AP2122



## HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR

AP2122

## Ordering Information



Package	Temperature Range	Condition	Part Number	Marking ID	Packing Type
SOT-23-5	-40 to 85°C	Active High (Pull-down resistor built-in)	AP2122AK-1.5TRE1	E2Z	Tape & Reel
		Active High (Pull-down resistor built-in)	AP2122AK-1.8TRE1	E2U	Tape & Reel
		Active High (Pull-down resistor built-in)	AP2122AK-2.5TRE1	E2V	Tape & Reel
		Active High (Pull-down resistor built-in)	AP2122AK-2.8TRE1	E2W	Tape & Reel
		Active High (Pull-down resistor built-in)	AP2122AK-3.0TRE1	E2X	Tape & Reel
		Active High (Pull-down resistor built-in)	AP2122AK-3.2TRE1	E3Y	Tape & Reel
		Active High (Pull-down resistor built-in)	AP2122AK-3.3TRE1	E2Y	Tape & Reel

BCD Semiconductor's Pb-free products, as designated with "E1" suffix in the part number, are RoHS compliant.



## HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR

AP2122

## Absolute Maximum Ratings (Note 1)

Parameter	Symbol	Value	Unit
Input Voltage	V <sub>IN</sub>	6.5	V
Enable Input Voltage	V <sub>CE</sub>	-0.3 to V <sub>IN</sub> +0.3	V
Output Current	I <sub>OUT</sub>	300	mA
Junction Temperature	T <sub>J</sub>	150	°C
Storage Temperature Range	T <sub>STG</sub>	-65 to 150	°C
Lead Temperature (Soldering, 10sec)	T <sub>LEAD</sub>	260	°C
Thermal Resistance (Note 2)	θ <sub>JA</sub>	250	°C/W
ESD (Human Body Model)	ESD	2000	V
ESD (Machine Model)	ESD	200	V

Note 1: Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "Recommended Operating Conditions" is not implied. Exposure to "Absolute Maximum Ratings" for extended periods may affect device reliability.

Note 2: Absolute maximum ratings indicate limits beyond which damage to the component may occur. Electrical specifications do not apply when operating the device outside of its operating ratings. The maximum allowable power dissipation is a function of the maximum junction temperature, T<sub>J(max)</sub>, the junction-to-ambient thermal resistance, θ<sub>JA</sub>, and the ambient temperature, T<sub>A</sub>. The maximum allowable power dissipation at any ambient temperature is calculated using: P<sub>D(max)</sub>=(T<sub>J(max)</sub> - T<sub>A</sub>)/θ<sub>JA</sub>. Exceeding the maximum allowable power dissipation will result in excessive die temperature.

## Recommended Operating Conditions

Parameter	Symbol	Min	Max	Unit
Input Voltage	V <sub>IN</sub>	2	6	V
Operating Junction Temperature Range	T <sub>J</sub>	-40	85	°C



## HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR

AP2122

## Electrical Characteristics

## AP2122-1.5 Electrical Characteristics

(V<sub>IN</sub>=2.5V, T<sub>J</sub>=25°C, C<sub>IN</sub>=1μF, C<sub>OUT</sub>=1μF, **Bold** typeface applies over -40°C≤T<sub>J</sub>≤85°C, unless otherwise specified.)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Output Voltage	V <sub>OUT</sub>	V <sub>IN</sub> =2.5V 1mA≤I <sub>OUT</sub> ≤30mA	1.47	1.5	1.53	V
Input Voltage	V <sub>IN</sub>				6	V
Output Current	I <sub>OUT</sub>	V <sub>IN</sub> -V <sub>OUT</sub> =1V	150			mA
Load Regulation	V <sub>RLOAD</sub>	V <sub>IN</sub> =2.5V 1mA≤I <sub>OUT</sub> ≤80mA		12	40	mV
Line Regulation	V <sub>RLINE</sub>	2.3V≤V <sub>IN</sub> ≤6V I <sub>OUT</sub> =30mA		4	16	mV
Dropout Voltage	V <sub>DROP</sub>	I <sub>OUT</sub> =10mA		400	600	mV
		I <sub>OUT</sub> =100mA		400	600	
		I <sub>OUT</sub> =150mA		400	600	
Quiescent Current	I <sub>Q</sub>	V <sub>IN</sub> =2.5V, I <sub>OUT</sub> =0mA		25	50	μA
Standby Current	I <sub>STD</sub>	V <sub>IN</sub> =2.5V V <sub>CE</sub> in OFF mode		0.1	1	μA
Power Supply Rejection Ratio	PSRR	Ripple 0.5Vp-p, f=10kHz V <sub>IN</sub> =2.5V		70		dB
Output Voltage Temperature Coefficient	ΔV <sub>OUT</sub> /ΔT	I <sub>OUT</sub> =30mA		±150		μV/°C
	(ΔV <sub>OUT</sub> /V <sub>OUT</sub> )/ΔT			±100		ppm/°C
Short Current Limit	I <sub>LIMIT</sub>	V <sub>OUT</sub> =0V		50		mA
RMS Output Noise	V <sub>NOISE</sub>	T <sub>A</sub> =25°C 10Hz ≤f≤100kHz		30		μVrms
CE "High" Voltage		CE input voltage "High"	1.5			V
CE "Low" Voltage		CE input voltage "Low"			0.25	V
CE Pull-down Internal Resistance	R <sub>PD</sub>		2.5	5	10	MΩ



## HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR

AP2122

## Electrical Characteristics (Continued)

## AP2122-1.8 Electrical Characteristics

(V<sub>IN</sub>=2.8V, T<sub>J</sub>=25°C, C<sub>IN</sub>=1μF, C<sub>OUT</sub>=1μF, Bold typeface applies over -40°C≤T<sub>J</sub>≤85°C, unless otherwise specified.)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Output Voltage	V <sub>OUT</sub>	V <sub>IN</sub> =2.8V 1mA≤I <sub>OUT</sub> ≤30mA	1.764	1.8	1.836	V
Input Voltage	V <sub>IN</sub>				6	V
Output Current	I <sub>OUT</sub>	V <sub>IN</sub> -V <sub>OUT</sub> =1V	150			mA
Load Regulation	V <sub>RLOAD</sub>	V <sub>IN</sub> =2.8V 1mA≤I <sub>OUT</sub> ≤80mA		12	40	mV
Line Regulation	V <sub>RLINE</sub>	2.3V≤V <sub>IN</sub> ≤6V I <sub>OUT</sub> =30mA		4	16	mV
Dropout Voltage	V <sub>DROP</sub>	I <sub>OUT</sub> =10mA		20	40	mV
		I <sub>OUT</sub> =100mA		150	300	
		I <sub>OUT</sub> =150mA		200	400	
Quiescent Current	I <sub>Q</sub>	V <sub>IN</sub> =2.8V, I <sub>OUT</sub> =0mA		25	50	μA
Standby Current	I <sub>STD</sub>	V <sub>IN</sub> =2.8V V <sub>CE</sub> in OFF mode		0.1	1	μA
Power Supply Rejection Ratio	PSRR	Ripple 0.5Vp-p, f=10kHz V <sub>IN</sub> =2.8V		70		dB
Output Voltage Temperature Coefficient	ΔV <sub>OUT</sub> /ΔT	I <sub>OUT</sub> =30mA		±180		μV/°C
	(ΔV <sub>OUT</sub> /V <sub>OUT</sub> )/ΔT			±100		ppm/°C
Short Current Limit	I <sub>LIMIT</sub>	V <sub>OUT</sub> =0V		50		mA
RMS Output Noise	V <sub>NOISE</sub>	T <sub>A</sub> =25°C 10Hz ≤f≤100kHz		30		μVrms
CE "High" Voltage		CE input voltage "High"	1.5			V
CE "Low" Voltage		CE input voltage "Low"			0.25	V
CE Pull-down Internal Resistance	R <sub>PD</sub>		2.5	5	10	MΩ



## HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR

AP2122

## Electrical Characteristics (Continued)

## AP2122-2.5 Electrical Characteristics

(V<sub>IN</sub>=3.5V, T<sub>J</sub>=25°C, C<sub>IN</sub>=1μF, C<sub>OUT</sub>=1μF, Bold typeface applies over -40°C≤T<sub>J</sub>≤85°C, unless otherwise specified.)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Output Voltage	V <sub>OUT</sub>	V <sub>IN</sub> =3.5V 1mA≤I <sub>OUT</sub> ≤30mA	2.45	2.5	2.55	V
Input Voltage	V <sub>IN</sub>				6	V
Output Current	I <sub>OUT</sub>	V <sub>IN</sub> -V <sub>OUT</sub> =1V	150			mA
Load Regulation	V <sub>RLOAD</sub>	V <sub>IN</sub> =3.5V 1mA≤I <sub>OUT</sub> ≤80mA		12	40	mV
Line Regulation	V <sub>RLINE</sub>	3V≤V <sub>IN</sub> ≤6V I <sub>OUT</sub> =30mA		4	16	mV
Dropout Voltage	V <sub>DROP</sub>	I <sub>OUT</sub> =10mA		20	40	mV
		I <sub>OUT</sub> =100mA		150	300	
		I <sub>OUT</sub> =150mA		200	400	
Quiescent Current	I <sub>Q</sub>	V <sub>IN</sub> =3.5V, I <sub>OUT</sub> =0mA		25	50	μA
Standby Current	I <sub>STD</sub>	V <sub>IN</sub> =3.5V V <sub>CE</sub> in OFF mode		0.1	1	μA
Power Supply Rejection Ratio	PSRR	Ripple 0.5Vp-p, f=10kHz V <sub>IN</sub> =3.5V		70		dB
Output Voltage Temperature Coefficient	ΔV <sub>OUT</sub> /ΔT	I <sub>OUT</sub> =30mA		±250		μV/°C
	(ΔV <sub>OUT</sub> /V <sub>OUT</sub> )/ΔT			±100		ppm/°C
Short Current Limit	I <sub>LIMIT</sub>	V <sub>OUT</sub> =0V		50		mA
RMS Output Noise	V <sub>NOISE</sub>	T <sub>A</sub> =25°C 10Hz ≤f≤100kHz		30		μVrms
CE "High" Voltage		CE input voltage "High"	1.5			V
CE "Low" Voltage		CE input voltage "Low"			0.25	V
CE Pull-down Internal Resistance	R <sub>PD</sub>		2.5	5	10	MΩ



## HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR

AP2122

## Electrical Characteristics (Continued)

## AP2122-2.8 Electrical Characteristics

(V<sub>IN</sub>=3.8V, T<sub>J</sub>=25°C, C<sub>IN</sub>=1μF, C<sub>OUT</sub>=1μF, Bold typeface applies over -40°C≤T<sub>J</sub>≤85°C, unless otherwise specified.)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Output Voltage	V <sub>OUT</sub>	V <sub>IN</sub> =3.8V 1mA≤I <sub>OUT</sub> ≤30mA	2.744	2.8	2.856	V
Input Voltage	V <sub>IN</sub>				6	V
Output Current	I <sub>OUT</sub>	V <sub>IN</sub> -V <sub>OUT</sub> =1V	150			mA
Load Regulation	V <sub>RLOAD</sub>	V <sub>IN</sub> =3.8V 1mA≤I <sub>OUT</sub> ≤80mA		12	40	mV
Line Regulation	V <sub>RLINE</sub>	3.3V≤V <sub>IN</sub> ≤6V I <sub>OUT</sub> =30mA		4	16	mV
Dropout Voltage	V <sub>DROP</sub>	I <sub>OUT</sub> =10mA		20	40	mV
		I <sub>OUT</sub> =100mA		150	300	
		I <sub>OUT</sub> =150mA		200	400	
Quiescent Current	I <sub>Q</sub>	V <sub>IN</sub> =3.8V, I <sub>OUT</sub> =0mA		25	50	μA
Standby Current	I <sub>STD</sub>	V <sub>IN</sub> =3.8V V <sub>CE</sub> in OFF mode		0.1	1	μA
Power Supply Rejection Ratio	PSRR	Ripple 0.5Vp-p, f=10kHz V <sub>IN</sub> =3.8V		70		dB
Output Voltage Temperature Coefficient	ΔV <sub>OUT</sub> /ΔT	I <sub>OUT</sub> =30mA		±280		μV/°C
	(ΔV <sub>OUT</sub> /V <sub>OUT</sub> )/ΔT			±100		ppm/°C
Short Current Limit	I <sub>LIMIT</sub>	V <sub>OUT</sub> =0V		50		mA
RMS Output Noise	V <sub>NOISE</sub>	T <sub>A</sub> =25°C 10Hz ≤f≤100kHz		30		μVrms
CE "High" Voltage		CE input voltage "High"	1.5			V
CE "Low" Voltage		CE input voltage "Low"			0.25	V
CE Pull-down Internal Resistance	R <sub>PD</sub>		2.5	5	10	MΩ



## HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR

AP2122

## Electrical Characteristics (Continued)

## AP2122-3.0 Electrical Characteristics

(V<sub>IN</sub>=4V, T<sub>J</sub>=25°C, C<sub>IN</sub>=1μF, C<sub>OUT</sub>=1μF, **Bold** typeface applies over -40°C≤T<sub>J</sub>≤85°C, unless otherwise specified.)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Output Voltage	V <sub>OUT</sub>	V <sub>IN</sub> =4V 1mA≤I <sub>OUT</sub> ≤30mA	2.94	3.0	3.06	V
Input Voltage	V <sub>IN</sub>				6	V
Output Current	I <sub>OUT</sub>	V <sub>IN</sub> -V <sub>OUT</sub> =1V	150			mA
Load Regulation	V <sub>RLOAD</sub>	V <sub>IN</sub> =4V 1mA≤I <sub>OUT</sub> ≤80mA		12	40	mV
Line Regulation	V <sub>RLINE</sub>	3.5V≤V <sub>IN</sub> ≤6V I <sub>OUT</sub> =30mA		4	16	mV
Dropout Voltage	V <sub>DROP</sub>	I <sub>OUT</sub> =10mA		20	40	mV
		I <sub>OUT</sub> =100mA		150	300	
		I <sub>OUT</sub> =150mA		200	400	
Quiescent Current	I <sub>Q</sub>	V <sub>IN</sub> =4V, I <sub>OUT</sub> =0mA		25	50	μA
Standby Current	I <sub>STD</sub>	V <sub>IN</sub> =4V V <sub>CE</sub> in OFF mode		0.1	1	μA
Power Supply Rejection Ratio	PSRR	Ripple 0.5Vp-p, f=10kHz V <sub>IN</sub> =4V		70		dB
Output Voltage Temperature Coefficient	ΔV <sub>OUT</sub> /ΔT	I <sub>OUT</sub> =30mA		±300		μV/°C
	(ΔV <sub>OUT</sub> /V <sub>OUT</sub> )/ΔT			±100		ppm/°C
Short Current Limit	I <sub>LIMIT</sub>	V <sub>OUT</sub> =0V		50		mA
RMS Output Noise	V <sub>NOISE</sub>	T <sub>A</sub> =25°C 10Hz≤f≤100kHz		30		μVrms
CE "High" Voltage		CE input voltage "High"	1.5			V
CE "Low" Voltage		CE input voltage "Low"			0.25	V
CE Pull-down Internal Resistance	R <sub>PD</sub>		2.5	5	10	MΩ



## HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR

AP2122

## Electrical Characteristics (Continued)

## AP2122-3.2 Electrical Characteristics

(V<sub>IN</sub>=4.2V, T<sub>J</sub>=25°C, C<sub>IN</sub>=1μF, C<sub>OUT</sub>=1μF, Bold typeface applies over -40°C≤T<sub>J</sub>≤85°C, unless otherwise specified.)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Output Voltage	V <sub>OUT</sub>	V <sub>IN</sub> =4.2V 1mA≤I <sub>OUT</sub> ≤30mA	3.136	3.2	3.264	V
Input Voltage	V <sub>IN</sub>				6	V
Output Current	I <sub>OUT</sub>	V <sub>IN</sub> -V <sub>OUT</sub> =1V	150			mA
Load Regulation	V <sub>RLOAD</sub>	V <sub>IN</sub> =4.2V 1mA≤ I <sub>OUT</sub> ≤ 80mA		12	40	mV
Line Regulation	V <sub>RLINE</sub>	3.7V≤V <sub>IN</sub> ≤6V I <sub>OUT</sub> =30mA		4	16	mV
Dropout Voltage	V <sub>DROP</sub>	I <sub>OUT</sub> =10mA		20	40	mV
		I <sub>OUT</sub> =100mA		150	300	
		I <sub>OUT</sub> =150mA		200	400	
Quiescent Current	I <sub>Q</sub>	V <sub>IN</sub> =4.2V, I <sub>OUT</sub> =0mA		25	50	μA
Standby Current	I <sub>STD</sub>	V <sub>IN</sub> =4.2V V <sub>CE</sub> in OFF mode		0.1	1	μA
Power Supply Rejection Ratio	PSRR	Ripple 0.5Vp-p, f=10kHz V <sub>IN</sub> =4.2V		70		dB
Output Voltage Temperature Coefficient	ΔV <sub>OUT</sub> /ΔT	I <sub>OUT</sub> =30mA		±320		μV/°C
	(ΔV <sub>OUT</sub> /V <sub>OUT</sub> )/ΔT			±100		ppm/°C
Short Current Limit	I <sub>LIMIT</sub>	V <sub>OUT</sub> =0V		50		mA
RMS Output Noise	V <sub>NOISE</sub>	T <sub>A</sub> =25°C 10Hz ≤f≤100kHz		30		μVrms
CE "High" Voltage		CE input voltage "High"	1.5			V
CE "Low" Voltage		CE input voltage "Low"			0.25	V
CE Pull-down Internal Resistance	R <sub>PD</sub>		2.5	5	10	MΩ



## HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR

AP2122

## Electrical Characteristics (Continued)

## AP2122-3.3 Electrical Characteristics

(V<sub>IN</sub>=4.3V, T<sub>J</sub>=25°C, C<sub>IN</sub>=1μF, C<sub>OUT</sub>=1μF, Bold typeface applies over -40°C≤T<sub>J</sub>≤85°C, unless otherwise specified.)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Output Voltage	V <sub>OUT</sub>	V <sub>IN</sub> =4.3V 1mA≤I <sub>OUT</sub> ≤30mA	3.234	3.3	3.366	V
Input Voltage	V <sub>IN</sub>				6	V
Output Current	I <sub>OUT</sub>	V <sub>IN</sub> -V <sub>OUT</sub> =1V	150			mA
Load Regulation	V <sub>RLOAD</sub>	V <sub>IN</sub> =4.3V 1mA≤I <sub>OUT</sub> ≤80mA		12	40	mV
Line Regulation	V <sub>RLINE</sub>	3.8V≤V <sub>IN</sub> ≤6V I <sub>OUT</sub> =30mA		4	16	mV
Dropout Voltage	V <sub>DROP</sub>	I <sub>OUT</sub> =10mA		20	40	mV
		I <sub>OUT</sub> =100mA		150	300	
		I <sub>OUT</sub> =150mA		200	400	
Quiescent Current	I <sub>Q</sub>	V <sub>IN</sub> =4.3V, I <sub>OUT</sub> =0mA		25	50	μA
Standby Current	I <sub>STD</sub>	V <sub>IN</sub> =4.3V V <sub>CE</sub> in OFF mode		0.1	1	μA
Power Supply Rejection Ratio	PSRR	Ripple 0.5Vp-p, f=10kHz V <sub>IN</sub> =4.3V		70		dB
Output Voltage Temperature Coefficient	ΔV <sub>OUT</sub> /ΔT	I <sub>OUT</sub> =30mA		±330		μV/°C
	(ΔV <sub>OUT</sub> /V <sub>OUT</sub> )/ΔT			±100		ppm/°C
Short Current Limit	I <sub>LIMIT</sub>	V <sub>OUT</sub> =0V		50		mA
RMS Output Noise	V <sub>NOISE</sub>	T <sub>A</sub> =25°C 10Hz ≤f≤100kHz		30		μVrms
CE "High" Voltage		CE input voltage "High"	1.5			V
CE "Low" Voltage		CE input voltage "Low"			0.25	V
CE Pull-down Internal Resistance	R <sub>PD</sub>		2.5	5	10	MΩ

## HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR

AP2122

## Typical Performance Characteristics




Figure 4. Output Voltage vs. Output Current




Figure 5. Output Voltage vs. Output Current




Figure 6. Output Voltage vs. Input Voltage




Figure 7. Output Voltage vs. Input Voltage

## HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR

AP2122

## Typical Performance Characteristics (Continued)




Figure 8. Dropout Voltage vs. Output Current




Figure 9. Dropout Voltage vs. Output Current




Figure 10. Output Voltage vs. Junction Temperature




Figure 11. Output Voltage vs. Junction Temperature

## HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR

AP2122

## Typical Performance Characteristics (Continued)




Figure 12. Supply Current vs. Input Voltage




Figure 13. Supply Current vs. Input Voltage




Figure 14. Supply Current vs. Junction Temperature




Figure 15. Supply Current vs. Junction Temperature

## HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR

AP2122

## Typical Performance Characteristics (Continued)




Figure 16. Line Transient  
(Conditions:  $I_{OUT}=30mA$ ,  $C_{IN}=1\mu F$ ,  $C_{OUT}=1\mu F$ )




Figure 17. Line Transient  
(Conditions:  $I_{OUT}=30mA$ ,  $C_{IN}=1\mu F$ ,  $C_{OUT}=1\mu F$ )




Figure 18. Load Transient  
(Conditions:  $V_{IN}=2.5V$ ,  $C_{IN}=1\mu F$ ,  $C_{OUT}=1\mu F$ )




Figure 19. Load Transient  
(Conditions:  $V_{IN}=4V$ ,  $C_{IN}=1\mu F$ ,  $C_{OUT}=1\mu F$ )


**HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR****AP2122****Typical Performance Characteristics (Continued)**

Figure 20. PSRR vs. Frequency





Figure 21. PSRR vs. Frequency

**HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR****AP2122****Typical Application**

Note: Filter capacitors are required at the AP2122's input and output.  $1\mu F$  capacitor is required at the input. The minimum output capacitance required for stability should be more than  $1\mu F$  with ESR from  $0.01\Omega$  to  $100\Omega$ . Ceramic capacitors are recommended.

Figure 22. Typical Application of AP2122


## HIGH SPEED, EXTREMELY LOW NOISE LDO REGULATOR

AP2122

## Mechanical Dimensions

SOT-23-5

Unit: mm(inch)





## BCD Semiconductor Manufacturing Limited

<http://www.bcdsemi.com>

### IMPORTANT NOTICE

BCD Semiconductor Manufacturing Limited reserves the right to make changes without further notice to any products or specifications herein. BCD Semiconductor Manufacturing Limited does not assume any responsibility for use of any its products for any particular purpose, nor does BCD Semiconductor Manufacturing Limited assume any liability arising out of the application or use of any its products or circuits. BCD Semiconductor Manufacturing Limited does not convey any license under its patent rights or other rights nor the rights of others.

---

#### MAIN SITE

- Headquarters  
**BCD Semiconductor Manufacturing Limited**  
No. 1600, Zi Xing Road, Shanghai Zizhu Science-based Industrial Park, 200241, China  
Tel: +86-21-24162266, Fax: +86-21-24162277

- Wafer Fab  
**Shanghai SIM-BCD Semiconductor Manufacturing Co., Ltd.**  
800 Yi Shan Road, Shanghai 200233, China  
Tel: +86-21-6485 1491, Fax: +86-21-5450 0008

---

#### REGIONAL SALES OFFICE

**Shenzhen Office**  
**Shanghai SIM-BCD Semiconductor Manufacturing Co., Ltd., Shenzhen Office**  
Room E, SF, Noble Center, No.1006, 3rd Fuzhong Road, Futian District, Shenzhen,  
518026, China  
Tel: +86-755-8826 7951  
Fax: +86-755-8826 7865

**Taiwan Office**  
**BCD Semiconductor (Taiwan) Company Limited**  
4F, 298-1, Rui Guang Road, Nei-Hu District, Taipei,  
Taiwan  
Tel: +886-2-2656 2808  
Fax: +886-2-2656 2806

**USA Office**  
**BCD Semiconductor Corp.**  
30920 Huntwood Ave. Hayward,  
CA 94544, USA  
Tel : +1-510-324-2988  
Fax: +1-510-324-2788