

**WIDE INPUT VOLTAGE RANGE, 150mA ULDO REGULATOR****AP2204****Description**

AP2204 series are positive voltage regulator IC fabricated by high voltage EPNP process.

The AP2204 has features of wide input voltage range and high accuracy, high ripple rejection, low dropout voltage, low noise, current limit and ultra-low quiescent current which make them ideal for use in various USB and portable device.

The IC consists of a voltage reference, an error amplifier, a resistor network for setting output voltage, a current limit circuit for current protection, and a chip enable circuit.

AP2204 has adjustable, 1.8V, 3.3V, 5.0V fixed voltage versions.

Features

- Wide Input Voltage Range: 2.3V to 24V
- Excellent Ripple Rejection: 60dB @ f=1kHz
- Low Dropout Voltage: $V_{\text{DROP}}=50\text{mV}$ @ $I_{\text{OUT}}=100\mu\text{A}$
- Low Ground Current
- High Output Voltage Accuracy
- Compatible with Low ESR Ceramic Capacitor
- Excellent Line/Load Regulation
- Thermal Shutdown Function
- Reverse Battery Protection
- Reverse Leakage Protection

Benefits

- Low Noise
- Low Dropout
- Very Low Standby Current
- High PSRR
- Lower Price
- Easy to Use in Mobile Phone

Parametric Table


Maximum Output Current (Min.) (A)	0.15
Standby Current (Max) (μA)	1
V_{DROP} at 100 μA (Typ) (mV)	50
V_{IN} (Min) (V)	2.3
V_{IN} (Max) (V)	24
V_{OUT} (V)	1.8, 3.3, 5.0, ADJ.
PSRR (dB)	60
Accuracy (%)	± 2
Load Regulation (Typ) (mV)	15 (3.3V)
Line Regulation (Typ) (mV)	10 (3.3V)
On/Off Pin	Yes
Error Flag	No

Applications

- Battery-powered Equipment
- Laptop, Palmtops, Notebook Computers
- Portable Information Appliance

Additional Available Materials

- Samples
- Preliminary Datasheet
- ESD Report

WIDE INPUT VOLTAGE RANGE, 150mA ULDO REGULATOR
AP2204
Pin Configuration

Ordering Information Example

Package	Temperature Range	Part Number	Marking ID	Packing Type
		Green	Green	
SOT-23-5	-40 to 125°C	AP2204K-ADJTRG1	GAF	Tape & Reel
		AP2204K-1.8TRG1	GAG	Tape & Reel
		AP2204K-3.3TRG1	GAH	Tape & Reel
		AP2204K-5.0TRG1	GAI	Tape & Reel
SOT-89	-40 to 125°C	AP2204R-1.8TRG1	G31C	Tape & Reel
		AP2204R-3.3TRG1	G31D	Tape & Reel
		AP2204R-5.0TRG1	G31E	Tape & Reel

Detailed information please refer to the relevant datasheet.

Sales Office:
Shanghai

No. 1600, Zi Xing Road, Shanghai ZiZhu Science-based Industrial Park, 200241, China
 Tel : 86-21-24162266
 Fax : 86-21-24162277

Taiwan

4F, 298-1 Rui Guang Road, Nei-Hu District, Taipei, Taiwan
 Tel : 886-2-2656-2808
 Fax : 886-2-2656-2806

USA

30920 Huntwood Ave. Hayward, CA 94544, USA
 Tel : +1-510-324-2988
 Fax : +1-510-324-2788

Shenzhen

Room E, 5F, Noble Center, No.1006, 3rd Fuzhong Road, Futian District, Shenzhen 518026, China
 Tel : 86-755-8826 7951
 Fax : 86-755-8826 7865