


Thermopile Infrared Detectors

# Thermopile Detector TPS 534



**Large absorber size – high signal output**


**Low temperature coefficient of sensitivity**

**Thermistor temperature reference included**

**Applications in pyrometers, and - with additional infrared bandpass filters - in gas detectors**




The **TPS 534** thermopile sensor in TO 5 type housing employs a chip of 1.2 x 1.2 mm<sup>2</sup> absorber size and a 30 kΩ thermistor as temperature reference. The round window opening is equipped with a 5.5 μm longpass (standard) infrared filter. The sensor shows a flat sensitivity characteristics over the wavelength.

Remark: The TPS 534 can also be equipped with infrared bandpass filters for NDIR gas detection.



Parameters	TPS	534	typical	units	condition
<b>Sensitive area</b>	1.2 x 1.2	mm <sup>2</sup>	absorbing area		
<b>Window size</b>	3.8	mm	diameter		
<b>DC Sensitivity</b>	20	V/W	500K BB, 5...14μm		
<b>Resistance</b>	40	kΩ	25°C		
<b>Noise</b>	25	nV/√Hz	r.m.s. 300K, 1Hz		
<b>NEP</b>	1.26	nW/√Hz	500K BB, 5...14μm		
<b>D*</b>	0.96 x 10 <sup>8</sup>	cm <sup>2</sup> /Hz/W	500K BB, 5...14μm		
<b>Time constant</b>	35	ms			
<b>tc of responsivity</b>	-0.01	%/K			
<b>tc of resistance</b>	0.02	%/K			
<b>Operating Temperature</b>	-40	100	non permanent		
<b>Storage Temperature</b>	-40	120	non permanent		
<b>Thermistor Resistance</b>	30	kΩ	25°C		
<b>Beta</b>	3964	K	25°C / 100°C		
<b>Field of view</b>	80	°	at 50% points		

Right for modification reserved / WS / 2.7.2001



Europe:  
**PerkinElmer** Optoelectronics GmbH  
 Wenzel Jaksch Str 31  
 Wiesbaden / Germany  
 Phone +49(0)611 492 0  
 Fax +49(0)611 492 170

USA:  
**PerkinElmer** Optoelectronics  
 2175 Mission College Blvd  
 Santa Clara, CA 95054  
 Phone +408 565 0830  
 Fax +408 565 0703

Asia:  
**PerkinElmer** Optoelectronics  
 47, Ayer Rajah Crescent #06-12  
 Singapore 139947  
 Phone +65 775 2022  
 Fax +65 775 1008



DATASHEET