

μ A727

Temperature-Controlled Differential Preamplifier

Special Function Products

Description

The μ A727 is a monolithic, fixed gain, Differential Input/Output Preamplifier, constructed with the Fairchild Planar epitaxial process, mounted in a high thermal resistance package, and held at constant temperature by active regulator circuitry. The high gain and low-standby dissipation of the regulator circuit give tight temperature control over a wide ambient temperature range. The device is intended for use as a self-contained input stage in very low drift dc amplifiers, replacing complex chopper-stabilized amplifiers in such applications as thermo-couple bridges, strain-gauge transducers, and a/d converters.

- **VERY LOW OFFSET DRIFTS**
- **HIGH INPUT IMPEDANCE** $300 \text{ M}\Omega$
- **WIDE COMMON MODE RANGE** $C_{MRR} = 100 \text{ dB}$

Absolute Maximum Ratings

Operating Temperature Range

Military (μ A727) -55°C to $+125^\circ\text{C}$ Commercial (μ A727C) -20°C to $+85^\circ\text{C}$

Storage Temperature Range

 -65°C to $+150^\circ\text{C}$

Pin Temperature (Soldering, 60 s)

 300°C

Internal Power Dissipation

500 mW


Supply Voltage

(Amplifier and Heater) $\pm 18 \text{ V}$

Differential Input Voltage

 $\pm 10 \text{ V}$


Common Mode Input Voltage

 $\pm 15 \text{ V}$
**Connection Diagram
10-Pin Metal Package**


(Top View)

Order Information

Type	Package	Code	Part No.
μ A727	Metal	5U	μ A727HM
μ A727C	Metal	5U	μ A727HC

Equivalent Circuit

μ A727

Electrical Characteristics $-55^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$, $V_{H+} = +15\text{ V}$, $V- = -15\text{ V}$, $R_{ADJ} = 330\text{ k}\Omega$, unless otherwise specified.

Characteristic	Condition	Min	Typ	Max	Unit
Input Offset Voltage	$R_S \leq 50\text{ }\Omega$		2.0	10	mV
Input Offset Current			2.5	15	nA
Input Bias Current			12	40	nA
Input Offset Voltage Drift	$R_S \leq 50\text{ }\Omega$, $+25^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$		0.6	1.5	$\mu\text{V}/^{\circ}\text{C}$
	$R_S \leq 50\text{ }\Omega$, $-55^{\circ}\text{C} \leq T_A \leq +25^{\circ}\text{C}$		0.6	1.5	$\mu\text{V}/^{\circ}\text{C}$
Input Offset Current Drift	$+25^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$		2.0		$\text{pA}/^{\circ}\text{C}$
	$-55^{\circ}\text{C} \leq T_A \leq +25^{\circ}\text{C}$		2.0		$\text{pA}/^{\circ}\text{C}$
Input Bias Current Drift	$-55^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$		15		$\text{pA}/^{\circ}\text{C}$
Differential Input Resistance			300		M Ω
Common-Mode Input Resistance			1000		M Ω
Input Voltage Range		± 12	± 13		V
Supply Voltage Rejection Ratio	$R_S \leq 100\text{ k}\Omega$		80		$\mu\text{V/V}$
Common-Mode Rejection Ratio	$R_S \leq 100\text{ k}\Omega$	80	100		dB
Output Resistance			1.0	4.0	k Ω
Output Common-Mode Voltage		-6.0	-5.0	-4.0	V
Differential Output Voltage Swing		± 5.0	± 7.0	± 10	V
Output Sink Current		10	30	80	μA
Differential Load Rejection			5.0	10	$\mu\text{V}/\mu\text{A}$
Differential Voltage Gain		60	100	250	
Low Frequency Noise	$BW = 10\text{ Hz to }500\text{ Hz}$, $R_S \leq 50\text{ }\Omega$		3.0		μV_{rms}
Long Term Drift	$R_S \leq 50\text{ }\Omega$		5.0		$\mu\text{V}/\text{week}$
Amplifier Supply Current	$T_A = +25^{\circ}\text{C}$		1.0	2.0	mA
Heater Supply Current	$T_A = +25^{\circ}\text{C}$		10	15	mA


μA727C

Electrical Characteristics $-20^\circ\text{C} \leq T_A \leq +85^\circ\text{C}$, $V_{H+} = V_{A+} = +15\text{ V}$, $V_- = -15\text{ V}$, $R_{ADJ} = 1\text{ M}\Omega$, unless otherwise specified.


Characteristic	Condition	Min	Typ	Max	Unit	
Input Offset Voltage	$R_S \leq 50\text{ }\Omega$		2.0	10	mV	
Input Offset Current			2.5	25	nA	
Input Bias Current			12	75	nA	
Input Offset Voltage Drift	$R_S \leq 50\text{ }\Omega$		0.6	3.0	$\mu\text{V}/^\circ\text{C}$	
Input Offset Current Drift			2.0		$\text{pA}/^\circ\text{C}$	
Input Bias Current Drift			15		$\text{pA}/^\circ\text{C}$	
Differential Input Resistance			300		MΩ	
Common Mode Input Resistance			1000		MΩ	
Input Voltage Range		± 12	± 13		V	
Supply Voltage Rejection Ratio	$R_S \leq 100\text{ k}\Omega$		80		$\mu\text{V/V}$	
Common Mode Rejection Ratio	$R_S \leq 100\text{ k}\Omega$	70	100		dB	
Output Resistance			1.0	4.0	kΩ	
Output Common Mode Voltage			-7.0	-5.0	-4.0	V
Differential Output Voltage Swing			± 3.0	± 7.0	± 10	V
Output Sink Current		10	30	80	μA	
Differential Load Rejection			5.0	15	$\mu\text{V}/\mu\text{A}$	
Differential Voltage Gain		50	100	250		
Low Frequency Noise	$BW = 10\text{ Hz to } 500\text{ Hz}$, $R_S \leq 50\text{ }\Omega$		3.0		μV_{rms}	
Long Term Drift	$R_S \leq 50\text{ }\Omega$		5.0		$\mu\text{V}/\text{week}$	
Amplifier Supply Current	$T_A = +25^\circ\text{C}$		1.0	2.0	mA	
Heater Supply Current	$T_A = +25^\circ\text{C}$		10	15	mA	

Typical Performance Curves


Noise Voltage vs Frequency



Noise Current vs Frequency




Spot Noise Contours




Typical Performance Curves (Cont.)


Recommended R_{ADJ} vs Maximum Ambient Temperature




Relative Chip Temperature vs Ambient Temperature




Power Consumption vs Ambient Temperature




Input Common-Mode Voltage Range vs Supply Voltage




Output Common-Mode Voltage vs Supply Voltage




Amplifier Current vs Supply Voltage



Differential Voltage Gain vs Supply Voltage



Required R_{ADJ} for Constant I_{ADJ} vs Supply Voltage



Open Loop Frequency Response for Various Values of Compensation

