

Silicon PNP Power Transistors

2SA1093

DESCRIPTION


- With TO-3P(I) package
- Complement to type 2SC2563
- High transition frequency

APPLICATIONS

- Audio frequency power amplifier applicatios

PINNING

PIN	DESCRIPTION
1	Emitter
2	Collector;connected to mounting base
3	Base

Absolute maximum ratings($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	Open emitter	-120	V
V_{CEO}	Collector-emitter voltage	Open base	-120	V
V_{EBO}	Emitter-base voltage	Open collector	-5	V
I_C	Collector current		-8	A
I_B	Base current		-0.8	A
P_T	Total power dissipation	$T_C=25^\circ\text{C}$	80	W
T_j	Junction temperature		150	$^\circ\text{C}$
T_{stg}	Storage temperature		-55~150	$^\circ\text{C}$

Silicon PNP Power Transistors

2SA1093

CHARACTERISTICS

T_j=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-emitter breakdown voltage	I _C =-50mA, I _B =0	-120			V
V _{CEsat}	Collector-emitter saturation voltage	I _C =-4A; I _B =-0.4A		-1.0	-2.0	V
V _{BE}	Base-emitter voltage	I _C =-4A; V _{CE} =-5V		-1.5	-2.5	V
I _{CBO}	Collector cut-off current	V _{CB} =-120V; I _E =0			-50	μ A
I _{EBO}	Emitter cut-off current	V _{EB} =-5V; I _C =0			-50	μ A
h _{FE-1}	DC current gain	I _C =-1A; V _{CE} =-5V	55		240	
h _{FE-2}	DC current gain	I _C =-4A; V _{CE} =-5V	30			
f _T	Transition frequency	I _C =-1A; V _{CE} =-10V		90		MHz
C _{ob}	Output capacitance	I _E =0; V _{CB} =-10V; f=1MHz		150		pF

◆ h_{FE-1} Classifications

R	O	Y
55-110	80-160	120-240

Silicon PNP Power Transistors

2SA1093

PACKAGE OUTLINE

