

**NPN EPITAXIAL SILICON TRANSISTOR
FOR MICROWAVE HIGH-GAIN AMPLIFICATION**

FEATURE

- High f_T
17 GHz TYP.
- High gain
 $|S_{21e}|^2 = 15.5$ dB TYP.
@ $f = 2$ GHz, $V_{CE} = 2$ V, $I_c = 7$ mA
- $NF = 1.1$ dB, @ $f = 2$ GHz $V_{CE} = 2$ V, $I_c = 1$ mA
- 6-pin Small Mini Mold Package



ORDERING INFORMATION

PART NUMBER	QUANTITY	PACKING STYLE
2SC5408-T1	3 kpcs/reel	8-mm wide emboss taping, 6-pin (collector) feed hole direction

Remark To order evaluation samples, consult your NEC sales personnel (supported in 50-pcs units).

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATING	UNIT
Collector to Base Voltage	V_{CBO}	5	V
Collector to Emitter Voltage	V_{CEO}	3	V
Emitter to Base Voltage	V_{EBO}	2	V
Collector Current	I_c	10	mA
Total Power Dissipation	P_T	30	mW
Junction Temperature	T_j	150	°C
Storage Temperature	T_{stg}	-65 to +150	°C

PACKAGE DIMENSIONS (in mm)**PIN CONNECTIONS**

E: Emitter
C: Collector
B: Base

Because this product uses high-frequency process, avoid excessive input of static electricity, etc.





ELECTRICAL CHARACTERISTICS (T_A = 25 °C)






PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I _{CBO}	V _{CB} = 5 V, I _E = 0			0.1	μA
Emitter Cut-off Current	I _{EBO}	V _{EB} = 1 V, I _C = 0			0.1	μA
DC Current Gain	h _{FE}	V _{CE} = 2 V, I _C = 7 mA Note 1	70		140	
Gain Bandwidth Product	f _T	V _{CE} = 2 V, I _C = 7 mA, f = 2.0 GHz		17		GHz
Feed-back Capacitance	C _{re}	V _{CB} = 2 V, I _E = 0, f = 1 MHz Note 2		0.1	0.15	pF
Insertion Power Gain	S _{21e} ²	V _{CE} = 2 V, I _C = 7 mA, f = 2.0 GHz	13	15.5		dB
Noise Figure	NF	V _{CE} = 2 V, I _C = 1 mA, f = 2.0 GHz		1.1	1.8	dB

Rank	FB
Marking	T1E
h _{FE}	70 to 40

- Notes**
1. Pulse measurement PW ≤ 350 μs, duty cycle ≤ 2 %, pulsed
 2. Measured with three-pin bridge, with emitter pin connected to the bridge guard.

TYPICAL CHARACTERISTICS (T_A = 25 °C)





S PARAMETER

V_{CE} = 2 V I_c = 1 mA

FREQUENCY MHz	S ₁₁		S ₂₁		S ₁₂		S ₂₂	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
100.000	0.969	-4.1	3.345	174.9	0.006	84.6	0.991	-3.2
200.000	0.967	-8.2	3.287	170.3	0.012	82.8	0.993	-6.8
300.000	0.959	-12.3	3.334	165.9	0.018	79.0	0.990	-10.0
400.000	0.952	-16.6	3.361	161.4	0.024	75.8	0.990	-13.6
500.000	0.943	-20.8	3.280	156.3	0.031	71.8	0.980	-17.3
600.000	0.931	-25.2	3.307	151.2	0.036	68.4	0.971	-20.8
700.000	0.919	-29.5	3.286	146.9	0.042	64.5	0.963	-24.2
800.000	0.903	-34.1	3.278	141.6	0.047	61.0	0.952	-28.1
900.000	0.883	-38.6	3.268	136.4	0.052	57.0	0.940	-31.6
1 000.000	0.865	-42.9	3.226	132.3	0.057	53.4	0.927	-35.3
1 100.000	0.842	-47.4	3.197	127.4	0.060	49.9	0.913	-38.8
1 200.000	0.817	-51.9	3.175	122.4	0.065	46.0	0.901	-42.6
1 300.000	0.796	-56.6	3.127	118.2	0.067	42.8	0.885	-46.2
1 400.000	0.774	-61.3	3.077	113.1	0.070	39.4	0.863	-49.6
1 500.000	0.748	-66.2	3.059	108.5	0.072	36.6	0.852	-53.2
1 600.000	0.725	-71.1	3.047	103.9	0.073	33.5	0.836	-56.8
1 700.000	0.702	-76.1	2.978	99.4	0.074	30.8	0.824	-60.0
1 800.000	0.678	-81.1	2.920	95.4	0.075	28.1	0.808	-64.0
1 900.000	0.653	-86.3	2.920	90.5	0.074	25.7	0.794	-67.2
2 000.000	0.633	-91.5	2.856	86.3	0.074	23.5	0.780	-70.8
2 100.000	0.611	-97.3	2.834	82.0	0.074	21.1	0.771	-74.1
2 200.000	0.591	-102.9	2.795	77.6	0.073	19.0	0.756	-77.6
2 300.000	0.571	-108.8	2.751	73.0	0.072	16.9	0.748	-81.4
2 400.000	0.554	-114.9	2.713	68.6	0.071	15.0	0.744	-85.0
2 500.000	0.535	-120.7	2.656	64.2	0.068	13.6	0.733	-88.5
2 600.000	0.520	-127.0	2.619	59.7	0.065	12.7	0.727	-91.6

V_{CE} = 2 V I_c = 7 mA

FREQUENCY MHz	S ₁₁		S ₂₁		S ₁₂		S ₂₂	
	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
100.000	0.828	-9.4	15.424	169.5	0.005	82.0	0.969	-5.9
200.000	0.806	-18.5	14.864	160.4	0.011	77.6	0.951	-11.9
300.000	0.765	-27.2	14.467	151.7	0.016	72.4	0.920	-17.2
400.000	0.722	-35.7	13.904	143.2	0.020	67.5	0.892	-22.0
500.000	0.675	-43.3	12.879	135.6	0.024	62.8	0.846	-26.7
600.000	0.625	-50.8	12.259	127.9	0.028	59.6	0.809	-30.5
700.000	0.575	-57.8	11.555	121.5	0.030	56.6	0.772	-33.9
800.000	0.527	-64.6	10.806	115.1	0.033	54.4	0.738	-37.6
900.000	0.481	-70.9	10.151	109.2	0.035	52.6	0.708	-40.2
1 000.000	0.439	-77.0	9.573	104.2	0.037	51.0	0.678	-42.9
1 100.000	0.400	-82.9	8.988	99.2	0.038	50.0	0.650	-45.4
1 200.000	0.364	-89.1	8.510	94.4	0.039	49.3	0.628	-47.9
1 300.000	0.335	-95.3	8.017	90.2	0.041	48.9	0.611	-50.3
1 400.000	0.309	-101.6	7.572	85.8	0.042	48.9	0.589	-52.4
1 500.000	0.284	-108.2	7.203	82.0	0.043	48.7	0.575	-54.8
1 600.000	0.264	-115.1	6.876	78.1	0.044	49.5	0.563	-57.4
1 700.000	0.249	-122.5	6.569	74.1	0.046	49.4	0.553	-59.5
1 800.000	0.239	-129.9	6.225	70.9	0.047	50.1	0.541	-62.4
1 900.000	0.226	-138.1	6.019	67.4	0.048	50.8	0.532	-64.7
2 000.000	0.222	-145.1	5.728	63.8	0.050	50.9	0.525	-68.0
2 100.000	0.220	-154.2	5.541	60.6	0.052	51.9	0.519	-70.5
2 200.000	0.220	-161.9	5.326	57.0	0.054	52.3	0.511	-73.1
2 300.000	0.223	-169.9	5.112	53.7	0.056	52.5	0.511	-76.3
2 400.000	0.230	-176.7	4.951	50.6	0.059	53.1	0.510	-79.8
2 500.000	0.235	176.3	4.761	47.3	0.062	53.1	0.510	-83.1
2 600.000	0.245	169.7	4.602	43.9	0.065	53.0	0.513	-86.4

[MEMO]

[MEMO]

[MEMO]

No part of this document may be copied or reproduced in any form or by any means without the prior written consent of NEC Corporation. NEC Corporation assumes no responsibility for any errors which may appear in this document.

NEC Corporation does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from use of a device described herein or any other liability arising from use of such device. No license, either express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Corporation or others.

While NEC Corporation has been making continuous effort to enhance the reliability of its semiconductor devices, the possibility of defects cannot be eliminated entirely. To minimize risks of damage or injury to persons or property arising from a defect in an NEC semiconductor device, customers must incorporate sufficient safety measures in its design, such as redundancy, fire-containment, and anti-failure features.

NEC devices are classified into the following three quality grades:

"Standard", "Special", and "Specific". The Specific quality grade applies only to devices developed based on a customer designated "quality assurance program" for a specific application. The recommended applications of a device depend on its quality grade, as indicated below. Customers must check the quality grade of each device before using it in a particular application.

Standard: Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots

Special: Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support)

Specific: Aircrafts, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems or medical equipment for life support, etc.

The quality grade of NEC devices is "Standard" unless otherwise specified in NEC's Data Sheets or Data Books. If customers intend to use NEC devices for applications other than those specified for Standard quality grade, they should contact an NEC sales representative in advance.

Anti-radioactive design is not implemented in this product.