



NPN Silicon Germanium RF Transistor

Preliminary data

- High gain low noise RF transistor
- Small package 1.4 x 0.8 x 0.59 mm
- Outstanding noise figure $F = 0.7 \text{ dB}$ at 1.8 GHz
Outstanding noise figure $F = 1.3 \text{ dB}$ at 6 GHz
- Maximum stable gain
 $G_{ms} = 21 \text{ dB}$ at 1.8 GHz
 $G_{ma} = 10 \text{ dB}$ at 6 GHz
- Gold metallization for extra high reliability



ESD: Electrostatic discharge sensitive device, observe handling precaution!

Type	Marking	Pin Configuration						Package
BFP620F E7764	R2s	1=B	2=E	3=C	4=E	-	-	TSFP-4

Maximum Ratings

Parameter	Symbol	Value	Unit
Collector-emitter voltage	V_{CEO}	2.3	V
Collector-emitter voltage	V_{CES}	7.5	
Collector-base voltage	V_{CBO}	7.5	
Emitter-base voltage	V_{EBO}	1.2	
Collector current	I_C	80	mA
Base current	I_B	3	
Total power dissipation ¹⁾ $T_S \leq 96^\circ\text{C}$	P_{tot}	185	mW
Junction temperature	T_j	150	$^\circ\text{C}$
Ambient temperature	T_A	-65 ... 150	
Storage temperature	T_{stg}	-65 ... 150	

Thermal Resistance

Parameter	Symbol	Value	Unit
Junction - soldering point ²⁾	R_{thJS}	≤ 290	K/W

¹ T_S is measured on the collector lead at the soldering point to the pcb

² For calculation of R_{thJA} please refer to Application Note Thermal Resistance

Electrical Characteristics at $T_A = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
DC Characteristics					
Collector-emitter breakdown voltage $I_C = 1 \text{ mA}, I_B = 0$	$V_{(\text{BR})\text{CEO}}$	2.3	2.8	-	V
Collector-emitter cutoff current $V_{CE} = 7.5 \text{ V}, V_{BE} = 0$	I_{CES}	-	-	10	μA
Collector-base cutoff current $V_{CB} = 5 \text{ V}, I_E = 0$	I_{CBO}	-	-	100	nA
Emitter-base cutoff current $V_{EB} = 0.5 \text{ V}, I_C = 0$	I_{EBO}	-	-	3	μA
DC current gain $I_C = 50 \text{ mA}, V_{CE} = 1.5 \text{ V}$	h_{FE}	100	180	320	-

Electrical Characteristics at $T_A = 25^\circ\text{C}$, unless otherwise specified


Parameter	Symbol	Values			Unit
		min.	typ.	max.	
AC Characteristics (verified by random sampling)					
Transition frequency $I_C = 50 \text{ mA}, V_{CE} = 1.5 \text{ V}, f = 1 \text{ GHz}$	f_T	-	65	-	GHz
Collector-base capacitance $V_{CB} = 2 \text{ V}, f = 1 \text{ MHz}$	C_{cb}	-	0.12	0.2	pF
Collector emitter capacitance $V_{CE} = 2 \text{ V}, f = 1 \text{ MHz}$	C_{ce}	-	0.2	-	
Emitter-base capacitance $V_{EB} = 0.5 \text{ V}, f = 1 \text{ MHz}$	C_{eb}	-	0.45	-	
Noise figure $I_C = 5 \text{ mA}, V_{CE} = 1.5 \text{ V}, f = 1.8 \text{ GHz}, Z_S = Z_{Sopt}$ $I_C = 5 \text{ mA}, V_{CE} = 1.5 \text{ V}, f = 6 \text{ GHz}, Z_S = Z_{Sopt}$	F	-	0.7	-	dB
-		-	1.3	-	
Power gain, maximum stable ¹⁾ $I_C = 50 \text{ mA}, V_{CE} = 1.5 \text{ V}, Z_S = Z_{Sopt},$ $Z_L = Z_{Lopt}, f = 1.8 \text{ GHz}$	G_{ms}	-	21	-	dB
Power gain, maximum available ¹⁾ $I_C = 50 \text{ mA}, V_{CE} = 1.5 \text{ V}, Z_S = Z_{Sopt},$ $Z_L = Z_{Lopt}, f = 6 \text{ GHz}$	G_{ma}	-	10	-	dB
Transducer gain $I_C = 50 \text{ mA}, V_{CE} = 1.5 \text{ V}, Z_S = Z_L = 50 \Omega,$ $f = 1.8 \text{ GHz}$ $I_C = 50 \text{ mA}, V_{CE} = 1.5 \text{ V}, Z_S = Z_L = 50 \Omega,$ $f = 6 \text{ GHz}$	$ S_{21e} ^2$	-	19.5	-	dB
-		-	9.5	-	
Third order intercept point at output ²⁾ $V_{CE} = 2 \text{ V}, I_C = 50 \text{ mA}, f = 1.8 \text{ GHz},$ $Z_S = Z_L = 50 \Omega$	IP_3	-	25	-	dBm
1dB Compression point at output $I_C = 50 \text{ mA}, V_{CE} = 2 \text{ V}, Z_S = Z_L = 50 \Omega,$ $f = 1.8 \text{ GHz}$	$P_{-1\text{dB}}$	-	14	-	

¹ $G_{ma} = |S_{21e}| / S_{12e} | (k - (k^2 - 1)^{1/2})$, $G_{ms} = |S_{21e}| / S_{12e} |$
² IP_3 value depends on termination of all intermodulation frequency components.
Termination used for this measurement is 50Ω from 0.1 MHz to 6 GHz

SPICE Parameter (Gummel-Poon Model, Berkley-SPICE 2G.6 Syntax):
Transistor Chip Data:

IS =	0.22	fA	BF =	425	-	NF =	1.025	-
VAF =	1000	V	IKF =	0.25	A	ISE =	21	fA
NE =	2	-	BR =	50	-	NR =	1	-
VAR =	2	V	IKR =	10	mA	ISC =	18	pA
NC =	2	-	RB =	3.129	Ω	IRB =	1.522	mA
RBM =	2.707	Ω	RE =	0.6	-	RC =	2.364	Ω
CJE =	250.7	fF	VJE =	0.75	V	MJE =	0.3	-
TF =	1.43	ps	XTF =	10	-	VTF =	1.5	V
ITF =	2.4	A	PTF =	0	deg	CJC =	124.9	fF
VJC =	0.6	V	MJC =	0.5	-	XCJC =	1	-
TR =	0.2	ns	CJS =	128.1	fF	VJS =	0.52	V
MJS =	0.5	-	NK =	-1.42	-	EG =	1.078	eV
XTI =	3	-	FC =	0.8		TNOM	298	K
AF =	2	-	KF =	7.291E-11				
TITF1	-0.0065	-	TITF2	1.0E-5				

All parameters are ready to use, no scaling is necessary.


Package Equivalent Circuit:


To avoid high complexity of the package equivalent circuit, both emitter leads of TSFP-4 are combined in one electrical connection. R_{LxI} are series resistors for the inductances L_{xI} and K_{xa-yb} are the coupling coefficients between the inductances L_{xa} and L_{yb} .


$L_{B0} =$	0.22	nH
$L_{E0} =$	0.28	nH
$L_{C0} =$	0.22	nH
$K_{B0-E0} =$	0.1	-
$K_{B0-C0} =$	0.01	-
$K_{E0-C0} =$	0.11	-
$C_{BE} =$	34	fF
$C_{BC} =$	2	fF
$C_{CE} =$	33	fF
$L_{BI} =$	0.42	nH
$R_{LBI} =$	0.15	Ω
$L_{EI} =$	0.26	nH
$R_{LEI} =$	0.11	Ω
$L_{CI} =$	0.35	nH
$R_{LI} =$	0.13	Ω
$K_{BI-EI} =$	-0.05	-
$K_{BI-CI} =$	-0.08	-
$K_{EI-CI} =$	0.2	-

Valid up to 6GHz

Total power dissipation $P_{\text{tot}} = f(T_S)$




Permissible Pulse Load $R_{\text{thJS}} = f(t_p)$




Permissible Pulse Load




$$P_{\text{totmax}}/P_{\text{totDC}} = f(t_p)$$



Collector-base capacitance $C_{\text{cb}} = f(V_{\text{CB}})$

$f = 1\text{MHz}$



Transition frequency $f_T = f(I_C)$
 $f = 1\text{GHz}$
 $V_{CE} = \text{Parameter in V}$

Power Gain $G_{ma}, G_{ms} = f(f)$
 $|S_{21}|^2 = f(f)$
 $V_{CE} = 1.5\text{V}, I_C = 50\text{mA}$

Power gain $G_{ma}, G_{ms} = f(I_C)$
 $V_{CE} = 1.5\text{V}$
 $f = \text{Parameter in GHz}$

Power gain $G_{ma}, G_{ms} = f(V_{CE})$
 $I_C = 50\text{mA}$
 $f = \text{Parameter in GHz}$
