

Radiation Hardened Octal Buffer/Line Driver, Three-State

Intersil's Satellite Applications Flow™ (SAF) devices are fully tested and guaranteed to 100kRAD total dose. These QML Class T devices are processed to a standard flow intended to meet the cost and shorter lead-time needs of large volume satellite manufacturers, while maintaining a high level of reliability.

The Intersil HCS244T is a Radiation Hardened Non-Inverting Octal Buffer/Line Driver, Three-State, with two active-low output enables.

Specifications

Specifications for Rad Hard QML devices are controlled by the Defense Supply Center in Columbus (DSCC). The SMD numbers listed below must be used when ordering.

Detailed Electrical Specifications for the HCS244T are contained in SMD 5962-95731. A "hot-link" is provided from our website for downloading.

www.intersil.com/spacedefense/newsafclasst.asp

Intersil's Quality Management Plan (QM Plan), listing all Class T screening operations, is also available on our website.

www.intersil.com/quality/manuals.asp

Ordering Information

| ORDERING INFORMATION | PART NUMBER | TEMP. RANGE (°C) |
|----------------------|-------------|------------------|
| 5962R9573101TRC | HCS244DTR | -55 to 125 |
| 5962R9573101TXC | HCS244KTR | -55 to 125 |


NOTE: **Minimum order quantity for -T is 150 units through distribution, or 450 units direct.**

Features


- QML Class T, Per MIL-PRF-38535
- Radiation Performance
 - Gamma Dose (γ) 1×10^5 RAD(Si)
 - Latch-Up Free Under Any Conditions
 - SEP Effective LET No Upsets: >100 MEV-cm²/mg
 - Single Event Upset (SEU) Immunity $< 2 \times 10^{-9}$ Errors/Bit-Day (Typ)
- 3 Micron Radiation Hardened CMOS SOS
- Fanout (Over Temperature Range)
- Bus Driver Outputs - 15 LSTTL Loads
- Significant Power Reduction Compared to LSTTL ICs
- DC Operating Voltage Range: 4.5V to 5.5V
- Input Logic Levels
 - $V_{IL} = 0.3 V_{CC}$ Max
 - $V_{IH} = 0.7 V_{CC}$ Min
- Input Current Levels $I_i \leq 5\mu A$ at V_{OL}, V_{OH}

Pinouts


HCS244DTR (SBDIP), CDIP2-T20
TOP VIEW



HCS244KTR (FLATPACK), CDFP4-F20
TOP VIEW



Functional Diagram



TRUTH TABLE

| INPUTS | | OUTPUT |
|----------|---|--------|
| 1OE, 2OE | A | Y |
| L | L | L |
| L | H | H |
| H | X | Z |

H = High Voltage Level
 L = Low Voltage Level
 X = Immaterial
 Z = High Impedance

HCS244T

Die Characteristics

DIE DIMENSIONS:

(2747 μ m x 2693 μ m x 533 μ m \pm 51.0 μ m)
108 x 106 x 21mils \pm 2mil

METALLIZATION:

Type: Al Si
Thickness: 11.0k \AA \pm 1k \AA

SUBSTRATE POTENTIAL:

Unbiased Silicon on Sapphire

BACKSIDE FINISH:

Sapphire

PASSIVATION:

Type: Silox (SiO₂)
Thickness: 13.0k \AA \pm 2.6k \AA

WORST CASE CURRENT DENSITY:

< 2.0e5 A/cm²


TRANSISTOR COUNT:

224

PROCESS:

CMOS SOS

Metallization Mask Layout



All Intersil semiconductor products are manufactured, assembled and tested under **ISO9000** quality systems certification.

Intersil semiconductor products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see web site <http://www.intersil.com>

Sales Office Headquarters

NORTH AMERICA

Intersil Corporation
P. O. Box 883, Mail Stop 53-204
Melbourne, FL 32902
TEL: (407) 724-7000
FAX: (407) 724-7240

EUROPE

Intersil SA
Mercure Center
100, Rue de la Fusee
1130 Brussels, Belgium
TEL: (32) 2.724.2111
FAX: (32) 2.724.22.05

ASIA

Intersil (Taiwan) Ltd.
7F-6, No. 101 Fu Hsing North Road
Taipei, Taiwan
Republic of China
TEL: (886) 2 2716 9310
FAX: (886) 2 2715 3029