2×5mm Square Type Standard Type <Viewing Angle 201/2 : 130°>



SLB-25 Series

Emitting Color	Green(Yellowish Green)	Yellow Orange		Red	
Material	GaP		GaAsP on GaP		
Emitting Surface Dimension(mm)					
2×5		9	9	C.	
Part No.	SLB-25MG	SLB-25YY	SLB-25DU	SLB-25VR	

Absolute Maximum Ratings (Ta=25°C)


Part No.	Emitting color	Power dissipation Pp (mW)	Forward current IF (mA)	Peak forward current *IFP (mA)	Reverse voltage VR (V)	Operating temperature T _{opr} (°C)	Storage temperature Tstg (°C)
SLB-25MG	Green (Yellowish Green)	75	25				
SLB-25YY	Yellow			60	3	-25 to +85	-30 to +100
SLB-25DU	Orange	60	20	00	5	-23 10 +03	-30 10 +100
SLB-25VR	Red						

*:Duty ≦1/ 5, pulse width ≦1ms.


Electrical Optical Characteristics (Ta=25°C)

Part No. Resin Color		volt	Forward voltage VF IR		rent	Light wavelength Peak Half-wave λp Δλ			Brightness Iv		
		Тур. (V)	lF (mA)	Мах. (µА)	Vr (V)	Typ. (nm)	Typ. (nm)	lF (mA)	Min. (mcd)	Typ. (mcd)	l⊧ (mA)
SLB-25MG		2.1				563					
SLB-25YY	Diffused	2.1	10	10	3	585	40	10	0.36	1.0	10
SLB-25DU	Colored	2.0		10	3	610	40	10	0.30	1.0	10
SLB-25VR		2.0				650					


Dimensions (Unit:mm)




Directivity (Typ.)



Recommended Pad Layout




■Packaging Specifications (Unit:mm)




Electrical Characteristic Curves

Forward Current - Forward Voltage




Relative Luminous Intensity - Case Temperature






Relative Luminous Intensity - Forward Current




 SLB-25MG
 SLB-25YY
 SLB-25DU
 SLB-25VR

Ratio of Maximum Tolerable Peak Current - Pulse Duration





Derating



Notes

- No technical content pages of this document may be reproduced in any form or transmitted by any means without prior permission of ROHM CO.,LTD.
- The contents described herein are subject to change without notice. The specifications for the product described in this document are for reference only. Upon actual use, therefore, please request that specifications to be separately delivered.
- Application circuit diagrams and circuit constants contained herein are shown as examples of standard use and operation. Please pay careful attention to the peripheral conditions when designing circuits and deciding upon circuit constants in the set.
- Any data, including, but not limited to application circuit diagrams information, described herein are intended only as illustrations of such devices and not as the specifications for such devices. ROHM CO.,LTD. disclaims any warranty that any use of such devices shall be free from infringement of any third party's intellectual property rights or other proprietary rights, and further, assumes no liability of whatsoever nature in the event of any such infringement, or arising from or connected with or related to the use of such devices.
- Upon the sale of any such devices, other than for buyer's right to use such devices itself, resell or
 otherwise dispose of the same, no express or implied right or license to practice or commercially
 exploit any intellectual property rights or other proprietary rights owned or controlled by
- ROHM CO., LTD. is granted to any such buyer.
- Products listed in this document are no antiradiation design.

The products listed in this document are designed to be used with ordinary electronic equipment or devices (such as audio visual equipment, office-automation equipment, communications devices, electrical appliances and electronic toys).

Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

About Export Control Order in Japan

Products described herein are the objects of controlled goods in Annex 1 (Item 16) of Export Trade Control Order in Japan.

In case of export from Japan, please confirm if it applies to "objective" criteria or an "informed" (by MITI clause) on the basis of "catch all controls for Non-Proliferation of Weapons of Mass Destruction.

rohm