

TOSHIBA TRANSISTOR SILICON NPN EPITAXIAL PLANAR TYPE (PCT PROCESS)


# 2SC4539

POWER AMPLIFIER APPLICATIONS

POWER SWITCHING APPLICATIONS

- Low Saturation Voltage :  $V_{CE(sat)} = 0.5V$  (Max.)  
( $I_C = 700mA$ )
- High Speed Switching Time :  $t_{stg} = 0.3\mu s$  (Typ.)
- Small Flat Package
- $P_C = 1\sim 2W$  (Mounted on Ceramic Substrate)
- Complementary to 2SA1734

Unit in mm




Weight : 0.05g

MAXIMUM RATINGS ( $T_a = 25^\circ C$ )

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	$V_{CBO}$	50	V
Collector-Emitter Voltage	$V_{CEO}$	30	V
Emitter-Base Voltage	$V_{EBO}$	6	V
Collector Current	$I_C$	1.2	A
Base Current	$I_B$	0.3	A
Collector Power Dissipation	$P_C$	500	mW
Collector Power Dissipation	$P_C$ (Note)	1000	mW
Junction Temperature	$T_j$	150	$^\circ C$
Storage Temperature Range	$T_{stg}$	-55~150	$^\circ C$

(Note) : Mounted on ceramic substrate (250mm<sup>2</sup>×0.4t)


MARKING



961001EAA1

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current		$I_{CBO}$	$V_{CB} = 50V, I_E = 0$	—	—	0.1	$\mu A$
Emitter Cut-off Current		$I_{EBO}$	$V_{EB} = 6V, I_C = 0$	—	—	0.1	$\mu A$
Collector-Emitter Breakdown Voltage		$V_{(BR)CEO}$	$I_C = 10mA, I_B = 0$	30	—	—	V
DC Current Gain		$h_{FE(1)}$	$V_{CE} = 2V, I_C = 100mA$	120	—	400	
		$h_{FE(2)}$	$V_{CE} = 2V, I_C = 1.0A$	40	—	—	
Collector-Emitter Saturation Voltage		$V_{CE(sat)}$	$I_C = 700mA, I_B = 35mA$	—	—	0.5	V
Base-Emitter Saturation Voltage		$V_{BE(sat)}$	$I_C = 700mA, I_B = 35mA$	—	—	1.2	V
Transition Frequency		$f_T$	$V_{CE} = 2V, I_C = 100mA$	—	100	—	MHz
Collector Output Capacitance		$C_{ob}$	$V_{CB} = 10V, I_E = 0, f = 1MHz$	—	10	—	pF
Switching Time	Turn-on Time	$t_{on}$	 <p><math>I_{B1} = -I_{B2} = 35mA,</math> DUTY CYCLE <math>\leq 1\%</math></p>	—	0.1	—	$\mu s$
	Storage Time	$t_{stg}$		—	0.3	—	
	Fall Time	$t_f$		—	0.1	—	

