


SILICON TRANSISTORS  
**2SC4181, 2SC4181A**

AUDIO FREQUENCY AMPLIFIER, SWITCHING  
NPN SILICON EPITAXIAL TRANSISTORS



**FEATURES**

- High DC Current Gain :  $h_{FE} = 1\ 000$  to  $3\ 200$
- Low  $V_{CE(sat)}$  :  $V_{CE(sat)} = 0.07\ V$  TYP.
- High  $V_{EBO}$  :  $V_{EBO} = 15\ V$  (2SC4181A)

**ABSOLUTE MAXIMUM RATINGS**

Maximum Voltages and Current ( $T_a = 25\ ^\circ C$ )	2SC4181	2SC4181A	
Collector to Base Voltage		60	V
Collector to Emitter Voltage		50	V
Emitter to Base Voltage	12	15	V
Collector Current (DC)		150	mA
Maximum Power Dissipation			
Total Power Dissipation			
at $25\ ^\circ C$ Ambient Temperature		150	mW
Maximum Temperatures			
Junction Temperature		150	$^\circ C$
Storage Temperature Range		-55 to +150	$^\circ C$

**ELECTRICAL CHARACTERISTICS ( $T_a = 25\ ^\circ C$ )**







CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITIONS
Collector Cutoff Current	$I_{CBO}$			100	nA	$V_{CB} = 50\ V, I_E = 0$
Emitter Cutoff Current	$I_{EBO}$			100	nA	$V_{EB} = 10\ V, I_C = 0$
DC Current Gain	$h_{FE1}^*$	1000	1800	3200		$V_{CE} = 5.0\ V, I_C = 1.0\ mA$
DC Current Gain	$h_{FE2}^*$	200	350			$V_{CE} = 5.0\ V, I_C = 100\ mA$
Base to Emitter Voltage	$V_{BE}^*$		0.56		V	$V_{CE} = 5.0\ V, I_C = 1.0\ mA$
Collector Saturation Voltage	$V_{CE(sat)}^*$		0.07	0.3	V	$I_C = 50\ mA, I_B = 5.0\ mA$
Base Saturation Voltage	$V_{BE(sat)}^*$		0.8	1.2	V	$I_C = 50\ mA, I_B = 5.0\ mA$
Gain Bandwidth Product	$f_T$		250		MHz	$V_{CE} = 5.0\ V, I_E = -10\ mA$
Output Capacitance	$C_{ob}$		3.0		pF	$V_{CB} = 5\ V, I_E = 0, f = 1.0\ MHz$
Turn-on Time	$t_{on}$		0.13		ns	$V_{CC} = 10\ V, V_{BE(off)} = -2.7\ V$
Storage Time	$t_{stg}$		0.72		ns	$I_C = 50\ mA$
Turn-off Time	$t_{off}$		1.22		ns	$I_{B1} = -I_{B2} = 1.0\ mA$

\*Pulsed:  $PW \leq 350\ \mu s$ , Duty Cycle  $\leq 2\ %$


**$h_{FE}$  Classification**

Marking	2SC4181	L17	L18
	2SC4181A	L15	L16
$h_{FE1}$	1000 to 2000	1600 to 3200	


TYPICAL CHARACTERISTICS ( $T_a = 25^\circ\text{C}$ )




GAIN BANDWIDTH PRODUCT vs. COLLECTOR CURRENT



OUTPUT CAPACITANCE vs. COLLECTOR TO BASE VOLTAGE



SWITCHING TIME vs. COLLECTOR CURRENT



[MEMO]

No part of this document may be copied or reproduced in any form or by any means without the prior written consent of NEC Corporation. NEC Corporation assumes no responsibility for any errors which may appear in this document.

NEC Corporation does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from use of a device described herein or any other liability arising from use of such device. No license, either express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Corporation or of others.

This datasheet has been download from:

[www.datasheetcatalog.com](http://www.datasheetcatalog.com)

Datasheets for electronics components.