

<b>VI TELEFILTER</b>	<b>Filter specification</b>	<b>TFS 70H14</b>	<b>1/5</b>
----------------------	-----------------------------	------------------	------------

**Measurement condition :**

Ambient temperature  $T_A$ : 25 °C  
 Input power level: 0 dBm  
 Terminating impedances in  $f_C$ :  
     for input: 50  $\Omega$  // 0 pF  
     for output: 50  $\Omega$  // 0 pF

**Characteristics :**

Remark:

Reference level for the relative attenuation  $a_{rel}$  of the **TFS 70H14** is the minimum of the pass band attenuation  $a_{min}$ . The minimum of the pass band attenuation  $a_{min}$  is defined as the insertion loss  $a_e$ . The reference frequency  $f_C$  is the arithmetic mean value of the upper and lower frequencies at the 20 dB filter attenuation level relative to the insertion loss  $a_e$ . The temperature coefficient of frequency  $T_C$  is valid both for the reference frequency  $f_C$  and the frequency response of the filter in the operating temperature range. The frequency shift of the filter in the operating temperature range is not included in the production tolerance scheme.

Data	typ. value	tolerance / limit
<b>Insertion loss (Reference level)</b>	$a_e$	max. 25 dB
<b>Centre frequency at ambient temperature (<math>f_{CTA}</math>)</b>	$f_C$ 70,0 MHz	70,0 $\pm$ 0,1 MHz
<b>Pass band :</b>	<b>PB</b>	$f_C \dots f_C \pm 3,85$ MHz
<b>Amplitude ripple in PB :</b>		max. 0,8 dB
<b>Bandwidth at ambient temperature <math>T_A</math>:</b>	<b>BW</b>	
1 dB - band width		min. 8,0 MHz
3 dB - band width	8,9 MHz	min. 8,5 MHz
40 dB - band width	10,9 MHz	max. 11,1 MHz
<b>Relative attenuation</b>	$a_{rel}$	
$f_C$ ..... $f_C \pm 4,0$ MHz	-	max. 1 dB
$f_C \pm 4,0$ MHz ..... $f_C \pm 4,25$ MHz	-	max. 3 dB
$f_C \pm 5,55$ MHz ..... $f_C \pm 20$ MHz	45 dB	min. 40 dB
<b>Group delay ( mean value in PB ):</b>	1,8 $\mu$ s	max. 2,5 $\mu$ s
<b>Group delay ripple in PB (p-p):</b>	33 ns	max. 100 ns
<b>Deviation from linear phase in PB :</b>	0,6 °	max. 5 °
<b>Temperature coefficient of frequency ( <math>T_C</math> ):</b>	-87 ppm/K <sup>2</sup>	
<b>Frequency deviation of <math>f_C</math> over temperature :</b>	$\Delta f_C(\text{Hz}) = T_C(\text{ppm/K}) \times (T - T_0) \times f_{CTA} (\text{MHz})$	
<b>Operating temperature range</b>		- 25 °C ... + 80 °C
<b>Storage temperature range</b>		- 40 °C ... + 85 °C



generated:checked / approved:

**VI TELEFILTER**  
 Potsdamer Straße 18  
 D 14 513 TELTOW / Germany  
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30  
 E-Mail: [tft@telefilter.com](mailto:tft@telefilter.com)


**Vectron International, Inc.**  
 267 Lowell Road  
 Hudson, NH 03051 / USA  
 Tel: (603) 598-0070 Fax: (603) 598-0075  
 E-Mail: [vti@vtinh.com](mailto:vti@vtinh.com)

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information

Package and pin connection : (All dimensions in mm)




date code: year + week  
 M 2000  
 N 2001  
 P 2002  
 ... ..



Pin 14      **Input**  
 Pin 1      Input RF Return  
 Pin 8      **Output**  
 Pin 7      Output RF Return  
 Pin 2, 9    Package Ground

50  $\Omega$  matching network :



VI TELEFILTER  
 Potsdamer Straße 18  
 D 14 513 TELTOW / Germany  
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30  
 E-Mail: [tft@telefilter.com](mailto:tft@telefilter.com)

Vectron International, Inc.  
 267 Lowell Road  
 Hudson, NH 03051 / USA  
 Tel: (603) 598-0070 Fax: (603) 598-0075  
 E-Mail: [vti@vtinh.com](mailto:vti@vtinh.com)

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information

**Stability characteristics :**

After the following tests the filter shall meet the whole specification:

1. Shock: 500g, 18 ms, half sine wave, 3 shocks each plane;  
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,35 mm or 5g respectively, 1 octave per min, 10 cycles per plan, 3 plans;  
DIN IEC 68 T2 - 6
3. Change of temperature: -55 °C to 125°C / 30 min. each / 10 cycles  
DIN IEC 68 part 2 – 14 Test N
4. Resistance to solder heat (reflow): reflow possible: twice max.;  
for temperature conditions, please refer to the attached "Air reflow temperature conditions" on page 4;

---

**VI TELEFILTER**  
**Potsdamer Straße 18**  
**D 14 513 TELTOW / Germany**  
**Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30**  
**E-Mail: [tft@telefilter.com](mailto:tft@telefilter.com)**

---

**Vectron International, Inc.**  
**267 Lowell Road**  
**Hudson, NH 03051 / USA**  
**Tel: (603) 598-0070 Fax: (603) 598-0075**  
**E-Mail: [vti@vtinh.com](mailto:vti@vtinh.com)**

---

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information

## Air reflow temperature conditions :

## 1st and 2nd air reflow profile

<b>Name:</b>	pre-heating periods	main-heating periods	peak temperature
<b>Temperature:</b>	150 °C - 170 °C	over 200 °C	255 °C ± 5 °C
<b>Time:</b>	60 sec. - 90 sec.	20 sec. - 25 sec.	

## Air reflow profile




Table for temperature vs. time during the air reflow process

Tolerance of temperatures: ± 5 °C

time / sec.	temperature / °C	time / sec.	temperature / °C
0	23	140	160
10	34	150	161
20	46	160	164
30	60	170	170
40	80	180	180
50	103	190	205
60	121	195	230
70	134	200	255
80	143	205	230
90	150	210	205
100	154	215	180
110	156	220	165
120	158	230	140
130	159	240	120

VI TELEFILTER  
 Potsdamer Straße 18  
 D 14 513 TELTOW / Germany  
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30  
 E-Mail: [tft@telefilter.com](mailto:tft@telefilter.com)

Vectron International, Inc.  
 267 Lowell Road  
 Hudson, NH 03051 / USA  
 Tel: (603) 598-0070 Fax: (603) 598-0075  
 E-Mail: [vti@vtinh.com](mailto:vti@vtinh.com)

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information

**VI TELEFILTER****Filter specification****TFS 70H14****5/5****History**

<b>Version</b>	<b>Reason of changes</b>	<b>Name</b>	<b>Date</b>
1.0	Generate preliminary specification .	Dunzow W.	23.11.2001
1.1.	typical values added	Pfeiffer	16.04.2002

**VI TELEFILTER**  
**Potsdamer Straße 18**  
**D 14 513 TELTOW / Germany**  
**Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30**  
**E-Mail: [tft@telefilter.com](mailto:tft@telefilter.com)**

**Vectron International, Inc.**  
**267 Lowell Road**  
**Hudson, NH 03051 / USA**  
**Tel: (603) 598-0070 Fax: (603) 598-0075**  
**E-Mail: [vti@vtinh.com](mailto:vti@vtinh.com)**

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information