

FEATURES

- Complete Switch Mode Power Supply
- Wide Input Voltage Range: 4.5V to 60V (7.5V Minimum Voltage to Start)
- Wide Output Voltage Range: 2.5V to 24V (See Table 2)
- 4A Output Current
- Programmable Soft-Start
- 10 μ A Shutdown Supply Current
- Selectable Switching Frequency Current Mode Control
- Up to 95% Efficiency
- Pb-Free (e4) RoHS Compliant Package with Gold Pad Finish
- Tiny, Low Profile (15mm \times 15mm \times 4.32mm) Surface Mount LGA Package

APPLICATIONS

- 12V and 42V Automotive and Heavy Equipment
- 48V Telecom Power Supplies
- Avionics and Industrial Control Systems
- Distributed Power Converters

DESCRIPTION

The LTM[®]8027 is a complete 4A, DC/DC step-down power supply. Included in the package are the switching controller, power switches, inductor and all support components. Operating over an input voltage range of 4.5V to 60V (7.5V minimum voltage to start), the LTM8027 supports output voltages up to 24V, and a switching frequency range of 100kHz to 500kHz, each set by a single resistor. Only the bulk input and output filter capacitors are needed to finish the design.


The low profile package (4.32mm) enables utilization of unused space on the bottom of PC boards for high density point of load regulation. A built-in soft-start timer is adjustable with a small capacitor.

The LTM8027 is packaged in a thermally enhanced, compact (15mm \times 15mm) and low profile (4.32mm) over-molded land grid array (LGA) package suitable for automated assembly by standard surface mount equipment. The LTM8027 is Pb-free and RoHS compliant.


LT, LT, LTC, LTM, μ Module, Linear Technology and the Linear logo are registered trademarks of Linear Technology Corporation. All other trademarks are the property of their respective owners.

TYPICAL APPLICATION

48W, 16V_{IN} to 60V_{IN} DC/DC μ Module[®] Regulator



Efficiency vs Load



8027 TA01b


LTM8027

ABSOLUTE MAXIMUM RATINGS

(Note 1)

| | |
|---|----------------|
| V_{IN} Voltage..... | 65V |
| BIAS1, BIAS2 | 15V |
| SYNC, ADJ, R_T , RUN, SS Voltages..... | 5V |
| Current Into RUN Pin (Note 2) | 1mA |
| V_{OUT} , AUX | 25V |
| Current Out of AUX | 200mA |
| Internal Operating Temperature (Note 3)..... | -40°C to 125°C |
| Maximum Soldering Temperature..... | 245°C |
| Storage Temperature Range | -55°C to 125°C |

PIN CONFIGURATION



ORDER INFORMATION

| LEAD FREE FINISH | TRAY | PART MARKING | PACKAGE DESCRIPTION | INTERNAL TEMPERATURE RANGE |
|------------------|----------------|--------------|-------------------------------------|----------------------------|
| LTM8027EV#PBF | LTM8027EV#PBF | LTM8027V | 113-Lead (15mm × 15mm × 4.32mm) LGA | -40°C to 125°C |
| LTM8027IV#PBF | LTM8027IV#PBF | LTM8027V | 113-Lead (15mm × 15mm × 4.32mm) LGA | -40°C to 125°C |
| LTM8027MPV#PBF | LTM8027MPV#PBF | LTM8027V | 113-Lead (15mm × 15mm × 4.32mm) LGA | -55°C to 125°C |

Consult LTC Marketing for parts specified with wider operating temperature ranges.

Consult LTC Marketing for information on non-standard lead based finish parts.

For more information on lead free part marking, go to: <http://www.linear.com/leadfree/>

This product is only offered in trays. For more information go to: <http://linear.com/packaging/>

ELECTRICAL CHARACTERISTICS

The ● denotes the specifications which apply over the full operating temperature range, otherwise specifications are at $T_A = 25^{\circ}\text{C}$. $V_{IN} = 20\text{V}$, BIAS1 = BIAS2 = 10V, RUN = 2V, unless otherwise noted.

| SYMBOL | PARAMETER | CONDITIONS | MIN | TYP | MAX | UNITS |
|----------------------------------|--|--|-----|-----|-----|-------|
| V_{IN} | Input DC Voltage | (Note 5) ● | 4.5 | | 60 | V |
| V_{OUT} | Maximum Output DC Voltage | $0 < I_{OUT} \leq 4\text{A}$, $V_{IN} = 48\text{V}$ | | 24 | | V |
| I_{OUT} | Output DC Current | $V_{IN} \leq 60\text{V}$, $V_{OUT} = 12\text{V}$, (Note 4) | 0 | | 4 | A |
| $V_{IN(START)}$ | Minimum Start Voltage | | | | 7.5 | V |
| $\Delta V_{OUT}/\Delta V_{IN}$ | Line Regulation | $V_{OUT} = 12\text{V}$, $15\text{V} < V_{IN} < 60\text{V}$, $I_{LOAD} = 4\text{A}$ | | 0.2 | | % |
| $\Delta V_{OUT}/\Delta I_{LOAD}$ | Load Regulation | $V_{OUT} = 12\text{V}$, $V_{IN} = 24\text{V}$, $0\text{A} < I_{LOAD} \leq 4\text{A}$ | | 0.2 | | % |
| $V_{UVLO(RISING)}$ | Input Undervoltage Lockout Threshold (Rising) | (Note 5) | | 4.6 | | V |
| $V_{UVLO(FALLING)}$ | Input Undervoltage Lockout Threshold (Falling) | (Note 5) | | 3.7 | | V |

8027f

ELECTRICAL CHARACTERISTICS

The ● denotes the specifications which apply over the full operating temperature range, otherwise specifications are at $T_A = 25^\circ\text{C}$. $V_{IN} = 20\text{V}$, $\text{BIAS1} = \text{BIAS2} = 10\text{V}$, $\text{RUN} = 2\text{V}$, unless otherwise noted.

| SYMBOL | PARAMETER | CONDITIONS | MIN | TYP | MAX | UNITS |
|---------------------------|---|--|----------------|------------|----------------|---------------------|
| V_{ADJ} | ADJ Voltage | ● | 1.224 1.215 | | 1.238 1.245 | V V |
| $I_{Q_{\text{VIN}}}$ | Quiescent Current into IN | $V_{\text{BIAS}} = V_{\text{AUX}}$, $V_{\text{OUT}} = 12\text{VDC}$, No Load $V_{\text{RUN}} = 0\text{V}$ | | 39 9 | | mA μA |
| V_{BIAS1} | BIAS1 Undervoltage Lockout (Rising) BIAS1 Undervoltage Lockout (Falling) | | | 6.5 6 | | V V |
| I_{BIAS1} | Current into BIAS1 | No Load $\text{RUN} = 0\text{V}$ | | 25 25 | | mA μA |
| V_{BIAS2} | Minimum BIAS2 Voltage | | | 6 | | V |
| I_{BIAS2} | Current Into BIAS2 | | | 1 | | μA |
| $V_{\text{BIAS(MINOV)}}$ | Minimum Voltage to Overdrive INTV _{CC} Regulator | | | 8.5 | | V |
| R_{FB} | Internal Feedback Resistor | | | 499 | | k Ω |
| $V_{\text{RUN(RISING)}}$ | RUN Enable Voltage (Rising) | | | 1.4 | | V |
| $V_{\text{RUN(FALLING)}}$ | RUN Enable Voltage (Falling) | | | 1.2 | | V |
| f_{SW} | Switching Frequency | $R_T = 187\text{k}\Omega$ $R_T = 23.7\text{k}\Omega$ | | 100 500 | | kHz kHz |
| R_{SYNC} | SYNC Input Resistance | | | 40 | | k Ω |
| $V_{\text{SYNC(TH)}}$ | SYNC Voltage Threshold | $f_{\text{SYNC}} = 350\text{kHz}$ | ● | 2.3 | | V |
| I_{SS} | Soft-Start Charging Current | | | 2 | | μA |

Note 1: Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. Exposure to any Absolute Maximum Rating condition for extended periods may affect device reliability and lifetime.

Note 2: The RUN pin is internally clamped to 5V


Note 3: The LTM8027E is guaranteed to meet performance specifications from 0°C to 125°C internal operating temperature. Specifications over the full -40°C to 125°C internal operating temperature range are assured by design, characterization and correlation with statistical process controls. The LTM8027I is guaranteed to meet specifications over the full

-40°C to 125°C internal operating temperature range. The LTM8027MP is guaranteed to meet specifications over the full -55°C to 125°C internal operating range. Note that the maximum internal temperature is determined by specific operating conditions in conjunction with board layout, the rated package thermal resistance and other environmental factors.

Note 4: The maximum continuous output current may be derated by the LTM8027 junction temperature.


Note 5: V_{IN} voltages below the start-up threshold (7.5V) are only supported when the V_{CC} is externally driven above 6.5V.

TYPICAL PERFORMANCE CHARACTERISTICS (T_A = 25°C unless otherwise noted)




TYPICAL PERFORMANCE CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Input Current vs Load,
 $V_{OUT} = 2.5V$




8027 G43

Input Current vs Load,
 $V_{OUT} = 3.3V$




8027 G10

Input Current vs Load,
 $V_{OUT} = 5V$




8027 G11

Input Current vs Load,
 $V_{OUT} = 8V$




8027 G12

Input Current vs Load,
 $V_{OUT} = 12V$




8027 G13

Input Current vs Load,
 $V_{OUT} = 15V$




8027 G14

Input Current vs Load,
 $V_{OUT} = 18V$




8027 G15

Input Current vs Load,
 $V_{OUT} = 24V$



8027 G16


Bias Current vs Load,
 $V_{OUT} = 2.5V$



8027 G17


TYPICAL PERFORMANCE CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

**Bias Current vs Load,
 $V_{OUT} = 3.3\text{V}$**




8027 G18

**Bias Current vs Load,
 $V_{OUT} = 5\text{V}$**




8027 G19

**Bias Current vs Load,
 $V_{OUT} = 8\text{V}$**




8027 G20

**Bias Current vs Load,
 $V_{OUT} = 12\text{V}$**




8027 G21

**Bias Current vs Load,
 $V_{OUT} = 15\text{V}$**




8027 G22

**Bias Current vs Load,
 $V_{OUT} = 18\text{V}$**




8027 G23

**Bias Current vs Load,
 $V_{OUT} = 24\text{V}$**




8027 G44

**Minimum V_{IN} vs Load,
 $V_{OUT} = 5\text{V}$**



8027 G25


**Minimum V_{IN} vs Load,
 $V_{OUT} = 8\text{V}$**



8027 G26


TYPICAL PERFORMANCE CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Minimum V_{IN} vs Load,
 $V_{OUT} = 12\text{V}$




8027 G27

Minimum V_{IN} vs Load,
 $V_{OUT} = 15\text{V}$




8027 G28

Minimum V_{IN} vs Load,
 $V_{OUT} = 18\text{V}$




8027 G29

Minimum V_{IN} vs Load,
 $V_{OUT} = 24\text{V}$




8027 G30

Minimum V_{IN} vs V_{OUT} ,
 $I_{OUT} = 4\text{A}$




8027 G31

Minimum V_{IN} vs Load,
 $V_{OUT} = -3.3\text{V}$




8027 G45

Minimum V_{IN} vs Load,
 $V_{OUT} = -5\text{V}$




8027 G32

Minimum V_{IN} vs Load,
 $V_{OUT} = -8\text{V}$



8027 G33

Minimum V_{IN} vs Load,
 $V_{OUT} = -12\text{V}$




8027 G34

8027f


TYPICAL PERFORMANCE CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Temperature Rise vs Load,
 $V_{OUT} = 2.5V$




8027 G35

Temperature Rise vs Load,
 $V_{OUT} = 3.3V$




8027 G36

Temperature Rise vs Load,
 $V_{OUT} = 5V$




8027 G37

Temperature Rise vs Load,
 $V_{OUT} = 8V$




8027 G38

Temperature Rise vs Load,
 $V_{OUT} = 12V$




8027 G39

Temperature Rise vs Load,
 $V_{OUT} = 15V$




8027 G40

Temperature Rise vs Load,
 $V_{OUT} = 18V$



8027 G41

Temperature Rise vs Load,
 $V_{OUT} = 24V$



8027 G42

PIN FUNCTIONS

V_{IN} (Bank 3): The V_{IN} pin supplies current to the LTM8027's internal regulator and to the internal power switch. This pin must be locally bypassed with an external, low ESR capacitor (see Table 2).

V_{OUT} (Bank 1): Power Output Pins. Apply the output filter capacitor and the output load between these and the GND pins.

AUX (Pin A7): Low Current Voltage Source for BIAS1 and BIAS2. In many designs, the BIAS pins are simply connected to V_{OUT}. The AUX pin is internally connected to V_{OUT} and is placed near the BIAS pins to ease printed circuit board routing. Although this pin is internally connected to V_{OUT}, do NOT connect this pin to the load. If this pin is not tied to BIAS1 and BIAS2, leave it floating.

BIAS1 (Pin A6): The BIAS1 pin connects to the internal power bus. Connect to a power source greater than 8.5V. If the output is greater than 8.5V, connect it to this pin. If the output voltage is less, connect this to a voltage source between 8.5V and 15V. For proper operation, connect this pin to the same power source as BIAS2.

BIAS2 (Pin A3): Internal Biasing Power. This pin must be connected to the same power source as BIAS1 for proper operation. Always connect this pin to a voltage source above 8.5V. Do not leave BIAS2 floating.

RUN (Pin A4): Tie the RUN pin to ground to shut down the LTM8027. Tie to 1.4V or more for normal operation. The RUN pin is internally clamped to 5V, so when it is pulled up, be sure to use a pull-up resistor that limits the current in to the RUN pin to less than 1mA. If the shutdown feature is not used, tie this pin to the V_{IN} pin through a pull-up resistor.

GND (Bank 2): Tie these GND pins to a local ground plane below the LTM8027 and the circuit components.

RT (Pin B1): The RT pin is used to program the switching frequency of the LTM8027 by connecting a resistor from this pin to ground. The Applications Information section of the data sheet includes a table to determine the resistance value based on the desired switching frequency. Minimize capacitance at this pin.

SYNC (Pin C1): The SYNC pin provides an external clock input for synchronization of the internal oscillator. The R_T resistor should be set such that the internal oscillator frequency is 10% to 25% below the external clock frequency. If unused, the SYNC pin is connected to GND. For more information see Oscillator Sync in the Application Information section of this data sheet.

ADJ (Pin A2): The LTM8027 regulates its ADJ pin to 1.23V. Connect the adjust resistor from this pin to ground. The value of R_{ADJ} is given by the equation:

$$R_{ADJ} = 613.77 / (V_{OUT} - 1.23)$$


where R_{ADJ} is in kΩ.

SS (Pin A5): The soft-start pin is used to program the supply soft-start function. Use the following formula to calculate C_{SS} for a given output voltage slew rate:

$$C_{SS} = 2\mu A(t_{SS} / 1.231V)$$

The pin should be left unconnected when not using the soft-start function.

BLOCK DIAGRAM



OPERATION

The LTM8027 is a standalone nonisolated step-down switching DC/DC power supply with an input voltage range of 4.5V to 60V that can deliver up to 4A of output current. This module provides a precisely regulated output voltage up to 24V, programmable via one external resistor. Given that the LTM8027 is a step-down converter, make sure that the input voltage is high enough to support the desired output voltage and load current. A simplified block diagram is given above. The LTM8027 contains a current mode controller, power switching element, power inductor, power MOSFETs and a modest amount of input and output capacitance.

The LTM8027 is a fixed frequency PWM regulator. The switching frequency is set by simply connecting the appropriate resistor from the RT pin to GND.

A linear regulator provides internal power (shown as INTV_{CC} on the Block Diagram) to the control circuitry. The bias regulator normally draws power from the V_{IN} pin, but if the BIAS1 and BIAS2 pins are connected to an external voltage higher than 8.5V, bias power will be drawn from the external source (typically the regulated output voltage). This improves efficiency. The RUN pin is used to enable or place the LTM8027 in shutdown, disconnecting the output and reducing the input current to less than 10µA.

APPLICATIONS INFORMATION

For most applications, the design process is straight forward, summarized as follows:

1. Look at Table 2 and find the row that has the desired input range and output voltage.
2. Apply the recommended C_{IN} , C_{OUT} , R_{ADJ} and R_T values.
3. Connect the BIAS pins as indicated.

While these component and connection combinations have been tested for proper operation, it is incumbent upon the user to verify proper operation over the intended system's line, load and environmental conditions.

Capacitor Selection Considerations

The C_{IN} and C_{OUT} capacitor values in Table 2 are the minimum recommended values for the associated operating conditions. Applying capacitor values below those indicated in Table 2 is not recommended, and may result in undesirable operation. Using larger values is generally acceptable, and can yield improved dynamic response, if it is necessary. Again, it is incumbent upon the user to verify proper operation over the intended system's line, load and environmental conditions.

Ceramic capacitors are small, robust and have very low ESR. However, not all ceramic capacitors are suitable. X5R and X7R types are stable over temperature and applied voltage and give dependable service. Other types, including Y5V and Z5U have very large temperature and voltage coefficients of capacitance. In an application circuit they may have only a small fraction of their nominal capacitance resulting in much higher output voltage ripple than expected.

Ceramic capacitors are also piezoelectric. The LTM8027's switching frequency depends on the load current, and at light loads it can excite a ceramic capacitor at audio frequencies, generating audible noise.

A final precaution regarding ceramic capacitors concerns the maximum input voltage rating of the LTM8027. A ceramic input capacitor combined with trace or cable

inductance forms a high Q (under damped) tank circuit. If the LTM8027 circuit is plugged into a live supply, the input voltage can ring to twice its nominal value, possibly exceeding the device's rating. This situation is easily avoided; see the Hot-Plugging Safely section.

Input Power Requirements

The LTM8027 is biased using an internal linear regulator to generate operational voltages from the V_{IN} pin. Virtually all of the circuitry in the LTM8027 is biased via this internal linear regulator output (INTV_{CC}). This pin is internally decoupled with a low ESR capacitor to GND. The V_{CC} regulator generates an 8V output provided there is ample voltage on the V_{IN} pin. The V_{CC} regulator has approximately 1V of dropout, and will follow the V_{IN} pin with voltages below the dropout threshold.

The LTM8027 has a typical start-up requirement of $V_{IN} > 7.5V$. This assures that the onboard regulator has ample headroom to bring INTV_{CC} above its UVLO threshold. The INTV_{CC} regulator can only source current, so forcing the BIAS pin above 8.5V allows use of externally derived power for the IC. This effectively shuts down the internal linear regulator and reduces power dissipation within the LTM8027. Using the onboard regulator for start-up, then deriving power for V_{CC} from the converter output maximizes conversion efficiencies and is common practice. If V_{CC} is maintained above 6.5V using an external source, the LTM8027 can continue to operate with V_{IN} as low as 4V.

BIAS Power

The internal circuitry of the LTM8027 is powered by the INTV_{CC} bus, which is derived either from the aforementioned internal linear regulator or the BIAS1 and BIAS2 pins, if it is greater than 8.5V. Since the internal linear regulator is by nature dissipative, deriving INTV_{CC} from an external source through the BIAS pins reduces the power lost within the LTM8027 and can increase overall system efficiency.

APPLICATIONS INFORMATION

For example, suppose the LTM8027 needs to provide 5V from an input voltage source that is nominally 12V. From Table 2, the recommended R_T value is 162k, which corresponds to an operating frequency of 210kHz. From the graphs in the Typical Performance Characteristics, the typical $INTV_{CC}$ current at $12V_{IN}$ and 210kHz is 15mA. The power dissipated by the internal linear regulator at $12V_{IN}$ is given by the equation:

$$P_{INTV_{CC}} = (V_{IN} - 8.5) \cdot I_{INTV_{CC}}$$

or only 54mW. This has a small but probably acceptable effect on the operating temperature of the LTM8027.

If the input rises to 60V, however, the power dissipation is a lot higher, over 750mW. This can cause unnecessarily high junction temperatures if the $INTV_{CC}$ regulator must dissipate this amount of power for very long.

Soft-Start

The soft-start function controls the slew rate of the power supply output voltage during start-up. A controlled output voltage ramp minimizes output voltage overshoot, reduces inrush current from the V_{IN} supply, and facilitates supply sequencing. A capacitor connected from the SS pin to GND programs the slew rate. The capacitor is charged from an internal 2μA current source producing a ramped voltage that overrides the command reference to the controller, resulting in a smooth output voltage ramp. The soft-start circuit is disabled once the SS pin voltage has been charged to 200mV above the internal reference of 1.231V.

During a V_{IN} UVLO, $INTV_{CC}$ undervoltage or RUN event, the SS pin voltage is discharged with a 50μA. Therefore, the value of the SS capacitor determines how long one of these events must be in order to completely discharge the soft-start capacitor. In the case of an output overload or short circuit, the SS pin voltage is clamped to a diode drop above the ADJ pin. Once the short has been removed the V_{ADJ} pin voltage starts to recover. The soft-start circuit takes control of the output voltage slew rate once the V_{ADJ} pin voltage has exceeded the slowly ramping SS pin voltage, reducing the output voltage overshoot during a short-circuit recovery.

Operating Frequency Tradeoffs

The LTM8027 uses a constant frequency architecture that can be programmed over a 100kHz to 500kHz range with a single resistor from the R_T pin to ground. The nominal voltage on the R_T pin is 1V and the current that flows from this pin is used to charge an internal oscillator capacitor. The value of R_T for a given operating frequency can be chosen from Figure 1 or Table 1.




Figure 1. Timing Resistor (R_T) Value

Table 1 lists typical resistor values for common operating frequencies.

Table 1. R_T Resistor Values vs Frequency

| R_T (kΩ) | f_{sw} (kHz) |
|------------|----------------|
| 187 | 100 |
| 118 | 150 |
| 82.5 | 200 |
| 63.4k | 250 |
| 48.7k | 300 |
| 40.2k | 350 |
| 31.6k | 400 |
| 27.4k | 450 |
| 23.7k | 500 |

APPLICATIONS INFORMATION

It is recommended that the user apply the R_T value given in Table 2 for the input and output operating condition. System level or other considerations, however, may necessitate another operating frequency. While the LTM8027 is flexible enough to accommodate a wide range of operating frequencies, a haphazardly chosen one may result in undesirable operation under certain operating or fault conditions. A frequency that is too high can damage the LTM8027 if the output is overloaded or short circuited. A frequency that is too low can result in a final design that has too much output ripple or too large of an output capacitor.

The maximum frequency (f_{MAX}) at which the LTM8027 should be allowed to switch and the minimum frequency set resistor value that should be used for a given set of input and output operating condition is given in Table 2 as $R_{T(MIN)}$. There are additional conditions that must be satisfied if the synchronization function is used. Please refer to the Synchronization section for details.

Output Voltage Programming

The LTM8027 regulates its ADJ pin to 1.23V. Connect the adjust resistor from this pin to ground. The value of R_{ADJ} is given by the equation $R_{ADJ} = 613.77/(V_{OUT} - 1.23)$, where R_{ADJ} is in $k\Omega$.

RUN Control

The LTM8027 RUN pin uses a reference threshold of 1.4V. This precision threshold allows use of the RUN pin for both logic-level controlled applications and analog monitoring applications such as power supply sequencing. The LTM8027 operational status is primarily controlled by a UVLO circuit on internal power source. When the LTM8027 is enabled via the RUN pin, only the V_{CC} regulator is enabled. Switching remains disabled until the UVLO threshold is achieved at the V_{CC} pin, when the remainder of the LTM8027 is enabled and switching commences.

Because the LTM8027 high power converter is a power transfer device, a voltage that is lower than expected on the input supply could require currents that exceed the sourcing capabilities of that supply, causing the system to lock up in an undervoltage state. Input supply start-up protection can be achieved by enabling the RUN pin using a resistive divider from the V_{IN} supply to ground. Setting the divider output to 1.4V when that supply is at an adequate voltage prevents an LTM8027 converter from drawing large currents until the input supply is able to provide the required power. 200mV of input hysteresis on the RUN pin allows for about 15% of input supply droop before disabling the converter.

Input UVLO and RUN

The RUN pin has a precision voltage threshold with hysteresis which can be used as an undervoltage lockout threshold (UVLO) for the power supply. Undervoltage lockout keeps the LTM8027 in shutdown until the supply input voltage is above a certain voltage programmed by the user. The hysteresis voltage prevents noise from falsely tripping UVLO. Resistors are chosen by first selecting R_B (refer to Figure 2). Then:

$$R_A = R_B \cdot \left(\frac{V_{IN(ON)}}{1.4V} - 1 \right)$$

where $V_{IN(ON)}$ is the input voltage at which the undervoltage lockout is disabled and the supply turns on.




Figure 2. Undervoltage Lockout Resistive Divider

APPLICATIONS INFORMATION

Example: Select $R_B = 49.9k$, $V_{IN(ON)} = 14.5V$ (based upon a 15V minimum input voltage)

$$R_A = 49.9k \cdot \left(\frac{14.5V}{1.4V} - 1 \right) = 464k$$

The V_{IN} turn off voltage is 15% below turn on. In the example the $V_{IN(OFF)}$ would be 12.3V. The shutdown function can be disabled by connecting the RUN pin to the V_{IN} pin through a large value pull-up resistor. This pin contains a low impedance clamp at 6V, so the RUN pin will sink current from the pull-up resistor (R_{PU}):

$$I_{RUN} = \frac{V_{IN} - 6V}{R_{PU}}$$

Because this arrangement will clamp the RUN pin to 6V, it will violate the 5V absolute maximum voltage rating of the pin. This is permitted, however, as long as the absolute maximum input current rating of 1mA is not exceeded. Input RUN pin currents of $<100\mu A$ are recommended: a 1M or greater pull-up resistor is typically used for this configuration.

Soft-Start

The desired soft-start time (t_{SS}) is programmed via the C_{SS} capacitor as follows:

$$C_{SS} = \frac{2\mu A \cdot t_{SS}}{1.231V}$$

The amount of time in which the power supply must be under a V_{IN} , V_{CC} or V_{SHDN} UVLO fault condition (t_{FAULT}) before the SS pin voltage enters its active region is approximated by the following formula:

$$t_{FAULT} = \frac{C_{SS} \cdot 0.65V}{50\mu A}$$

Hot-Plugging Safely

The small size, robustness and low impedance of ceramic capacitors make them an attractive option for the input bypass capacitor of LTM8027. However, these capacitors can cause problems if the LTM8027 is plugged into a live supply (see Linear Technology Application Note 88 for a complete discussion). The low loss ceramic capacitor combined with stray inductance in series with the power source forms an under damped tank circuit, and the voltage at the V_{IN} pin of the LTM8027 can ring to twice the nominal input voltage, possibly exceeding the LTM8027's rating and damaging the part. If the input supply is poorly controlled or the user will be plugging the LTM8027 into an energized supply, the input network should be designed to prevent this overshoot by introducing a damping element into the path of current flow. This is often done by adding an inexpensive electrolytic bulk capacitor across the input terminals of the LTM8027. The criteria for selecting this capacitor is that the ESR is high enough to damp the ringing, and the capacitance value is several times larger than the LTM8027 ceramic input capacitor. The bulk capacitor does not need to be located physically close to the LTM8027; it should be located close to the application board's input connector, instead.

Synchronization

The oscillator can be synchronized to an external clock. Choose the R_T resistor such that the resultant frequency is at least 10% below the desired synchronization frequency. It is recommended that the SYNC pin be driven with a square wave that has amplitude greater than 2.3V, pulse width greater than $1\mu s$ and rise time less than 500ns. The rising edge of the sync wave form triggers the discharge of the internal oscillator capacitor.

APPLICATIONS INFORMATION

PCB Layout

Most of the headaches associated with PCB layout have been alleviated or even eliminated by the high level of integration of the LTM8027. The LTM8027 is nevertheless a switching power supply, and care must be taken to minimize EMI and ensure proper operation. Even with the high level of integration, you may fail to achieve specified operation with a haphazard or poor layout. See Figure 3 for a suggested layout.

Ensure that the grounding and heatsinking are acceptable. A few rules to keep in mind are:

1. Place the R_{ADJ} and R_T resistors as close as possible to their respective pins.
2. Place the C_{IN} capacitor as close as possible to the V_{IN} and GND connection of the LTM8027.
3. Place the C_{OUT} capacitor as close as possible to the V_{OUT} and GND connection of the LTM8027.
4. Place the C_{IN} and C_{OUT} capacitors such that their ground current flow directly adjacent to or underneath the LTM8027.
5. Connect all of the GND connections to as large a copper pour or plane area as possible on the top layer. Avoid breaking the ground connection between the external components and the LTM8027.

Use vias to connect the GND copper area to the board's internal ground planes. Liberally distribute these GND vias to provide both a good ground connection and thermal path to the internal planes of the printed circuit board. Pay attention to the location and density of the thermal vias in Figure 3. The LTM8027 can benefit from the heat sinking afforded by vias that connect to internal GND planes at these locations, due to their proximity to internal power handling components. The optimum number of thermal vias depends upon the printed circuit board design. For example, a board might use very small via holes. It should employ more thermal vias than a board that uses larger holes.

Thermal Considerations

The LTM8027 output current may need to be derated if it is required to operate in a high ambient temperature or deliver a large amount of continuous power. The amount of current derating is dependent upon the input voltage, output power and ambient temperature. The temperature rise curves given in the Typical Performance Characteristics section can be used as a guide. These curves were generated by a LTM8027 mounted to a 58cm² 4-layer FR4 printed circuit board. Boards of other sizes and layer count can exhibit different thermal behavior, so it is incumbent upon the user to verify proper operation over the intended system's line, load and environmental operating conditions.




Figure 3. Suggested Layout

APPLICATIONS INFORMATION

The junction-to-air and junction-to-board thermal resistances given in the Pin Configuration diagram may also be used to estimate the LTM8027 internal temperature. These thermal coefficients are determined per JESD 51-9 (JEDEC standard, test boards for area array surface mount package thermal measurements) through analysis and physical correlation. Bear in mind that the actual thermal resistance of the LTM8027 to the printed circuit board depends upon the design of the circuit board.


The die temperature of the LTM8027 must be lower than the maximum rating of 125°C, so care should be taken in the layout of the circuit to ensure good heat sinking of the LTM8027. The bulk of the heat flow out of the LTM8027 is through the bottom of the module and the LGA pads into the printed circuit board. Consequently a poor printed circuit board design can cause excessive heating, resulting in impaired performance or reliability. Please refer to the PCB Layout section for printed circuit board design suggestions.

Table 2. Recommended Component Values and Configuration
(T_A = 25°C. See Typical Performance Characteristics for load Conditions)


| V _{IN} RANGE (V) | V _{OUT} (V) | C _{IN} | C _{OUT} | BIAS1/BIAS2 | R _{ADJ} (kΩ) | f _{OPTIMAL} (kHz) | R _{OPTIMAL} (kΩ) | f _{MAX} (kHz) | R _{MAX} (kΩ) |
|---------------------------|----------------------|---------------------|---------------------|--------------------------|-----------------------|----------------------------|---------------------------|------------------------|-----------------------|
| 4.5 to 60 | 3.3 | 2 × 4.7μF 2220 100V | 5 × 100μF 1812 6.3V | 8.5V to 15V | 301 | 115 | 154 | 160 | 107 |
| 7.5 to 60 | 5 | 2 × 4.7μF 2220 100V | 4 × 100μF 1210 6.3V | 8.5V to 15V | 162 | 210 | 75.0 | 230 | 68.2 |
| 10.5 to 60 | 8 | 2 × 4.7μF 2220 100V | 4 × 47μF 1210 10V | 8.5V to 15V | 90.9 | 260 | 59.0 | 350 | 40.2 |
| 16 to 60 | 12 | 2 × 4.7μF 2220 100V | 4 × 22μF 1210 16V | AUX | 56.2 | 300 | 48.7 | 500 | 23.7 |
| 20.5 to 60 | 15 | 2 × 4.7μF 2220 100V | 4 × 22μF 1210 16V | AUX | 44.2 | 350 | 40.2 | 500 | 23.7 |
| 26 to 60 | 18 | 2 × 4.7μF 2220 100V | 4 × 10μF 1812 25V | 8.5V to 15V | 36.5 | 400 | 31.6 | 500 | 23.7 |
| 34 to 60 | 24 | 2 × 4.7μF 2220 100V | 4 × 10μF 1812 25V | 8.5V to 15V | 26.7 | 430 | 28.7 | 500 | 23.7 |
| 4.5 to 40 | 2.5 | 2 × 10μF 2220 50V | 5 × 100μF 1812 6.3V | 8.5V to 15V | 487 | 145 | 124 | 185 | 88.7 |
| 4.5 to 40 | 3.3 | 2 × 10μF 2220 50V | 4 × 100μF 1812 6.3V | 8.5V to 15V | 301 | 165 | 102 | 240 | 64.9 |
| 7.5 to 40 | 5 | 2 × 10μF 2220 50V | 4 × 100μF 1210 6.3V | 8.5V to 15V | 162 | 210 | 75.0 | 315 | 45.3 |
| 10.5 to 40 | 8 | 2 × 10μF 2220 50V | 4 × 47μF 1210 10V | 8.5V to 15V | 90.9 | 260 | 59.0 | 500 | 23.7 |
| 16 to 40 | 12 | 2 × 10μF 2220 50V | 4 × 22μF 1210 16V | AUX | 56.2 | 300 | 48.7 | 500 | 23.7 |
| 20.5 to 40 | 15 | 1 × 10μF 2220 50V | 4 × 22μF 1210 16V | AUX | 44.2 | 350 | 40.2 | 500 | 23.7 |
| 26 to 40 | 18 | 1 × 10μF 2220 50V | 4 × 10μF 1812 25V | 8.5V to 15V | 36.5 | 400 | 31.6 | 500 | 23.7 |
| 34 to 40 | 24 | 1 × 10μF 2220 50V | 4 × 10μF 1812 25V | 8.5V to 15V | 26.7 | 430 | 28.7 | 500 | 23.7 |
| 4.5 to 56 | –3.3 | 2 × 4.7μF 2220 100V | 5 × 100μF 1812 6.3V | 8.5V to 15V Above Output | 301 | 115 | 154 | 155 | 115 |
| 4.5 to 55 | –5 | 2 × 4.7μF 2220 100V | 4 × 100μF 1210 6.3V | 8.5V to 15V Above Output | 162 | 190 | 90.9 | 230 | 68.2 |
| 10.5 to 52 | –8 | 2 × 4.7μF 2220 100V | 4 × 47μF 1210 10V | 8.5V to 15V Above Output | 90.9 | 260 | 59.0 | 350 | 40.2 |
| 16 to 48 | –12 | 2 × 4.7μF 2220 100V | 4 × 22μF 1210 16V | AUX | 56.2 | 300 | 48.7 | 500 | 23.7 |

TYPICAL APPLICATIONS


3.3V V_{OUT} Step-Down Converter




5V V_{OUT} Step-Down Converter




15V V_{OUT} Step-Down Converter



18V V_{OUT} Step-Down Converter





-12V V_{OUT} Positive-to-Negative Converter



PACKAGE DESCRIPTION

LGA Package
113-Lead (15mm × 15mm × 4.32mm)
(Reference LTC DWG # 05-08-1756 Rev 0)




PACKAGE DESCRIPTION

**Pin Assignment Table
(Arranged by Pin Number)**

| PIN NAME | | PIN NAME | | PIN NAME | |
|----------|-------|----------|------------------|----------|------------------|
| A1 | GND | D6 | GND | H5 | GND |
| A2 | ADJ | D7 | GND | H6 | GND |
| A3 | BIAS2 | D8 | GND | H7 | GND |
| A4 | RUN | D9 | GND | H8 | GND |
| A5 | SS | D10 | GND | H9 | V _{OUT} |
| A6 | BIAS1 | D11 | GND | H10 | V _{OUT} |
| A7 | AUX | E1 | GND | H11 | V _{OUT} |
| A8 | GND | E2 | GND | J1 | V _{IN} |
| A9 | GND | E3 | GND | J2 | V _{IN} |
| A10 | GND | E4 | GND | J3 | V _{IN} |
| A11 | GND | E5 | GND | J5 | GND |
| B1 | RT | E6 | GND | J6 | GND |
| B2 | GND | E7 | GND | J7 | GND |
| B3 | GND | E8 | GND | J8 | GND |
| B4 | GND | E9 | V _{OUT} | J9 | V _{OUT} |
| B5 | GND | E10 | V _{OUT} | J10 | V _{OUT} |
| B6 | GND | E11 | V _{OUT} | J11 | V _{OUT} |
| B7 | GND | F1 | GND | K1 | V _{IN} |
| B8 | GND | F2 | GND | K2 | V _{IN} |
| B9 | GND | F3 | GND | K3 | V _{IN} |
| B10 | GND | F4 | GND | K5 | GND |
| B11 | GND | F5 | GND | K6 | GND |
| C1 | SYNC | F6 | GND | K7 | GND |
| C2 | GND | F7 | GND | K8 | GND |
| C3 | GND | F8 | GND | K9 | V _{OUT} |
| C4 | GND | F9 | V _{OUT} | K10 | V _{OUT} |
| C5 | GND | F10 | V _{OUT} | K11 | V _{OUT} |
| C6 | GND | F11 | V _{OUT} | L1 | V _{IN} |
| C7 | GND | G5 | GND | L2 | V _{IN} |
| C8 | GND | G6 | GND | L3 | V _{IN} |
| C9 | GND | G7 | GND | L5 | GND |
| C10 | GND | G8 | GND | L6 | GND |
| C11 | GND | G9 | V _{OUT} | L7 | GND |
| D1 | GND | G10 | V _{OUT} | L8 | GND |
| D2 | GND | G11 | V _{OUT} | L9 | V _{OUT} |
| D3 | GND | H1 | V _{IN} | L10 | V _{OUT} |
| D4 | GND | H2 | V _{IN} | L11 | V _{OUT} |
| D5 | GND | H3 | V _{IN} | | |

PACKAGE PHOTOGRAPH



RELATED PARTS

| PART NUMBER | DESCRIPTION | COMMENTS |
|----------------------|--|---|
| LTM4600 | 10A DC/DC μModule Regulator | Basic 10A DC/DC μModule, 15mm × 15mm × 2.8mm LGA |
| LTM4600HVMPV | Military Plastic 10A DC/DC μModule Regulator | –55°C to 125°C Operation, 15mm × 15mm × 2.8mm LGA |
| LTM4601/ LTM4601A | 12A DC/DC μModule with PLL, Output Tracking/ Margining and Remote Sensing | Synchronizable, PolyPhase Operation, LTM4601-1 Version has no Remote Sensing |
| LTM4602 | 6A DC/DC μModule Regulator | Pin Compatible with the LTM4600 |
| LTM4603 | 6A DC/DC μModule with PLL and Output Tracking/ Margining and Remote Sensing | Synchronizable, PolyPhase Operation, LTM4603-1 Version has no Remote Sensing, Pin Compatible with the LTM4601 |
| LTM4604 | 4A Low V_{IN} DC/DC μModule Regulator | $2.375V \leq V_{IN} \leq 5V$, $0.8V \leq V_{OUT} \leq 5V$, 9mm × 15mm × 2.3mm LGA |
| LTM4608 | 8A Low V_{IN} DC/DC μModule Regulator | $2.375V \leq V_{IN} \leq 5V$, $0.8V \leq V_{OUT} \leq 5V$, 9mm × 15mm × 2.8mm LGA |
| LTM8020 | 200mA, 36V DC/DC μModule Regulator | Fixed 450kHz Frequency, $1.25V \leq V_{OUT} \leq 5V$, 6.25mm × 6.25mm × 2.32mm LGA |
| LTM8022 | 1A, 36V DC/DC μModule Regulator | Adjustable Frequency, $0.8V \leq V_{OUT} \leq 5V$, 11.25mm × 9mm × 2.82mm LGA, Pin Compatible to the LTM8023 |
| LTM8023 | 2A, 36V DC/DC μModule Regulator | Adjustable Frequency, $0.8V \leq V_{OUT} \leq 5V$, 11.25mm × 9mm × 2.82mm LGA, Pin Compatible to the LTM8022 |
| LTM8025 | 3A, 36V DC/DC μModule Regulator | $0.8V \leq V_{OUT} \leq 24V$, 9mm × 15mm × 4.32mm LGA |