



PLX Technology Acquired Oxford Semiconductor in January 2009

This document is not yet formatted to PLX style

For more information, please visit our Website

Website: www.plxtech.com

Sales: www.plxtech.com/sales

Technical Support: www.plxtech.com/support



© 2009 PLX Technology, Inc. All rights reserved.

OX16C950B

High Performance UART

Description

Utilizing Oxford Semiconductor's high performance UART technology, the OX16C950B is the ideal solution for a diverse range of products requiring serial port connectivity including: PC Add-on Cards, Industrial PC, Point of Sale Terminals, Industrial Control and Network Management.

The OX16C950B is a single chip, single UART for high performance applications. The device incorporates Oxford Semiconductor's high performance, feature-rich UART technology that combines the industry's fastest baud rates and deepest FIFOs. It adds up to a class leading serial connectivity solution.



Features

- High performance UART with peak asynchronous data rates up to 15Mbps
- RS232/422/485 full and half duplex interfaces
- Deep 128-Byte receive/transmit FIFOs
- Full modem interface with hardware out of band flow control
- Automated Xon/Xoff in-band flow control
- Flexible clock prescaler allows for a wide range of baud rates
- Infra-red (IrDA) receive and transmit operation
- Software compatible with industry standard 16C550 type devices
- 3.3/5V operation
- Pin compatible with TL16C550B/C, ST16C650 and TL16C750
- 48 TQFP package
- Commercial temperature range (0 to +70°C)

OX16C950B Block Diagram

