



BATTERIES

SEALED LEAD ACID

SECTION 7

- Multi cell design for economy installations and maintenance
- Individual value for each cell
- High quality flame retardant ABS for cases
- Long life
- Low self discharge rate
- 6v and 12v available.



ORDERING INFORMATION

Ordering Code	Nominal	Nominal Capacity (AH)				Dimensions (mm)				Weight (kg)
	Voltage	20H Rate	10H Rate	5H Rate	1H Rate	Length	Width	Height	Total	
	(V)	VPC (1.75)	VPC (1.75)	VPC (1.70)	VPC (1.60)				Height	
SLA6V1.2	6	1.2	1.1	1.0	0.72	97	25	51	56	0.29
SLA6V1.3	6	1.3	1.2	1.1	0.8	97	25	51	56	0.3
SLA6V4	6	4	3.7	3.4	2.4	70	47	102	106	0.66
SLA6V4.5	6	4.5	4.2	3.8	2.7	70	47	102	106	0.71
SLA6V5	6	5	4.7	4.3	3.0	70	47	102	106	0.78
SLA6V7	6	7	6.5	6.0	4.2	151	34	94	101	1.1
SLA6V8	6	8	7.4	6.8	4.8	151	34	94	101	1.3
SLA6V10	6	10	9.3	8.5	6.0	151	50	94	99	1.7
SLA6V12	6	12	11.3	11.0	7.8	151	50	94	99	1.85
SLA12V1.2	12	1.2	1.1	1.0	0.72	97	48	52	57	0.62
SLA12V2	12	2	1.9	1.7	1.2	178	34	61	65	0.89
SLA12V3	12	3	2.9	2.5	1.8	133	67	61	66	1.25
SLA12V4	12	4	3.7	3.4	2.4	90	70	101	106	1.35
SLA12V5	12	5	4.7	4.3	3.0	90	70	101	106	1.68
SLA12V7	12	7	6.5	6.0	4.2	151	65	94	98	2.2
SLA12V7.5	12	7.5	6.9	6.4	4.5	151	65	94	98	2.35
SLA12V8	12	8	7.4	6.8	4.8	151	65	94	98	2.5
SLA12V10	12	10	9.4	9.1	6.5	151	98	94	100	3.2
SLA12V12	12	12	11.3	11.0	7.8	151	98	94	100	3.65
SLA12V17	12	17	15.8	14.5	10.2	181	77	166	166	5.1
SLA12V18	12	18	16.7	15.3	10.8	181	77	166	166	5.9
SLA12V20	12	20	18.6	17.1	12.7	181	77	166	166	6
SLA12V26	12	26	24.2	22.1	15.6	165	175	125	125	8.7
SLA12V33	12	33	30.7	28.1	19.8	194	132	170	170	11.9
SLA12V40	12	40	37	34.0	24.0	198	166	170	170	14
SLA12V70	12	70	64	58.0	42.0	350	166	174	174	22
SLA12V100	12	100	91	84.0	63.0	331	176	215	235	31
SLA12V150	12	150	137	126.0	90.0	483	170	241	241	54
SLA12V200	12	200	182	168.0	126.0	522	240	244	244	66