

Radiation Hardened, Very Low Noise Quad Operational Amplifier

February 1998

Features

- QML Qualified Per MIL-PRF-38535 Requirements
- Radiation Environment
 - Total Dose 1×10^5 RAD(Si)
- Low Noise
 - At 1kHz $4.3\text{nV}/\sqrt{\text{Hz}}$ (Typ)
 - At 1kHz $0.6\text{pA}/\sqrt{\text{Hz}}$ (Typ)
- Low Offset Voltage 2.1mV (Max)
- High Slew Rate $1.7\text{V}/\mu\text{s}$ (Min)
- Gain Bandwidth Product 8.0MHz (Typ)

Applications

- High Q, Active Filters
- Voltage Regulators
- Integrators
- Signal Generators
- Voltage References
- Space Environments

Description

The HS-OP470ARH is a radiation hardened, monolithic quad operational amplifier that provides highly reliable performance in harsh radiation environments. Its excellent noise characteristics coupled with an unique array of dynamic specifications make this amplifier well-suited for a variety of satellite system applications. Dielectrically isolated, bipolar processing makes this device immune to Single Event Latch-up.

The HS-OP470ARH shows almost no change in offset voltage after exposure to 100K RAD(Si) gamma radiation, with only a minor increase in current. Complementing these specifications is a post radiation open loop gain in excess of 40kV/V.

This quad operational amplifier is available in an industry standard pinout, allowing for immediate interchangeability with most other quad operational amplifiers.

Specifications for Rad Hard QML devices are controlled by the Defense Supply Center in Columbus (DSCC). SMD numbers must be used when ordering.


Detailed Electrical Specifications for this are contained in SMD 5962-98533. A "hot-link" is provided on our homepage with instructions for downloading.
<http://www.intersil.com/data/sm/index.htm>

Ordering Information

SMD PART NUMBER	INTERSIL PART NUMBER	TEMP. RANGE (°C)	PACKAGE	CASE OUTLINE
5962R9853301VXC	HS9-OP470ARH-Q	-55 to 125	14 Ld Flatpack	CDFP3-F14
N/A	HS9-OP470ARH/Sample	25	14 Ld Flatpack	CDFP3-F14

Pinout

HS-OP470ARH (FLATPACK)
TOP VIEW



HS-OP470ARH

Metallization Mask Layout

DIE DIMENSIONS:

95 mils x 99 mils x 19 mils ± 1 mil
(2420 μ m x 2530 μ m x 483 μ m $\pm 25.4\mu$ m)

METALLIZATION:

Type: Al, 1% Cu
Thickness: 16k \AA ± 2 k \AA

SUBSTRATE POTENTIAL (Powered Up):

Unbiased

BACKSIDE FINISH:

Silicon

PASSIVATION:

Type: Nitride (Si₃N₄) over Silox (SiO₂, 5% Phos.)
Silox Thickness: 12k \AA ± 2 k \AA
Nitride Thickness: 3.5k \AA ± 1.5 k \AA

WORST CASE CURRENT DENSITY:


$< 2.0 \times 10^5$ A/cm²

TRANSISTOR COUNT:

175

PROCESS:

Bipolar Dielectric Isolation



All Intersil semiconductor products are manufactured, assembled and tested under **ISO9000** quality systems certification.

Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see web site <http://www.intersil.com>

Sales Office Headquarters

NORTH AMERICA

Intersil Corporation
P. O. Box 883, Mail Stop 53-204
Melbourne, FL 32902
TEL: (321) 724-7000
FAX: (321) 724-7240

EUROPE

Intersil SA
Mercure Center
100, Rue de la Fusee
1130 Brussels, Belgium
TEL: (32) 2.724.2111
FAX: (32) 2.724.22.05

ASIA

Intersil (Taiwan) Ltd.
Taiwan Limited
7F-6, No. 101 Fu Hsing North Road
Taipei, Taiwan
Republic of China
TEL: (886) 2 2716 9310
FAX: (886) 2 2715 3029