

10/100/1000BASE-T TCP Processing Engine, RDMA, iSCSI, and Ethernet Controller with PCI Express[®]


FEATURES

- **Single-chip solution for LAN on Motherboard (LOM) and Network interface card (NIC) applications**
 - Integrated 10BASE-T/100BASE-TX/1000BASE-T transceivers
 - Host interfaces
 - PCI Express[®] x4 Host interface
- **TCP processing engine**
 - Full fastpath TCP processing
- **iSCSI controller**
 - iSCSI initiator
- **RDMA controller (RNIC)**
 - RDMA over TCP (iWARP)—RDMAC 1.0 compliant
 - Hardware-based data placement in application buffers without CPU intervention (user and kernel modes)
- **Other performance features**
 - Receive side scaling (RSS)
 - TCP, IP checksum
 - TCP segmentation
 - Adaptive interrupts
 - Message signal interrupt (MSI) support
- **Robust manageability**
 - Universal management port (UMP)
 - PXE 2.0 remote boot
 - Wake-On LAN
 - IPMI pass-through feature
 - Statistics gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30))
 - Comprehensive diagnostic and configuration software suite
 - ACPI 1.1a-compliant power management
- **Advanced network features**
 - Virtual LANs—802.1q VLAN tagging
 - Jumbo frames (9 KB)
 - 802.3x flow control
- **Low-power CMOS design**
- **On-chip power circuit controller**
- **400-ball 21 mm x 21 mm FBGA package**
- **3.3V I/Os**
- **JTAG**

SUMMARY OF BENEFITS

- **Industry's first 10/100/1000 TOE solution—power and space optimized for server blade and low-profile NIC applications**
- **Extremely low CPU utilization for TCP/IP applications**
 - Host CPU is free to run application code
- **Accelerated IP-based storage**
 - Lower CPU utilization for file-level storage protocols such as CIFS and NFS
 - iSCSI functionality with low CPU utilization
- **RDMA support for data placement in application buffers reduces CPU utilization and lowers data transit latencies.**
- **Future-proof**
 - Flexible implementation for TCP, iWARP, and iSCSI can accommodate specification changes and interoperability issues
- **Performance-focused—optimized for throughput and CPU utilization**
 - Adaptive interrupts
 - RSS reduces CPU utilization on multi-CPU systems
 - MSI allows interrupt distribution in a multi-CPU host system
 - PCI Express host interface allows a low-latency access to CPU and memory resources
- **Robust and highly manageable**
 - UMP enables high bandwidth out-of-band system management functionality over shared infrastructure
 - PXE 2.0, ACPI 1.1, Wake-On LAN
 - IPMI pass-through capability allows on-board management controllers access to the network in OS-present and OS-absent states
- **Server class reliability, availability, and performance features**
 - Link aggregation and load balancing
 - Switch-dependent
 - 802.3ad (LACP), generic trunking (GEC/FEC)
 - Switch- and NIC-independent
- **Low power for zero airflow implementations**
 - Advanced power management
- **Minimal real estate—ideal for LOM**
 - On-chip power circuit controller

OVERVIEW



The BCM5708C provides a fully integrated Layer 4 and Layer 5 solution—TCP/IP, RDMA, and iSCSI 1.0 along with a complete 10/100/1000BASE-T Gigabit Ethernet, IEEE 802.3™ compliant media access control (MAC), and physical layer transceiver solution for high-performance network applications. By itself, the BCM5708C provides a complete single-chip Gigabit Ethernet NIC with a TCP/IP processing engine, RDMA NIC (RNIC), iSCSI 1.0 HBA, or LOM solution.

The BCM5708C is different from other network controllers because it can process the TCP/IP and relevant L5 protocols on data directly from the application buffers on the host, thereby relieving the host CPU from these time-consuming operations. On the receive path, the BCM5708C processes the frame up to the highest layer supported present in it. For example, the BCM5708C processes the frame for RDMA when the frame is an RDMA frame.

With the appropriate configuration, the BCM5708C can simultaneously support the following three functions:

- RDMA network interface controller (RNIC)
- iSCSI host bus adapter
- TOE chimney-enabled network accelerator

Target Applications of the BCM5708C

- Gigabit Ethernet NICs and LAN-on Motherboard (LOM)
- iSCSI 1.0 host bus adapters (HBA)
- RDMA network interface card (RNIC)

Network Interface Cards (NIC) Designs

10/1001000BASE-T	PCI Express x4 NIC
------------------	--------------------

LAN on Motherboard (LOM) Designs

10/1001000BASE-T	PCI Express x4, x2, or x1 LOM
------------------	-------------------------------

Broadcom®, the pulse logo, Connecting everything®, and the Connecting everything logo are among the trademarks of Broadcom Corporation and/or its affiliates in the United States, certain other countries and/or the EU. Any other trademarks or trade names mentioned are the property of their respective owners.

Connecting
everything®



BROADCOM CORPORATION

5300 California Avenue
Irvine, California 92617

© 2007 by BROADCOM CORPORATION. All rights reserved.

5708C-PB08-R 10/30/07

Phone: 949-926-5000
Fax: 949-926-5203
E-mail: info@broadcom.com
Web: www.broadcom.com