

M/A-COM 11 dB Directional Coupler 500 - 1000 MHz

Features

- Space Qualified
- Designed to meet the Stringent Reliability Standards of Space Hardware
- 50 Ohms Nominal Impedance

Description


M/A-COM's CH20-0059-S is a unique type of 11 dB Directional Coupler designed to operate within the frequency range of 500 MHz to 1000 MHz.

Absolute Maximum Ratings¹

Parameter	Absolute Maximum
Max. Input Power 10-500 MHz	1 Watt
Operating Temperature	-40°C to +85°C
Storage Temperature	-65°C to +125°C

1. Operation of this device above any one of these parameters may cause permanent damage.

FP-1



Electrical Specifications, T_A = +25°C

Parameter	Frequency	Units	Min.	Typ.	Max.
Coupling	500-1000 MHz	dB	-	10.8 dB ± 0.7 dB	-
Coupling Flatness	500-1000 MHz	dB	-	-	±0.5
Directivity	500-1000 MHz	dB	18	-	-
VSWR	500-1000 MHz	-	-	-	1.4:1
Main Line Loss	500-1000 MHz	dB	-	-	1.5

Specifications subject to change without notice.

- North America: Tel. (800) 366-2266, Fax (800) 618-8883
- Asia/Pacific: Tel.+81-44-844-8296, Fax +81-44-844-8298
- Europe: Tel. +44 (1344) 869 595, Fax+44 (1344) 300 020

Visit www.macom.com for additional data sheets and product information.

tyco / Electronics

M/A-COM

V 2.0

1