



JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
CF24236-24B	WHITE 7,570°k x = .300 y = .308	1260 TYP. @ 0°C	516	5.0	32,000±10%	50,000
			501	6.5	38,000±10%	30,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

 THIRD ANGLE PROJECTION	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.3 2 PL +/- 0.2 ANGLE +/- 0	<b>JKL COMPONENTS CORPORATION</b>			
		TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP			
DRAWN BY L. WENGSTROM	APPVD BY J.K.	DATE 1/20/04	SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>CF24236-24B</b>
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE	RELEASED DATE 1/20/04	REVISION DATE
REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE	REV. NO.	SHEET 1 OF 1	