




**FRONTIER
ELECTRONICS CO., LTD.**


**SRF10-03
THRU
SRF10-10**

10A SCHOTTKY BARRIER RECTIFIERS

CASE : ITO-220AC (SRF10-xx) , FULLY INSULATED PACKAGE



PIN 1 ← | → PIN 2
CASE



	MILLIMETERS	
	MIN	MAX
B	9.72	10.27
C	6.30	6.90
D	14.50	15.50
E	13.00	13.80
F	-	4.1
G	4.95	5.20
H	-	1.52
I	-	0.9
J	-	4.8
K	-	3.1
L	2.5	2.9
M	-	0.8
O	-	Ø 3.4

FEATURES

- EXTREMELY LOW VF
- LOW STORED CHARGE, MAJORITY CARRIER CONDUCTION
- LOW POWER LOSS / HIGH EFFICIENCY
- UL 94V0 FLAME RETARDANT EPOXY MOLDING COMPOUND

MECHANICAL DATA

- CASE : TRANSFER MOLDED
- LEADS : SOLDERABLE PER MIL-STD-202,METHOD 208
- POLARITY : AS MARKED
- WEIGHT : 1.81 GRAMS

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS
RATINGS AT 25°C AMBIENT TEMPERATURE UNLESS OTHERWISE SPECIFIED
SINGLE PHASE, HALF WAVE, 60 HZ, RESISTIVE OR INDUCTIVE LOAD.
FOR CAPACITIVE LOAD, DERATE CURRENT BY 20%

RATINGS	SYMBOL	SRF10	SRF10	SRF10	SRF10	SRF10	SRF10	SRF10	SRF10	SRF10	SRF10	UNITS
		-03	-035	-04	-045	-05	-06	-07	-08	-09	-10	
MAXIMUM RECURRENT PEAK REVERSE VOLTAGE	V _{RRM}	30	35	40	45	50	60	70	80	90	100	V
MAXIMUM RMS VOLTAGE	V _{RMS}	21	24	28	31	35	42	49	56	63	70	V
MAXIMUM DC BLOCKING VOLTAGE	V _{DC}	30	35	40	45	50	60	70	80	90	100	V
MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT SEE FIG.1 PER LEG	I _O	10.0 5.0										A
PEAK FORWARD SURGE CURRENT, 8.3ms SINGLE HALF SINE-WAVE SUPERIMPOSED ON RATED LOAD PER LEG	I _{FSM}	125										A
STORAGE TEMPERATURE RANGE	T _{STG}	- 55 TO + 150										°C
OPERATING TEMPERATURE RANGE	T _{OP}	- 55 TO + 125										°C

ELECTRICAL CHARACTERISTICS (A_T T_A =25°C UNLESS OTHERWISE NOTED)

CHARACTERISTICS	SYMBOL	SRF10	SRF10	SRF10	SRF10	SRF10	SRF10	SRF10	SRF10	SRF10	SRF10	UNITS
		-03	-035	-04	-045	-05	-06	-07	-08	-09	-10	
MAXIMUM FORWARD VOLTAGE AT I _O PER LEG	V _F	0.55			0.70			0.85			V	
MAXIMUM REVERSE CURRENT AT 25°C PER LEG (NOTE 1)	I _R	5.0										mA
MAXIMUM REVERSE CURRENT AT 100°C PER LEG (NOTE 1)	I _R	50.0										mA

THERMAL CHARACTERISTICS (T_C =25°C UNLESS OTHERWISE NOTED)

PARAMETER	SYMBOL	SRF10	UNITS
TYPICAL THERMAL RESISTANCE JUNCTION TO CASE PER LEG	R _{θjc}	4.0	°C/W

NOTES : 1. PULSE TEST: 300µS PULSE WIDTH, 1% DUTY CYCLE

RATINGS AND CHARACTERISTIC CURVES OF SRF10-03 AND SRF10-10

FIG. 1 - FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG. 3 - TYPICAL REVERSE CHARACTERISTICS




FIG. 4 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS

