

Memory Module Specification

KVR533D2N4/1G 1GB 128M x 64-Bit DDR2-533 CL4 240-Pin DIMM

DESCRIPTION:

This document describes ValueRAM's 128M x 64-bit (1GB) DDR2-533 CL4 SDRAM (Synchronous **DRAM**) memory module. The components on this module include eight 128M x 8-bit DDR2-533 SDRAM in FBGA packages. This 240-pin DIMM uses gold contact fingers and requires +1.8V. The electrical and mechanical specifications are as follows:

FEATURES:

☑ Clock Cycle Time (tCK) CL=4

- \mathbf{V} Row Cycle Time (tRC)
- Refresh to Active/Refresh Command Time (tRFC)
- \mathbf{V} Row Active Time (tRAS)
- Single Power Supply of
- Dever Power
- **UL** Rating

3.75ns (min.) / 8ns (max.) 60ns (min.) 127.5ns 45ns (min.) / 70,000ns (max.) +1.8V (+/- .1V) 1.170 W (operating) 94 V - 0

Note: The module defined in this data sheet is one of several configurations available under this part number. While all configurations are compatible, the DRAM combination and/or the module height may vary from what is described here.




Figure 1: KVR533D2N4/1G 240-Pin DIMM

Document No. VALUERAM0777-001.A00