

KVR333X64SC25/1G
1GB 128M x 64-Bit DDR333
CL2.5 200-Pin SODIMM

DESCRIPTION:

This document describes ValueRAM's 128M x 64-bit (1GB) DDR333 CL2.5 SDRAM (Synchronous DRAM) memory module. The components on this module include sixteen 64M x 8-bit (16M x 8-bit x 4 Bank) DDR333 SDRAM sealed in TCP packages. This 200-pin DIMM uses gold contact fingers and requires +2.5V. The electrical and mechanical specifications are as follows:

FEATURES:

<input checked="" type="checkbox"/>	Clock Cycle Time (tCK)	6ns (min.) / 12ns (max.)
<input checked="" type="checkbox"/>	Row Cycle Time (tRC)	60ns (min.)
<input checked="" type="checkbox"/>	Refresh Row Cycle Time (tRFC)	72ns (min.)
<input checked="" type="checkbox"/>	Row Active Time (tRAS)	42ns (min.) / 70,000ns (max.)
<input checked="" type="checkbox"/>	Single Power Supply of	+2.5V (+/- .2V)
<input checked="" type="checkbox"/>	Operating (IDD0)	4.400 W
<input checked="" type="checkbox"/>	UL Rating	94 V - 0




Figure 1: KVR333X64SC25/1G 200-Pin SODIMM