


May 2008

HYS64D[32/64]0x0EDL-5-D
HYS64D[32/64]0x0EDL-6-D

*200-Pin Small Outline Dual-In-Line Memory Modules
SO-DIMM
DDR SDRAM*

Advance
Internet Data Sheet

Rev. 0.60



www.qimonda.com

Qimonda

HYS64D[32/64]0x0EDL-[5/6]-D
Small Outline DDR SDRAM Modules

HYS64D[32/64]0x0EDL-5-D, HYS64D[32/64]0x0EDL-6-D	
Revision History: 2008-05, Rev. 0.60	
Page	Subjects (major changes since last revision)
All	Added product type HYS64D32000EDL-[5/6]-D and adapted to internet edition.
Previous Revision: Rev. 0.50, 2007-09	
All	New Document.

We Listen to Your Comments

Any information within this document that you feel is wrong, unclear or missing at all?

Your feedback will help us to continuously improve the quality of this document.

Please send your proposal (including a reference to this document) to:

techdoc@qimonda.com

HYS64D[32/64]0x0EDL-[5/6]-D
Small Outline DDR SDRAM Modules

1 Overview

This chapter contains features and the description.

1.1 Features

- Non-parity 200-Pin Small Outline Dual-In-Line Memory Modules
- One rank 32M × 64, two ranks 64M × 64 module organization
- JEDEC standard Double Data Rate Synchronous DRAMs (DDR SDRAM)
- Single +2.5 V (± 0.2 V) power supply and +2.6 V (± 0.1 V) for DDR400
- Built with 512 Mbit DDR SDRAMs organised as ×16 in packages P-TSOPII-66
- Programmable CAS Latency, Burst Length, and Wrap Sequence (Sequential & Interleave)
- Auto Refresh (CBR) and Self Refresh
- All inputs and outputs SSTL_2 compatible
- Serial Presence Detect with E²PROM
- Industry standard form factor: 67.60 mm × 31.75 mm × 3.80 mm
- Industry standard reference layout Raw Cards A
- DDR400 speed grade supported
- Gold plated contacts

TABLE 1
Performance for -5 and -6

Part Number Speed Code			-5	-6	Unit
Speed Grade	Component		DDR400B	DDR333B	—
	Module		PC3200-3033	PC2700-2533	
max. Clock Frequency	@CL3	f_{CK3}	200	166	MHz
	@CL2.5	$f_{CK2.5}$	166	166	MHz
	@CL2	f_{CK2}	133	133	MHz

1.2 Description

The HYS64D[32/64]0x0EDL-5-D and HYS64D[32/64]0x0EDL-6-D are industry standard 200-Pin Small Outline Dual-In-Line Memory Modules (SO-DIMMs) organized as 64M × 64. The memory array is designed with Double Data Rate Synchronous DRAMs (DDR SDRAM). A variety of decoupling capacitors are mounted on the PC board. The DIMMs feature serial presence detect based on a

serial E²PROM device using the 2-pin I²C protocol. The first 128 bytes are programmed with configuration data and the second 128 bytes are available to the customer.





HYS64D[32/64]0x0EDL-[5/6]-D
Small Outline DDR SDRAM Modules

TABLE 2
Ordering Information for Lead-Free (RoHS Compliant Products)

Product Type	Compliance Code	Description	SDRAM Technology	Note ¹⁾	
PC3200 (CL=3.0)					
HYS64D32000EDL-5-D	PC3200S-3033-1-C1	one rank 256MB SO-DIMM	512 MBit (×16)		
HYS64D64020EDL-5-D	PC3200S-3033-1-A1	two ranks 512MB SO-DIMM	512 MBit (×16)		
PC2700 (CL=2.5)					
HYS64D32000EDL-6-D	PC2700S-2533-1-C1	one rank 256MB SO-DIMM	512 MBit (×16)		
HYS64D64020EDL-6-D	PC2700S-2533-1-A1	two ranks 512MB SO-DIMM	512 MBit (×16)		

1) RoHS: Restriction of the use of certain hazardous substances in electrical and electronic equipment as defined in the directive 2002/95/EC issued by the European Parliament and of the Council of 27 January 2003. These substances include mercury, lead, cadmium, hexavalent chromium, polybrominated biphenyls and polybrominated biphenyl ethers.

Note: All product types end with a place code designating the silicon-die revision. Reference information available on request. Example: HYS64D64020EDL-5-D, indicating Rev.B die are used for SDRAM components. The Compliance Code is printed on the module labels and describes the speed sort (for example "PC3200"), the latencies (for example "30330" means CAS latency of 3.0 clocks, Row-Column-Delay (RCD) latency of 3 clocks and Row Precharge latency of 3 clocks), JEDEC SPD code definition version 1, and the Raw Card used for this module.

TABLE 3
Address Format

Density	Organization	Memory Ranks	SDRAMs	# of SDRAMs	# of row/bank/ columns bits	Refresh	Period	Interval
512MB	64M ×64	2	32M ×16	8	13/2/10	8K	64 ms	7.8 μs
256MB	32M ×64	1	32M ×16	4	13/2/10	8K	64 ms	7.8 μs



2 Pin Configuration

2.1 Pin Configuration

The pin configuration of the Unbuffered Small Outline DDR SDRAM DIMM is listed by function in **Table 4** (200 pins). The abbreviations used in columns Pin and Buffer Type are

explained in **Table 5** and **Table 6** respectively. The pin numbering is depicted in **Figure 1**.

TABLE 4
Pin Configuration of SO-DIMM

Pin#	Name	Pin Type	Buffer Type	Function
Clock Signals				
35	CK0	I	SSTL	Clock Signal
160	CK1	I	SSTL	Clock Signal
89	CK2	I	SSTL	Clock Signal <i>Note: ECC type module</i>
	NC	NC	–	<i>Note: non-ECC type module</i>
37	$\overline{\text{CK0}}$	I	SSTL	Complement Clock
158	$\overline{\text{CK1}}$	I	SSTL	Complement Clock
91	$\overline{\text{CK2}}$	I	SSTL	Complement Clock <i>Note: ECC type module</i>
	NC	NC	–	<i>Note: non-ECC type module</i>
96	CKE0	I	SSTL	Clock Enable Rank 0
95	CKE1	I	SSTL	Clock Enable Rank 1 <i>Note: 2-rank module</i>
	NC	NC	–	<i>Note: 1-rank module</i>
Control Signals				
121	$\overline{\text{S0}}$	I	SSTL	Chip Select Rank 0
122	$\overline{\text{S1}}$	I	SSTL	Chip Select Rank 1 <i>Note: 2-ranks module</i>
	NC	NC	–	<i>Note: 1-rank module</i>
118	$\overline{\text{RAS}}$	I	SSTL	Row Address Strobe
120	$\overline{\text{CAS}}$	I	SSTL	Column Address Strobe
119	$\overline{\text{WE}}$	I	SSTL	Write Enable



HYS64D[32/64]0x0EDL-[5/6]-D
Small Outline DDR SDRAM Modules

Pin#	Name	Pin Type	Buffer Type	Function
Address Signals				
117	BA0	I	SSTL	Bank Address Bus 1:0
116	BA1	I	SSTL	
112	A0	I	SSTL	Address Bus 11:0
111	A1	I	SSTL	
110	A2	I	SSTL	
109	A3	I	SSTL	
108	A4	I	SSTL	
107	A5	I	SSTL	
106	A6	I	SSTL	
105	A7	I	SSTL	
102	A8	I	SSTL	
101	A9	I	SSTL	
115	A10	I	SSTL	
	AP	I	SSTL	
100	A11	I	SSTL	
99	A12	I	SSTL	Address Signal 12 <i>Note: Module based on 256 Mbit or larger dies</i>
	NC	NC	–	<i>Note: 128 Mbit based module</i>
123	A13	I	SSTL	Address Signal 13 <i>Note: 1 Gbit based module</i>
	NC	NC	–	<i>Note: Module based on 512 Mbit or smaller dies</i>
Data Signals				
5	DQ0	I/O	SSTL	Data Bus 63:0
7	DQ1	I/O	SSTL	
13	DQ2	I/O	SSTL	
17	DQ3	I/O	SSTL	
6	DQ4	I/O	SSTL	
8	DQ5	I/O	SSTL	
14	DQ6	I/O	SSTL	
18	DQ7	I/O	SSTL	
19	DQ8	I/O	SSTL	
23	DQ9	I/O	SSTL	
29	DQ10	I/O	SSTL	
31	DQ11	I/O	SSTL	
20	DQ12	I/O	SSTL	
24	DQ13	I/O	SSTL	

HYS64D[32/64]0x0EDL-[5/6]-D
Small Outline DDR SDRAM Modules

Pin#	Name	Pin Type	Buffer Type	Function
30	DQ14	I/O	SSTL	Data Bus 63:0
32	DQ15	I/O	SSTL	
41	DQ16	I/O	SSTL	
43	DQ17	I/O	SSTL	
49	DQ18	I/O	SSTL	
53	DQ19	I/O	SSTL	
42	DQ20	I/O	SSTL	
44	DQ21	I/O	SSTL	
50	DQ22	I/O	SSTL	
54	DQ23	I/O	SSTL	
55	DQ24	I/O	SSTL	
59	DQ25	I/O	SSTL	
65	DQ26	I/O	SSTL	
67	DQ27	I/O	SSTL	
56	DQ28	I/O	SSTL	
60	DQ29	I/O	SSTL	
66	DQ30	I/O	SSTL	
68	DQ31	I/O	SSTL	
127	DQ32	I/O	SSTL	
129	DQ33	I/O	SSTL	
135	DQ34	I/O	SSTL	
139	DQ35	I/O	SSTL	
128	DQ36	I/O	SSTL	
130	DQ37	I/O	SSTL	
136	DQ38	I/O	SSTL	
140	DQ39	I/O	SSTL	
141	DQ40	I/O	SSTL	
145	DQ41	I/O	SSTL	
151	DQ42	I/O	SSTL	
153	DQ43	I/O	SSTL	
142	DQ44	I/O	SSTL	
146	DQ45	I/O	SSTL	
152	DQ46	I/O	SSTL	
154	DQ47	I/O	SSTL	
163	DQ48	I/O	SSTL	
165	DQ49	I/O	SSTL	
171	DQ50	I/O	SSTL	
175	DQ51	I/O	SSTL	
164	DQ52	I/O	SSTL	
166	DQ53	I/O	SSTL	



HYS64D[32/64]0x0EDL-[5/6]-D
Small Outline DDR SDRAM Modules

Pin#	Name	Pin Type	Buffer Type	Function
172	DQ54	I/O	SSTL	Data Bus 63:0
176	DQ55	I/O	SSTL	
177	DQ56	I/O	SSTL	
181	DQ57	I/O	SSTL	
187	DQ58	I/O	SSTL	
189	DQ59	I/O	SSTL	
178	DQ60	I/O	SSTL	
182	DQ61	I/O	SSTL	
188	DQ62	I/O	SSTL	
190	DQ63	I/O	SSTL	
71	CB0	I/O	SSTL	Check Bit 0 <i>Note: ECC type module</i>
	NC	NC	–	<i>Note: Non-ECC module</i>
73	CB1	I/O	SSTL	Check Bit 1 <i>Note: ECC type module</i>
	NC	NC	–	<i>Note: Non-ECC module</i>
79	CB2	I/O	SSTL	Check Bit 2 <i>Note: ECC type module</i>
	NC	NC	–	<i>Note: Non-ECC module</i>
83	CB3	I/O	SSTL	Check Bit 3 <i>Note: ECC type module</i>
	NC	NC	–	<i>Note: Non-ECC module</i>
72	CB4	I/O	SSTL	Check Bit 4 <i>Note: ECC type module</i>
	NC	NC	–	<i>Note: Non-ECC module</i>
74	CB5	I/O	SSTL	Check Bit 5 <i>Note: ECC type module</i>
	NC	NC	–	<i>Note: Non-ECC module</i>
80	CB6	I/O	SSTL	Check Bit 6 <i>Note: ECC type module</i>
	NC	NC	–	<i>Note: Non-ECC module</i>
84	CB7	I/O	SSTL	Check Bit 7 <i>Note: ECC type module</i>
	NC	NC	–	<i>Note: Non-ECC module</i>



HYS64D[32/64]0x0EDL-[5/6]-D
Small Outline DDR SDRAM Modules

Pin#	Name	Pin Type	Buffer Type	Function
11	DQS0	I/O	SSTL	Data Strobes 7:0 <i>Note: See block diagram for corresponding DQ signals</i>
25	DQS1	I/O	SSTL	
47	DQS2	I/O	SSTL	
61	DQS3	I/O	SSTL	
133	DQS4	I/O	SSTL	
147	DQS5	I/O	SSTL	
169	DQS6	I/O	SSTL	
183	DQS7	I/O	SSTL	
77	DQS8	I/O	SSTL	Data Strobe 8 <i>Note: ECC type module</i>
	NC	NC	–	<i>Note: Non-ECC module</i>
12	DM0	I	SSTL	Data Mask 7:0
26	DM1	I	SSTL	
48	DM2	I	SSTL	
62	DM3	I	SSTL	
134	DM4	I	SSTL	
148	DM5	I	SSTL	
170	DM6	I	SSTL	
184	DM7	I	SSTL	
78	DM8	I	SSTL	Data Mask 8 <i>Note: ECC type module</i>
	NC	NC	–	<i>Note: Non-ECC module</i>
EEPROM				
195	SCL	I	CMOS	Serial Bus Clock
193	SDA	I/O	OD	Serial Bus Data
194	SA0	I	CMOS	Slave Address Select Bus 2:0
196	SA1	I	CMOS	
198	SA2	I	CMOS	

HYS64D[32/64]0x0EDL-[5/6]-D
Small Outline DDR SDRAM Modules

Pin#	Name	Pin Type	Buffer Type	Function
Power Supplies				
1,2	V_{REF}	AI	–	I/O Reference Voltage
197	V_{DDSPD}	PWR	–	EEPROM Power Supply
9,10,21, 22, 33, 34, 36, 45, 46, 57, 58, 69, 70, 81, 82, 92, 93, 94, 113, 114, 131, 132, 143, 144, 155, 156, 157, 167, 168, 179, 180, 191, 192	V_{DD}	PWR	–	Power Supply



HYS64D[32/64]0x0EDL-[5/6]-D
Small Outline DDR SDRAM Modules

Pin#	Name	Pin Type	Buffer Type	Function
3,4, 15, 16, 27, 28, 38, 39, 40, 51, 52, 63, 64, 75, 76, 87, 88, 90, 103, 104, 125, 126, 137, 138, 149, 150, 159, 161, 162, 173, 174, 185, 186	V _{SS}	GND	–	Ground Plane
Other Pins				
199	V _{DDID}	O	OD	V _{DD} Identification <i>Note: Pin in tristate, indicating V_{DD} and V_{DDQ} nets connected on PCB</i>
85, 86, 97, 98, 124, 200	NC	NC	–	Not connected <i>Note: Pins not connected on Infineon SO DIMMs</i>

**TABLE 5**
Abbreviations for Pin Type

Abbreviation	Description
I	Standard input-only pin. Digital levels.
O	Output. Digital levels.
I/O	I/O is a bidirectional input/output signal.
AI	Input. Analog levels.
PWR	Power
GND	Ground
NC	Not Connected


TABLE 6
Abbreviations for Buffer Type

Abbreviation	Description
SSTL	Serial Stub Terminated Logic (SSTL2)
LV-CMOS	Low Voltage CMOS
CMOS	CMOS Levels
OD	Open Drain. The corresponding pin has 2 operational states, active low and tristate, and allows multiple devices to share as a wire-OR.



HYS64D[32/64]0x0EDL-[5/6]-D
Small Outline DDR SDRAM Modules

FIGURE 1
Pin Configuration Diagram 200-Pin SO-DIMM



MPPD0040



3 Electrical Characteristics

This chapter lists the electrical characteristics.

3.1 Operating Conditions

This chapter contains the operating conditions tables.

TABLE 7
Absolute Maximum Ratings

Parameter	Symbol	Values			Unit	Note/ Test Condition
		min.	typ.	max.		
Voltage on I/O pins relative to V_{SS}	V_{IN}, V_{OUT}	-0.5	-	$V_{DDQ} + 0.5$	V	-
Voltage on inputs relative to V_{SS}	V_{IN}	-1	-	+3.6	V	-
Voltage on V_{DD} supply relative to V_{SS}	V_{DD}	-1	-	+3.6	V	-
Voltage on V_{DDQ} supply relative to V_{SS}	V_{DDQ}	-1	-	+3.6	V	-
Operating temperature (ambient)	T_A	0	-	+70	°C	-
Storage temperature (plastic)	T_{STG}	-55	-	+150	°C	-
Power dissipation (per SDRAM component)	P_D	-	1	-	W	-
Short circuit output current	I_{OUT}	-	50	-	mA	-

Attention: Permanent damage to the device may occur if “Absolute Maximum Ratings” are exceeded. This is a stress rating only, and functional operation should be restricted to recommended operation conditions. Exposure to absolute maximum rating conditions for extended periods of time may affect device reliability and exceeding only one of the values may cause irreversible damage to the integrated circuit.

TABLE 8
Electrical Characteristics and DC Operating Conditions

Parameter	Symbol	Values			Unit	Note/Test Condition ¹⁾
		Min.	Typ.	Max.		
Device Supply Voltage	V_{DD}	2.3	2.5	2.7	V	$f_{CK} \leq 166$ MHz
Device Supply Voltage	V_{DD}	2.5	2.6	2.7	V	$f_{CK} > 166$ MHz ²⁾
Output Supply Voltage	V_{DDQ}	2.3	2.5	2.7	V	$f_{CK} \leq 166$ MHz ³⁾
Output Supply Voltage	V_{DDQ}	2.5	2.6	2.7	V	$f_{CK} > 166$ MHz ^{2,3)}
EEPROM supply voltage	V_{DDSPD}	2.3	2.5	3.6	V	—
Supply Voltage, I/O Supply Voltage	V_{SS}, V_{SSQ}	0		0	V	—
Input Reference Voltage	V_{REF}	$0.49 \times V_{DDQ}$	$0.5 \times V_{DDQ}$	$0.51 \times V_{DDQ}$	V	⁴⁾
I/O Termination Voltage (System)	V_{TT}	$V_{REF} - 0.04$		$V_{REF} + 0.04$	V	⁵⁾



HYS64D[32/64]0x0EDL-[5/6]-D
Small Outline DDR SDRAM Modules

Parameter	Symbol	Values			Unit	Note/Test Condition ¹⁾
		Min.	Typ.	Max.		
Input High (Logic1) Voltage	$V_{IH(DC)}$	$V_{REF} + 0.15$		$V_{DDQ} + 0.3$	V	⁶⁾
Input Low (Logic0) Voltage	$V_{IL(DC)}$	-0.3		$V_{REF} - 0.15$	V	⁶⁾
Input Voltage Level, CK and CK Inputs	$V_{IN(DC)}$	-0.3		$V_{DDQ} + 0.3$	V	⁶⁾
Input Differential Voltage, CK and CK Inputs	$V_{ID(DC)}$	0.36		$V_{DDQ} + 0.6$	V	⁶⁾⁷⁾
VI-Matching Pull-up Current to Pull-down Current	$V_{I_{Ratio}}$	0.71		1.4	—	⁸⁾
Input Leakage Current	I_I	-2		2	μA	Any input $0 V \leq V_{IN} \leq V_{DD}$; All other pins not under test = 0 V ⁹⁾
Output Leakage Current	I_{OZ}	-5		5	μA	DQs are disabled; $0 V \leq V_{OUT} \leq V_{DDQ}$ ⁹⁾
Output High Current, Normal Strength Driver	I_{OH}	-16.2		—	mA	$V_{OUT} = 1.95 V$
Output Low Current, Normal Strength Driver	I_{OL}	16.2		—	mA	$V_{OUT} = 0.35 V$

- 1) $0^\circ C \leq T_A \leq 70^\circ C$; $V_{DDQ} = 2.5 V \pm 0.2 V$, $V_{DD} = +2.5 V \pm 0.2 V$;
- 2) DDR400 conditions apply for all clock frequencies above 166 MHz
- 3) Under all conditions, V_{DDQ} must be less than or equal to V_{DD} .
- 4) Peak to peak AC noise on V_{REF} may not exceed $\pm 2\% V_{REF,DC}$. V_{REF} is also expected to track noise variations in V_{DDQ} .
- 5) V_{TT} is not applied directly to the device. V_{TT} is a system supply for signal termination resistors, is expected to be set equal to V_{REF} , and must track variations in the DC level of V_{REF} .
- 6) Inputs are not recognized as valid until V_{REF} stabilizes.
- 7) V_{ID} is the magnitude of the difference between the input level on CK and the input level on \overline{CK} .
- 8) The ratio of the pull-up current to the pull-down current is specified for the same temperature and voltage, over the entire temperature and voltage range, for device drain to source voltage from 0.25 to 1.0 V. For a given output, it represents the maximum difference between pull-up and pull-down drivers due to process variation.
- 9) Values are shown per pin.



3.2 Current Specification and Conditions

This chapter describes the Specifications and Conditions.

TABLE 9
 I_{DD} Conditions

Parameter	Symbol
Operating Current 0 one bank; active/precharge; DQ, DM, and DQS inputs changing once per clock cycle; address and control inputs changing once every two clock cycles.	I_{DD0}
Operating Current 1 one bank; active/read/precharge; Burst Length = 4; see component data sheet.	I_{DD1}
Precharge Power-Down Standby Current all banks idle; power-down mode; $CKE \leq V_{IL,MAX}$	I_{DD2P}
Precharge Floating Standby Current $\overline{CS} \geq V_{IH,MIN}$, all banks idle; $CKE \geq V_{IH,MIN}$; address and other control inputs changing once per clock cycle; $V_{IN} = V_{REF}$ for DQ, DQS and DM.	I_{DD2F}
Precharge Quiet Standby Current $\overline{CS} \geq V_{IH,MIN}$, all banks idle; $CKE \geq V_{IH,MIN}$; $V_{IN} = V_{REF}$ for DQ, DQS and DM; address and other control inputs stable at $\geq V_{IH,MIN}$ or $\leq V_{IL,MAX}$.	I_{DD2Q}
Active Power-Down Standby Current one bank active; power-down mode; $CKE \leq V_{IL,MAX}$; $V_{IN} = V_{REF}$ for DQ, DQS and DM.	I_{DD3P}
Active Standby Current one bank active; $\overline{CS} \geq V_{IH,MIN}$; $CKE \geq V_{IH,MIN}$; $t_{RC} = t_{RAS,MAX}$; DQ, DM and DQS inputs changing twice per clock cycle; address and control inputs changing once per clock cycle.	I_{DD3N}
Operating Current Read one bank active; Burst Length = 2; reads; continuous burst; address and control inputs changing once per clock cycle; 50% of data outputs changing on every clock edge; CL = 2 for DDR266(A), CL = 3 for DDR333 and DDR400B; $I_{OUT} = 0$ mA	I_{DD4R}
Operating Current Write one bank active; Burst Length = 2; writes; continuous burst; address and control inputs changing once per clock cycle; 50% of data outputs changing on every clock edge; CL = 2 for DDR266(A), CL = 3 for DDR333 and DDR400B	I_{DD4W}
Auto-Refresh Current $t_{RC} = t_{RFCMIN}$, burst refresh	I_{DD5}
Self-Refresh Current $CKE \leq 0.2$ V; external clock on	I_{DD6}
Operating Current 7 four bank interleaving with Burst Length = 4; see component data sheet.	I_{DD7}



HYS64D[32/64]0x0EDL-[5/6]-D
Small Outline DDR SDRAM Modules

TABLE 10
 I_{DD} Specification for HYS64D64020EDL-[5/6]-D

Product Type	HYS64D64020EDL-5-D		HYS64D64020EDL-6-D		Unit	Note ¹⁾²⁾
	512MB		512MB			
	×64		×64			
	2 Ranks		2 Ranks			
	-5		-6			
Symbol	Typ.	Max.	Typ.	Max.		
I_{DD0}	228	294	196	258	mA	3)
I_{DD1}	260	330	224	290	mA	3)4)
I_{DD2P}	8	37	8	37	mA	5)
I_{DD2F}	176	240	160	216	mA	5)
I_{DD2Q}	120	176	112	160	mA	5)
I_{DD3P}	64	112	64	112	mA	5)
I_{DD3N}	232	296	208	272	mA	5)
I_{DD4R}	296	370	256	326	mA	3)4)
I_{DD4W}	284	358	248	314	mA	3)
I_{DD5}	496	602	444	522	mA	5)
I_{DD6}	12	32	12	32	mA	5)
I_{DD7}	712	870	600	686	mA	3)4)

1) Module I_{DD} values are calculated on the basis of component I_{DD} and can be measured differently according to DQ loading capacity.

2) Test condition for maximum values: $V_{DD} = 2.7\text{ V}$, $T_A = 10\text{ °C}$

3) The module I_{DDx} values are calculated from the I_{DDx} values of the component data sheet as follows:

$m \times I_{DDx}[\text{component}] + n \times I_{DD2P}[\text{component}]$ with **m** and **n** number of components of rank 1 and 2; **n=0** for 1 rank modules

4) DQ I/O (I_{DDQ}) currents are not included in the calculations (see note¹⁾)

5) The module I_{DDx} values are calculated from the component I_{DDx} data sheet values as: $(m + n) \times I_{DDx}[\text{component}]$



HYS64D[32/64]0x0EDL-[5/6]-D
Small Outline DDR SDRAM Modules

TABLE 11
 I_{DD} Specification for HYS64D32000EDL-[5/6]-D

Product Type	HYS64D32000EDL-5-D		HYS64D32000EDL-6-D		Unit	Note ¹⁾²⁾
	256MB	256MB	256MB	256MB		
	×64	×64	×64	×64		
	1 Rank	1 Rank	1 Rank	1 Rank		
	-5	-5	-6	-6		
Symbol	Typ.	Max.	Typ.	Max.		
I_{DD0}	224	276	192	240	mA	3)
I_{DD1}	256	312	220	272	mA	3)4)
I_{DD2P}	4	18	4	18	mA	5)
I_{DD2F}	88	120	80	108	mA	5)
I_{DD2Q}	60	88	56	80	mA	5)
I_{DD3P}	32	56	32	56	mA	5)
I_{DD3N}	116	148	104	136	mA	5)
I_{DD4R}	292	352	252	308	mA	3)4)
I_{DD4W}	280	340	244	296	mA	3)
I_{DD5}	492	584	440	504	mA	5)
I_{DD6}	6	16	6	16	mA	5)
I_{DD7}	708	852	596	668	mA	3)4)

1) Module I_{DD} values are calculated on the basis of component I_{DD} and can be measured differently according to DQ loading capacity.

2) Test condition for maximum values: $V_{DD} = 2.7\text{ V}$, $T_A = 10\text{ °C}$

3) The module I_{DDx} values are calculated from the I_{DDx} values of the component data sheet as follows:

$m \times I_{DDx}[\text{component}] + n \times I_{DD2P}[\text{component}]$ with **m** and **n** number of components of rank 1 and 2; **n=0** for 1 rank modules

4) DQ I/O (I_{DDQ}) currents are not included in the calculations (see note¹⁾)

5) The module I_{DDx} values are calculated from the component I_{DDx} data sheet values as: $(m + n) \times I_{DDx}[\text{component}]$



3.3 AC Characteristics

This chapter describes the AC characteristics.

TABLE 12
AC Timing - Absolute Specifications for PC3200 and PC2700

Parameter	Symbol	-5		-6		Unit	Note/ Test Condition ¹⁾
		DDR400B		DDR333			
		Min.	Max.	Min.	Max.		
DQ output access time from CK/ $\overline{\text{CK}}$	t_{AC}	-0.7	+0.7	-0.7	+0.7	ns	2)3)4)5)
CK high-level width	t_{CH}	0.45	0.55	0.45	0.55	t_{CK}	2)3)4)5)
Clock cycle time	t_{CK}	5	12	6	12	ns	CL = 3.0 2)3)4)5)
		6	12	6	12	ns	CL = 2.5 2)3)4)5)
		7	12	7.5	12	ns	CL = 2.0 2)3)4)5)
CK low-level width	t_{CL}	0.45	0.55	0.45	0.55	t_{CK}	2)3)4)5)
Auto precharge write recovery + precharge time	t_{DAL}	$(t_{WR}/t_{CK}) + (t_{RP}/t_{CK})$				t_{CK}	2)3)4)5)6)
DQ and DM input hold time	t_{DH}	0.4	—	0.45	—	ns	2)3)4)5)
DQ and DM input pulse width (each input)	t_{DIPW}	1.75	—	1.75	—	ns	2)3)4)5)6)
DQS output access time from CK/ $\overline{\text{CK}}$	t_{DQSCK}	-0.6	+0.6	-0.6	+0.6	ns	2)3)4)5)
DQS input low (high) pulse width (write cycle)	$t_{DQSL,H}$	0.35	—	0.35	—	t_{CK}	2)3)4)5)
DQS-DQ skew (DQS and associated DQ signals)	t_{DQSQ}	—	+0.40	—	+0.45	ns	TSOPII 2)3)4)5)
Write command to 1 st DQS latching transition	t_{DQSS}	0.72	1.25	0.75	1.25	t_{CK}	2)3)4)5)
DQ and DM input setup time	t_{DS}	0.4	—	0.45	—	ns	2)3)4)5)
DQS falling edge hold time from CK (write cycle)	t_{DSH}	0.2	—	0.2	—	t_{CK}	2)3)4)5)
DQS falling edge to CK setup time (write cycle)	t_{DSS}	0.2	—	0.2	—	t_{CK}	2)3)4)5)
Clock Half Period	t_{HP}	Min. (t_{CL}, t_{CH})	—	Min. (t_{CL}, t_{CH})	—	ns	2)3)4)5)
Data-out high-impedance time from CK/ $\overline{\text{CK}}$	t_{HZ}	—	+0.7	-0.7	+0.7	ns	2)3)4)5)7)
Address and control input hold time	t_{IH}	0.6	—	0.75	—	ns	Fast slew rate 3)4)5)6)10)
		0.7	—	0.8	—	ns	Slow slew rate 3)4)5)6)10)
Control and Addr. input pulse width (each input)	t_{IPW}	2.2	—	2.2	—	ns	2)3)4)5)8)



HYS64D[32/64]0x0EDL-[5/6]-D
Small Outline DDR SDRAM Modules

Parameter	Symbol	-5		-6		Unit	Note/ Test Condition ¹⁾
		DDR400B		DDR333			
		Min.	Max.	Min.	Max.		
Address and control input setup time	t_{IS}	0.6	—	0.75	—	ns	Fast slew rate 3)4)5)6)9)
		0.7	—	0.8	—	ns	Slow slew rate 3)4)5)6)10)
Data-out low-impedance time from $\overline{CK}/\overline{CK}$	t_{LZ}	-0.7	+0.7	-0.7	+0.7	ns	2)3)4)5)7)
Mode register set command cycle time	t_{MRD}	2	—	2	—	t_{CK}	2)3)4)5)
DQ/DQS output hold time	t_{QH}	$t_{HP} - t_{QHS}$	—	$t_{HP} - t_{QHS}$	—	ns	2)3)4)5)
Data hold skew factor	t_{QHS}	—	+0.50	—	+0.55	ns	TSOPII 2)3)4)5)
Active to Autoprecharge delay	t_{RAP}	t_{RCD}	—	t_{RCD}	—	ns	2)3)4)5)
Active to Precharge command	t_{RAS}	40	70E+3	42	70E+3	ns	2)3)4)5)
Active to Active/Auto-refresh command period	t_{RC}	55	—	60	—	ns	2)3)4)5)
Active to Read or Write delay	t_{RCD}	15	—	18	—	ns	2)3)4)5)
Average Periodic Refresh Interval	t_{REFI}	—	7.8	—	7.8	μ s	2)3)4)5)10)
Auto-refresh to Active/Auto-refresh command period	t_{RFC}	70	—	72	—	ns	2)3)4)5)
Precharge command period	t_{RP}	15	—	18	—	ns	2)3)4)5)
Read preamble	t_{RPRE}	0.9	1.1	0.9	1.1	t_{CK}	2)3)4)5)
Read postamble	t_{RPST}	0.40	0.60	0.40	0.60	t_{CK}	2)3)4)5)
Active bank A to Active bank B command	t_{RRD}	10	—	12	—	ns	2)3)4)5)
Write preamble	t_{WPRE}	0.25	—	0.25	—	t_{CK}	2)3)4)5)
Write preamble setup time	t_{WPRES}	0	—	0	—	ns	2)3)4)5)11)
Write postamble	t_{WPST}	0.40	0.60	0.40	0.60	t_{CK}	2)3)4)5)12)
Write recovery time	t_{WR}	15	—	15	—	ns	2)3)4)5)
Internal write to read command delay	t_{WTR}	2	—	1	—	t_{CK}	2)3)4)5)
Exit self-refresh to non-read command	t_{XSNR}	75	—	75	—	ns	2)3)4)5)
Exit self-refresh to read command	t_{XSRD}	200	—	200	—	t_{CK}	2)3)4)5)

- 1) $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$; $V_{DDQ} = 2.5\text{ V} \pm 0.2\text{ V}$, $V_{DD} = +2.5\text{ V} \pm 0.2\text{ V}$ (DDR333); $V_{DDQ} = 2.6\text{ V} \pm 0.1\text{ V}$, $V_{DD} = +2.6\text{ V} \pm 0.1\text{ V}$ (DDR400)
- 2) Input slew rate $\geq 1\text{ V/ns}$ for DDR400, DDR333
- 3) The $\overline{CK}/\overline{CK}$ input reference level (for timing reference to $\overline{CK}/\overline{CK}$) is the point at which \overline{CK} and \overline{CK} cross: the input reference level for signals other than $\overline{CK}/\overline{CK}$, is V_{REF} . $\overline{CK}/\overline{CK}$ slew rate are $\geq 1.0\text{ V/ns}$.
- 4) Inputs are not recognized as valid until V_{REF} stabilizes.
- 5) The Output timing reference level, as measured at the timing reference point indicated in AC Characteristics (note 3) is V_{TT} .
- 6) For each of the terms, if not already an integer, round to the next highest integer. t_{CK} is equal to the actual system clock cycle time.
- 7) t_{HZ} and t_{LZ} transitions occur in the same access time windows as valid data transitions. These parameters are not referred to a specific voltage level, but specify when the device is no longer driving (HZ), or begins driving (LZ).



HYS64D[32/64]0x0EDL-[5/6]-D
Small Outline DDR SDRAM Modules

- 8) These parameters guarantee device timing, but they are not necessarily tested on each device.
- 9) Fast slew rate ≥ 1.0 V/ns, slow slew rate ≥ 0.5 V/ns and < 1 V/ns for command/address and \overline{CK} & \overline{CK} slew rate > 1.0 V/ns, measured between $V_{OH(ac)}$ and $V_{OL(ac)}$.
- 10) A maximum of eight Autorefresh commands can be posted to any given DDR SDRAM device.
- 11) The specific requirement is that DQS be valid (HIGH, LOW, or some point on a valid transition) on or before this CK edge. A valid transition is defined as monotonic and meeting the input slew rate specifications of the device. When no writes were previously in progress on the bus, DQS will be transitioning from Hi-Z to logic LOW. If a previous write was in progress, DQS could be HIGH, LOW, or transitioning from HIGH to LOW at this time, depending on t_{DQSS} .
- 12) The maximum limit for this parameter is not a device limit. The device operates with a greater value for this parameter, but system performance (bus turnaround) degrades accordingly.



4 SPD Codes

This chapter lists all hexadecimal byte values stored in the EEPROM of the products described in this data sheet. SPD stands for serial presence detect. All values with XX in the table are module specific bytes which are defined during production.

List of SPD Code Tables

- Table 13 “HYS64D[32/64]3x0EDL-[5/6]-D” on Page 22

TABLE 13
HYS64D[32/64]3x0EDL-[5/6]-D

Product Type		HYS64D32000EDL-5-D	HYS64D32000EDL-6-D	HYS64D64020EDL-5-D	HYS64D64020EDL-6-D
Organization		256MB	256MB	512MB	512MB
		×64	×64	×64	×64
		1 Rank (×16)	1 Rank (×16)	2 Ranks (×16)	2 Ranks (×16)
Label Code		PC3200S-30331	PC2700S-25331	PC3200S-30331	PC2700S-25331
JEDEC SPD Revision		Rev. 1.0	Rev. 1.0	Rev. 1.0	Rev. 1.0
Byte#	Description	HEX	HEX	HEX	HEX
0	Programmed SPD Bytes in E2PROM	80	80	80	80
1	Total number of Bytes in E2PROM	08	08	08	08
2	Memory Type (DDR = 07h)	07	07	07	07
3	Number of Row Addresses	0D	0D	0D	0D
4	Number of Column Addresses	0A	0A	0A	0A
5	Number of DIMM Ranks	01	01	02	02
6	Data Width (LSB)	40	40	40	40
7	Data Width (MSB)	00	00	00	00
8	Interface Voltage Levels	04	04	04	04
9	t _{CK} @ CL _{max} (Byte 18) [ns]	50	60	50	60
10	t _{AC} SDRAM @ CL _{max} (Byte 18) [ns]	70	70	70	70
11	Error Correction Support	00	00	00	00
12	Refresh Rate	82	82	82	82
13	Primary SDRAM Width	10	10	10	10



HYS64D[32/64]0x0EDL-[5/6]-D
Small Outline DDR SDRAM Modules

Product Type		HYS64D32000EDL-5-D	HYS64D32000EDL-6-D	HYS64D64020EDL-5-D	HYS64D64020EDL-6-D
Organization		256MB	256MB	512MB	512MB
		×64	×64	×64	×64
		1 Rank (×16)	1 Rank (×16)	2 Ranks (×16)	2 Ranks (×16)
Label Code		PC3200S-30331	PC2700S-25331	PC3200S-30331	PC2700S-25331
JEDEC SPD Revision		Rev. 1.0	Rev. 1.0	Rev. 1.0	Rev. 1.0
Byte#	Description	HEX	HEX	HEX	HEX
14	Error Checking SDRAM Width	00	00	00	00
15	t _{CCD} [cycles]	01	01	01	01
16	Burst Length Supported	0E	0E	0E	0E
17	Number of Banks on SDRAM Device	04	04	04	04
18	CAS Latency	1C	0C	1C	0C
19	CS Latency	01	01	01	01
20	Write Latency	02	02	02	02
21	DIMM Attributes	20	20	20	20
22	Component Attributes	C1	C1	C1	C1
23	t _{CK} @ CL _{max} -0.5 (Byte 18) [ns]	60	75	60	75
24	t _{AC} SDRAM @ CL _{max} -0.5 [ns]	70	70	70	70
25	t _{CK} @ CL _{max} -1 (Byte 18) [ns]	75	00	75	00
26	t _{AC} SDRAM @ CL _{max} -1 [ns]	70	00	70	00
27	t _{RPmin} [ns]	3C	48	3C	48
28	t _{RRDmin} [ns]	28	30	28	30
29	t _{RCDmin} [ns]	3C	48	3C	48
30	t _{RASmin} [ns]	28	2A	28	2A
31	Module Density per Rank	40	40	40	40
32	t _{AS} , t _{CS} [ns]	60	75	60	75
33	t _{AH} , t _{CH} [ns]	60	75	60	75
34	t _{DS} [ns]	40	45	40	45
35	t _{DH} [ns]	40	45	40	45
36 - 40	Not used	00	00	00	00
41	t _{RCmin} [ns]	37	3C	37	3C
42	t _{RFCmin} [ns]	41	48	41	48



HYS64D[32/64]0x0EDL-[5/6]-D
Small Outline DDR SDRAM Modules

Product Type		HYS64D32000EDL-5-D	HYS64D32000EDL-6-D	HYS64D64020EDL-5-D	HYS64D64020EDL-6-D
Organization		256MB	256MB	512MB	512MB
		×64	×64	×64	×64
		1 Rank (×16)	1 Rank (×16)	2 Ranks (×16)	2 Ranks (×16)
Label Code		PC3200S-30331	PC2700S-25331	PC3200S-30331	PC2700S-25331
JEDEC SPD Revision		Rev. 1.0	Rev. 1.0	Rev. 1.0	Rev. 1.0
Byte#	Description	HEX	HEX	HEX	HEX
43	t _{CKmax} [ns]	28	30	28	30
44	t _{DQSQmax} [ns]	28	2D	28	2D
45	t _{QHSmax} [ns]	50	55	50	55
46	not used	00	00	00	00
47	DIMM PCB Height	01	01	01	01
48 - 61	Not used	00	00	00	00
62	SPD Revision	10	10	10	10
63	Checksum of Byte 0-62	76	1A	77	1B
64	Manufacturer's JEDEC ID Code (1)	7F	7F	7F	7F
65	Manufacturer's JEDEC ID Code (2)	7F	7F	7F	7F
66	Manufacturer's JEDEC ID Code (3)	7F	7F	7F	7F
67	Manufacturer's JEDEC ID Code (4)	7F	7F	7F	7F
68	Manufacturer's JEDEC ID Code (5)	7F	7F	7F	7F
69	Manufacturer's JEDEC ID Code (6)	51	51	51	51
70	Manufacturer's JEDEC ID Code (7)	00	00	00	00
71	Manufacturer's JEDEC ID Code (8)	00	00	00	00
72	Module Manufacturer Location	xx	xx	xx	xx
73	Part Number, Char 1	36	36	36	36
74	Part Number, Char 2	34	34	34	34
75	Part Number, Char 3	44	44	44	44
76	Part Number, Char 4	33	33	36	36
77	Part Number, Char 5	32	32	34	34
78	Part Number, Char 6	30	30	30	30
79	Part Number, Char 7	30	30	32	32
80	Part Number, Char 8	30	30	30	30



HYS64D[32/64]0x0EDL-[5/6]-D
Small Outline DDR SDRAM Modules


Product Type		HYS64D32000EDL-5-D	HYS64D32000EDL-6-D	HYS64D64020EDL-5-D	HYS64D64020EDL-6-D
Organization		256MB	256MB	512MB	512MB
		×64	×64	×64	×64
		1 Rank (×16)	1 Rank (×16)	2 Ranks (×16)	2 Ranks (×16)
Label Code		PC3200S-30331	PC2700S-25331	PC3200S-30331	PC2700S-25331
JEDEC SPD Revision		Rev. 1.0	Rev. 1.0	Rev. 1.0	Rev. 1.0
Byte#	Description	HEX	HEX	HEX	HEX
81	Part Number, Char 9	45	45	45	45
82	Part Number, Char 10	44	44	44	44
83	Part Number, Char 11	4C	4C	4C	4C
84	Part Number, Char 12	35	36	35	36
85	Part Number, Char 13	44	44	44	44
86	Part Number, Char 14	20	20	20	20
87	Part Number, Char 15	20	20	20	20
88	Part Number, Char 16	20	20	20	20
89	Part Number, Char 17	20	20	20	20
90	Part Number, Char 18	20	20	20	20
91	Module Revision Code	0x	0x	0x	0x
92	Test Program Revision Code	xx	xx	xx	xx
93	Module Manufacturing Date Year	xx	xx	xx	xx
94	Module Manufacturing Date Week	xx	xx	xx	xx
95 - 98	Module Serial Number	xx	xx	xx	xx
99 - 127	Not used	00	00	00	00



5 Package Outlines

This chapter contains the package outlines of the products.

FIGURE 2
Package Outline SO-DIMM Raw Card A (L-DIM-200-6)



Notes

1. Drawing according to ISO 8015
2. Dimensions in mm
3. General tolerances ± 0.15



Table of Contents

1	Overview	3
1.1	Features	3
1.2	Description	3
2	Pin Configuration	5
2.1	Pin Configuration	5
3	Electrical Characteristics	14
3.1	Operating Conditions	14
3.2	Current Specification and Conditions	16
3.3	AC Characteristics	19
4	SPD Codes	22
5	Package Outlines	26
	Table of Contents	28

Edition 2008-05

Published by Qimonda AG
Gustav-Heinemann-Ring 212
D-81739 München, Germany
© Qimonda AG 2008.
All Rights Reserved.

Legal Disclaimer

THE INFORMATION GIVEN IN THIS INTERNET DATA SHEET SHALL IN NO EVENT BE REGARDED AS A GUARANTEE OF CONDITIONS OR CHARACTERISTICS. WITH RESPECT TO ANY EXAMPLES OR HINTS GIVEN HEREIN, ANY TYPICAL VALUES STATED HEREIN AND/OR ANY INFORMATION REGARDING THE APPLICATION OF THE DEVICE, QIMONDA HEREBY DISCLAIMS ANY AND ALL WARRANTIES AND LIABILITIES OF ANY KIND, INCLUDING WITHOUT LIMITATION WARRANTIES OF NON-INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS OF ANY THIRD PARTY.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Qimonda Office.

Warnings

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Qimonda Office.

Qimonda Components may only be used in life-support devices or systems with the express written approval of Qimonda, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

www.qimonda.com