

DIMENSIONS (mm)

Pins: Ø0.65 mm
 L = 3.2±0.3 mm
 Material: Cu-alloy tinned

LAYOUT
 pitch 2.54 mm/Top view

MARKING

MEDER-Label
 Type/Layout
 Production code,
 EN60062/Factory code

Test Circuit

Coil Data at 20 °C	Conditions	Min	Typ	Max	Unit
Coil resistance		270	300	330	Ohm
Coil voltage			5		VDC
Rated power			83		mW
Coil current			17		A
Pull-In voltage				3,8	VDC
Drop-Out voltage		0,4			VDC

Contact Data 85	Conditions	Min	Typ	Max	Unit
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			100	W
Switching voltage	DC or Peak AC			1.000	V
Switching current	DC or Peak AC			1	A
Carry current	DC or Peak AC 100% Duty Cycle			2,5	A
Contact resistance static	Measured with 40% overdrive			150	mOhm
Insulation resistance	RH <45 %, 100 V test voltage	10			TOhm
Breakdown voltage (<20 AT)		1,5			kV DC
Operate time incl. bounce	measured with 40% overdrive			1,1	ms
Release time	measured with no coil excitation			0,1	ms
Capacitance	@ 10 kHz across open switch		0,5		pF

Special Product Data	Conditions	Min	Typ	Max	Unit
Number of contacts				2	
Contact - form				A - NO	
Thermal Offset Voltage				1	µV
Case colour				blue	
Housing material				Metal DT4E	
Sealing compound				Polyurethan	
Connection pins				cu-alloy tinned	
Magnetic Shield				yes	
RoHS conformity				yes	



Products for tomorrow...

Europe: +49 / 7731 8399 0 | Email: info@meder.com
USA: +1 / 508 295 0771 | Email: salesusa@meder.com
Asia: +852 / 2955 1682 | Email: salesasia@meder.com

Item No.:
8805285800
Item:
BTS05-2A85

Environmental data	Conditions	Min	Typ	Max	Unit
Shock	1/2 sine wave duration 11ms			50	g
Vibration	from 10 - 2000 Hz			20	g
Operating temperature		-20		70	°C
Storage temperature		-35		105	°C
Soldering temperature	wave soldering max. 5 sec.			260	°C
Washability		fully sealed			

General data	Conditions	Min	Typ	Max	Unit
Packaging		VPE			

Modifications in the sense of technical progress are reserved

Designed at: 25.02.09 Designed by: WKOVACS

Approval at: 04.03.09 Approval by: KOLBRICH

Last Change at: 04.09.09 Last Change by: KSCHIELENSKI

Approval at: 23.11.09 Approval by: KOLBRICH

Version: 03