




192 x 32 Graphic LCD



MECHANICAL DATA					
ITEM	STANDARD VALUE	UNIT			
Module Dimension	116.0 x 37.0				
Viewing Area	84.0 x 18.6				
Dot Size	0.38 x 0.46				
Dot Pitch	0.42 x 0.50	mm			
Mounting Hole	108.0 x 29.0				
Character Size	N/a				

FEATURES

• Type: Graphic

Display format: 192 x 32 dotsBuilt-in controller: ST7920

Duty cycle: 1/32+ 5 V power supply

• LED can be driver by PIN 15, PIN 16

· Chinese version

• Compliant to RoHS directive 2002/95/EC



ABSOLUTE MAXIMUM RATINGS							
ITEM	SYMBOL	STAN	UNIT				
I I EIVI	STIVIBOL	MIN.	TYP.	MAX.	UNIT		
Power Supply	V_{DD} to V_{SS}	4.75	5.0	5.25	V		
Input Voltage	VI	0	-	V_{DD}	V		

Note

• $V_{SS} = 0 \text{ V}, V_{DD} = 5.0 \text{ V}$

ELECTRICAL CHARACTERISTICS								
ITEM	OVMBOL	COMPITION	STANDARD VALUE					
ITEM	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT		
Innut Valtage	V _{DD}	L level	L level 0.7 V _{DD} - \		V_{DD}	V		
Input Voltage	V _{IO}	H level	0	-	0.3 V _{DD}	v		
Supply Current	I _{DD}	V _{DD} = + 5 V	-	2.0	-	mA		
Recommended LC Driving Voltage for Normal Temperature Version Module	V _{DD} to V ₀	- 20 °C	-	-	5.2			
		0 °C	-	-	4.8	V		
		25 °C	-	4.5	-			
		50 °C	4.7	-	-			
		70 °C	3.8	-	-			
LED Forward Voltage	V _F	25 °C	-	4.2	4.6	V		
LED Forward Current	I _F	25 °C	-	210	420	mA		
EL Power Supply Current	I _{EL}	V _{EL} = 110 V _{AC} , 400 Hz	-	-	-	mA		

OPTIONS									
PROCESS COLOR				BACKLIGHT					
TN	STN Gray	STN Yellow	STN Blue	FSTN B&W	STN Color	None	LED	EL	CCFL
	х	х	Х	х		х	х	х	


For detailed information, please see the "Product Numbering System" document.

Document Number: 37362 Revision: 30-Mar-09

192 x 32 Graphic LCD



INTERFACE PIN FUNCTION						
PIN NO.	SYMBOL	FUNCTION				
1	V _{SS}	Ground				
2	V _{DD}	Power supply for logic				
3	V ₀	NC				
4	RS	Register select signal				
5	R/W	H/L read/write signal				
6	E	H → L enable signal				
7	DB0	Data bus line				
8	DB1	Data bus line				
9	DB2	Data bus line				
10	DB3	Data bus line				
11	DB4	Data bus line				
12	DB5	Data bus line				
13	DB6	Data bus line				
14	DB7	Data bus line				
15	A	Power supply for B/L				
16	К	Power supply for B/L				





Vishay

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Revision: 18-Jul-08

Document Number: 91000 www.vishay.com