


8 x 2 Character LCD



FEATURES

- Type: Character
- Display format: 8 x 2 characters
- Built-in controller: KS 0066 (or equivalent)
- Duty cycle: 1/16
- 5 x 8 dots includes cursor
- + 5 V power supply
- EL inverter built-in optional
- Compliant to RoHS directive 2002/95/EC


RoHS
COMPLIANT

| MECHANICAL DATA | | |
|------------------|----------------|------|
| ITEM | STANDARD VALUE | UNIT |
| Module Dimension | 56.0 x 24.0 | mm |
| Viewing Area | 31.6 x 15.1 | |
| Dot Size | 0.56 x 0.57 | |
| Dot Pitch | 0.61 x 0.62 | |
| Mounting Hole | 50.0 x 18.0 | |
| Character Size | 4.91 x 3.0 | |

| ABSOLUTE MAXIMUM RATINGS | | | | | |
|--------------------------|----------------------|----------------|------|----------|------|
| ITEM | SYMBOL | STANDARD VALUE | | | UNIT |
| | | MIN. | TYP. | MAX. | |
| Power Supply | V_{DD} to V_{SS} | - | 5.0 | 5.5 | V |
| Input Voltage | V_I | - 0.3 | - | V_{DD} | |

Note

- $V_{SS} = 0$ V, $V_{DD} = 5.0$ V


| ELECTRICAL CHARACTERISTICS | | | | | | |
|--|-------------------|-----------------|----------------|------|------|------|
| ITEM | SYMBOL | CONDITION | STANDARD VALUE | | | UNIT |
| | | | MIN. | TYP. | MAX. | |
| Input Voltage | V_{DD} | $V_{DD} = +5$ V | - | - | - | V |
| Supply Current | I_{DD} | $V_{DD} = +5$ V | - | - | - | mA |
| Recommended LC Driving Voltage for Normal Temperature Version Module | V_{DD} to V_0 | - 20 °C | - | - | 5.5 | V |
| | | 0 °C | - | - | 4.8 | |
| | | 25 °C | - | 4.5 | - | |
| | | 50 °C | 4.2 | - | - | |
| | | 70 °C | 3.8 | - | - | |

| OPTIONS | | | | | | | | | |
|---------------|----------|------------|----------|----------|-----------|-----------|-----|----|------|
| PROCESS COLOR | | | | | | BACKLIGHT | | | |
| TN | STN Gray | STN Yellow | STN Blue | FSTN B&W | STN Color | None | LED | EL | CCFL |
| x | x | x | | | | x | | x | |

For detailed information, please see the "Product Numbering System" document.

| DISPLAY CHARACTER ADDRESS CODE | | | | | | | | |
|--------------------------------|----|----|----|----|----|----|----|----|
| Display Position | | | | | | | | |
| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
| DD RAM Address | 00 | 01 | 02 | 03 | 04 | 05 | 06 | 07 |
| DD RAM Address | 40 | 41 | 42 | 43 | 44 | 45 | 46 | 47 |

| INTERFACE PIN FUNCTION | | |
|------------------------|-----------------|-------------------------------|
| PIN NO. | SYMBOL | FUNCTION |
| 1 | V _{SS} | Ground |
| 2 | V _{DD} | Power supply for logic |
| 3 | V ₀ | Operating voltage LCD driving |
| 4 | RS | Register select signal |
| 5 | R/W | H/L read/write signal |
| 6 | E | H → L enable signal |
| 7 | DB4 | Data bus line |
| 8 | DB5 | Data bus line |
| 9 | DB6 | Data bus line |
| 10 | DB7 | Data bus line |
| 11 | K | Power supply for B/L |
| 12 | K | Power supply for B/L |
| 13 | A | Power supply for B/L |
| 14 | A | Power supply for B/L |
| 15 | BLE | H: EL enable/L: EL disable |
| 16 | NC | No connection |
| 17 | DB0 | Data bus line |
| 18 | DB1 | Data bus line |
| 19 | DB2 | Data bus line |
| 20 | DB3 | Data bus line |





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.