




RoHS

COMPLIANT

320 x 240 Graphic LCD



MECHANICAL DATA					
ITEM	STANDARD VALUE	UNIT			
Module Dimension	94.7 x 71.7				
Viewing Area	81.4 x 61.0				
Dot Size	0.225 x 0.225				
Dot Pitch	0.24 x 0.24	mm			
Mounting Hole	85.3 x 83.3				
Character Size	N/a				

FEATURES

- Type: Graphic
- Display format: 320 x 240 dots (FSTN)
- Built-in controller: None
- Duty cycle: 1/240
- Built-in P/V output
- 4-bit data bus
- 3.3 V power supply (also available for + 5 V)
- Compliant to RoHS directive 2002/95/EC

ABSOLUTE MAXIMUM RATINGS							
ITEM	SYMBOL	STAN	UNIT				
	STMBOL	MIN.	TYP.	MAX.			
Power Supply	V V _{DD} to V _{SS} 3.0 3.3		3.5	v			
Input Voltage	VI	$0.8 V_{DD}$	-	V_{DD}	V		

ELECTRICAL CHARACTERISTICS							
	SYMBOL	CONDITION	ST	STANDARD VALUE			
ITEM	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT	
	V _{DD}	L level	0.8 V _{DD}	-	V _{DD}	v	
Input Voltage	V _{IO}	H level	V _{SS}	-	0.2 V _{DD}	Ň	
Supply Current	I _{DD}	$V_{DD} = + 3.5 V$	-	1.3	-	mA	
Recommended LC Driving Voltage for Normal Temperature Version Module		- 20 °C	-	-	-		
		0°C	-	-	-		
	V_0 to V_{SS}	25 °C	-	18.7	-	V	
		50 °C	-	-	-		
		70 °C	-	-	-		


OPTIONS									
PROCESS COLOR					BACKLIGHT				
TN	STN Gray	STN Yellow	STN Blue	FSTN B&W	STN Color	None	LED	EL	CCFL
				х		х	х	х	

For detailed information, please see the "Product Numbering System" document.

Document Number: 37397 Revision: 16-Mar-09 Vishay



INTERFACE PIN FUNCTION					
PIN NO.	SYMBOL	FUNCTION			
1	CP	Data latch			
2	LP	Data shift			
3	FLM	Scan start-up signal			
4	М	Control signal for AC driving			
5	D0	Date bus line			
6	D1	Date bus line			
7	D2	Date bus line			
8	D3	Date bus line			
9	V _{LCD}	Power supply for LCD			
10	V _{CC}	Power supply for logic			
11	V _{SS}	Ground			
12	BLE	H: EL enable/L: EL disable			
13	К	Power supply for B/L			
14	A	Power supply for B/L			
15	DISP	Display enable signal			
16	V _{EE} /FR	Frame			





Vishay

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.