



Coil Data at 20 °C	Conditions	Min	Typ	Max	Unit
Coil resistance		1.700	1.900	2.100	Ohm
Coil voltage			24		VDC
Rated power			303		mW
Thermal Resistance			26		K/W
Pull-In voltage				18	VDC
Drop-Out voltage		3,5			VDC

Contact data 16	Conditions	Min	Typ	Max	Unit
Contact-form					
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			250	W
Switching voltage	DC or Peak AC			250	VDC/VAC
Switching current	DC or Peak AC			1,5	A
Carry current	DC or Peak AC				A
Contact resistance static	Measured with 40% overdrive Start value			80	mOhm
Insulation resistance	RH <45 %, 100 V test Voltage				Ohm
Breakdown voltage	according to IEC 255-5	800			VDC
Operate time incl. bounce	measured with 40% overdrive			4	ms
Release time	measured with no coil excitation			0,2	ms
Capacity	@ 10 kHz across open switch		0,8		pF

Special Product Data	Conditions	Min	Typ	Max	Unit
Insulation resistance Coil/Contact	RH <45%, 200 VDC test voltage	1.000			GOhm
Dielectric Strength Coil/Contact	according to IEC 255-5	6			kV AC
Housing material			Polycarbonat		
Sealing compound			Polyurethan		
Connection pins			Copper alloy tin plated		
Number of contacts			1		



*Products for tomorrow...*

Europe: +49 / 7731 8399 0 | Email: info@meder.com  
USA: +1 / 508 295 0771 | Email: salesusa@meder.com  
Asia: +852 / 2955 1682 | Email: salesasia@meder.com

Item No.:  
**8524116000**  
Item:  
**HE24-1A16**

Environmental data	Conditions	Min	Typ	Max	Unit
Shock	1/2 sine wave duration 11ms			50	g
Vibration	from 10 - 2000 Hz			20	g
Operating temperature		-20		70	°C
Storage temperature		-35		105	°C
Soldering temperature	wave soldering max. 5 sec.			260	°C
Washability		fully sealed			

Modifications in the sense of technical progress are reserved

Designed at: 29.06.09    Designed by: WKOVACS  
Last Change at:            Last Change by:

Approval at: 29.06.09    Approval by: KOLBRICH  
Approval at:            Approval by:

Version: 01